

Cole-Parmer[®] Stuart[™] Digital Melting Point - MP-200D, MP-200D-HR

- Two samples can be tested simultaneously
- Samples viewed via a magnifying lens with clear observation aided by built in illumination
- Extendible back feet allow the unit to be operated at the optimum viewing angle
- Full access to the block aids cleaning
- The unit then heats at a fixed rate of 2°C per minute for the MP-200D and at a user selected rate of between 1 and 10°C per minute for the MP-200D-HR
- 8GB on-board storage is included, which should comfortably hold approximately 300 melt files





Cole-Parmer® Stuart™ Digital Melting Point - MP-200D, MP-200D-HR

The MP-200D and MP-200D-HR have been designed with safety and ease of operation in mind making it ideal for use in education. The temperature is selected, measured and displayed digitally making it accurate and negating the need for a thermometer. The MP-200D displays temperature to 1 degree resolution while the more advanced MP-200D-HR has a 0.1 degree resolution as well as a variable ramp rate and hold key so that the exact melt temperature can be recorded.

Technical Specification

| Specification | MP-200D | MP-200D-HR |
|---------------------------|---|---|
| Melting point method | Digital | Digital |
| No of samples | 2 | 2 |
| Temperature range | Ambient to 300°C | Ambient to 300°C |
| Temperature resolution | 1°C | 0.1°C |
| Display | Three digit LED | Four digit LED |
| Ramp rate | 20°C per minute plateau 2°C per minute to melt | 20°C per minute plateau variable between 1-10°C per minute to melt |
| Temperature sensor | PT100 Platinum resistance | PT100 Platinum resistance |
| Memory | No | No |
| Accessory printer | No | No |
| Date/time display | No | No |
| Cool down time 350-50°C | 40 mins (300-50°C) | 40 mins (300-50°C) |
| Heat up time 50-350°C | 15mins | 15mins |
| Electrical supply | 230V, 50Hz, 50W | 230V, 50Hz, 50W |
| Onboard capillary storage | No | No |
| In-built glass cutter | No | No |
| Language variants | English, German, French, Spanish | English, German, French, Spanish |
| Temperature units | °C | °C |
| Dimensions h x d x w | 170 x 220 x 160 | 170 x 220 x 160 |
| Net weight (kg) | 1.8 | 1.8 |

Ordering Information

| Description | Ordering Number | Series No. | Model No. | Legacy Sku. |
|---|-----------------|------------|----------------|---------------|
| Analogue melting point apparatus, complete with thermometer and pack of 100 open ended melting point tubes | 03011-41 | MP-200 | MP-200D | SMP10 |
| Digital melting point apparatus, 1°C resolution, complete with pack of 100 melting point tubes, closed at one end | 03011-47 | MP-200 | MP-200D-HR | SMP20 |
| Analogue melting point apparatus, complete with thermometer and pack of 100 open ended melting point tubes | 03011-40 | MP-200 | MP-200D-120 | SMP10/120V/60 |
| Digital melting point apparatus, 1°C resolution, complete with pack of 100 melting point tubes, closed at one end | 03011-45 | MP-200 | MP-200D-HR-120 | SMP20/120V/60 |
| Glass melting point tubes, closed ends, pack of 100 | 03013-65 | MP-200 | N/A | SMP2/1 |
| Glass melting point tubes, closed at one end, pack of 100 | 03013-64 | MP-200 | N/A | SMP10/1 |

coleparmer.com

USA:
+1.800.323.4340
+1.847.549.7600

Canada: +1.800.363.5900
China: +86.21.5109.9909
France: +33 (0) 1486 37800
Germany: +49 (0) 9377 92030

India: +1.800.266.1244
Italy: +39 (0) 1313 89513
UK: +44 (0) 1480 272279
All other countries: +1.847.549.7600

Cole-Parmer®
essentials

an antylia scientific company

Find out more at antylia.com