

Whatman™ GD/X non-sterile nylon syringe filters

High-viscosity filters suitable for challenging samples, such as environmental or food analysis. Biobased plastic options available in the 25 mm size.

Overview

The Whatman™ GD/X non-sterile, nylon membrane syringe filters are designed to enable the filtration of viscous, hard-to-filter samples greater than 10 mL. They combine a polypropylene housing, high-efficiency Whatman™ GMF 150 and GF/F pre-filter media, and a nylon membrane.

- Reduces need for multiple syringe filters by processing three to seven times more sample volume than syringe filters without prefilters
- Female luer lock for leak-free connections
- High-efficiency Whatman GMF 150 and GF/F pre-filter media
- Eliminates or greatly reduces the need to carry out separate prefiltration step for difficult-to-filter samples

High viscosity filter enables filtration of “difficult-to-filter” samples

The prefilter contains a high-efficiency borosilicate glass filtration stack that will retain fine particles down to 0.7 µm, allowing difficult sample filtration with less hand force. It reduces the need for multiple syringe filters by processing three to seven times more sample volume than syringe filters without prefilters. The filters can be autoclaved.

ISCC+ certified Biobased polypropylene housing (25mm devices):

- 90% Biobased plastic resin.
- Biobased plastic resin is ISCC Plus certified using Mass Balance approach.
- The polypropylene accounts for 95% of the weight/composition of the syringe filters.

Read more on the topic here.

DOMINIQUE DUTSCHER SAS

About nylon membranes

Nylon membrane is hydrophilic and can be used for aqueous and aqueous-organic samples. The membrane offers chemical resistance to most common HPLC solvents. However, it has limited resistance to acids, bases, halogenated hydrocarbons, aldehydes, and strong oxidizing agents. The most common application is HPLC sample filtration.

Product specifications
Whatman GD/X™ non-sterile nylon syringe filter, 25mm, 5 µm (150/Pk)

Catalog code	6870-2550
Biobased	Yes
Diameter	25 mm
Effective filtration area	4.6 cm²
Filter media	Nylon
Hold-up volume	< 250 µL
Housing material	Polypropylene (PP)
Inlet connector	Female luer lok
Pore size	5 µm
Pack size	150/Pk
Sample volume	< 100 mL
Sterile	No

DOMINIQUE DUTSCHER SAS