

DOMINIQUE DUTSCHER SAS

Whatman™ Puradisc™ sterile PES syringe filters

Sterile PES membrane syringe filters combine premium quality with economic efficiency. Biobased plastic options available in the 25 mm size.

Overview

Whatman™ Puradisc™ sterile syringe filters with polyethersulfone (PES) membrane combine premium quality with economic efficiency.

- 13 and 25 mm syringe filter diameter to suit sample volume
- Range of pore sizes for retaining a variety of particles
- Non-sterile PES version available

Hydrophilic PES membranes are designed for stability in low pH, have low levels of extractables, and exhibit low protein binding, making them suitable for many aqueous and organic solvents. PES membranes allow higher liquid flow than either PTFE or PVDF.

Whatman™ Puradisc™ is available in the following membrane materials: regenerated cellulose (RC), cellulose nitrate, nylon, polytetrafluoroethylene (PTFE), polyethersulfone (PES), polyvinylidene difluoride (PVDF), and cellulose acetate.

Cytiva also offers high-performance GD/X syringe filters with a multi-layer glass fiber prefilter for filtering larger volumes of harder-to-filter samples.

ISCC+ certified Biobased polypropylene housing (25mm devices):

- 90% Biobased plastic resin.
- Biobased plastic resin is ISCC Plus certified using Mass Balance approach.
- The polypropylene accounts for 95% of the weight/composition of the syringe filters.

Read more on the topic here.

Disclaimer

Lab filtration products are intended for professional laboratory use only and are not suitable for medical, clinical, surgical, patient protection applications, cGMP manufacturing, or production. For assistance with product selection, please contact our scientific support team.

Product specifications
Whatman™ Puradisc™ sterile PES syringe filter, 13 mm, 0.2 µm (50/Pk)

Catalog code	6780-1302
Biobased	No
Diameter	13 mm
Effective filtration area	1.3 cm²
Filter media	Hydrophilic polyethersulfone (PES)
Housing material	Polypropylene (PP)
Inlet connector	Female luer lok
Pack size	50/Pk
Pore size	0.2 µm
Sample volume	< 10 mL
Sterile	Yes
Hold-up volume	≤ 25 µL

DOMINIQUE DUTSCHER SAS