Technical Data Sheet

Edition Date: 2014-12-11
Revision Date: 2019-10-23
Revised by: Annette Roy, QA Coordinator

Product Name: Septum Screw Caps for Micrewtube®	Catalogue No.: T347AQX
This document replaces any previous version	

1. Product Description:

- **Septum Screw Caps for Micrewtube®:** Non-sterile, disposable with a pierceable septum

2. Packaging:

- **Case:** 250 units per package

3. Product Specifications:

- Material:
  - Polypropylene cap
  - Silicone and Teflon septum
- Temperature Range: -80^{O} to 121^{O}C. Autoclavable at 121°C, for up to 30 minutes
- The Cap incorporates a pierceable septum
- The septum is pierceable with pipet tip or syringe needle

4. Standards and Conformity:

- **ISO 2859-1:** Sampling and inspection procedures
- **FDA:** Resin conforms to FDA 21 CFR 177.1520
- **CONEG:** Plastics and colorants are in conformity with CONEG standards for heavy metals

5. Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Dimension measurements
- Closure verification

DOMINIQUE DUTSCHER SAS

6. Traceability:

- **Lot No. Composition:** 8 to 9 digits

- **The lot number can be found in one or all of these locations:**

  1. On exterior case label
  2. On label inserted inside the master case
  3. On the inner bag

7. Storage Conditions:

- Store at room temperature in normal warehouse conditions
- Avoid temperature variations and humidity
- Protect from any possible contamination

8. Recommended Use:

- Verify proper cap closure when using biohazard material and / or chemical reagents
- Follow chemical resistance chart recommendations

***OWNERSHIP OF MATERIALS**:*

*Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.*

DOMINIQUE DUTSCHER SAS