Technical Data Sheet

Edition Date: 2013-08-21
Revision Date : 2021-10-26
Revised by: Annette Roy, Regulatory

Product Name: Septum Screw Caps	**Catalogue No.: T504AQX**
This document replaces any previous version	

1. Product Description:

- **Septum Screw Caps:** Disposable, non-sterile cap with pierceable septum for external threaded sample tubes

- **Compatible with:**
  - T501 Sample Tubes

2. Packaging:

- **Case:** 250 units per package

3. Product Specifications:

- Material:
  - Cap: Polypropylene
  - Septum top: Teflon
  - Septum inner liner: Silicone
- Temperature range: -80°C to +121°C
- Autoclavable at 121°C, for up to 30 minutes

4. Standards and Conformity:

- **ISO 2859-1:** Sampling and inspection procedures
- **LATEX:** Material is Latex Free
- **BSE / TSE:** Material is BSE / TSE Free

Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Dimension measurements
- Closure verification

DOMINIQUE DUTSCHER SAS

5. Traceability:

- **Lot No. Composition:** 8 or 9 digits

- **The lot number can be found in one or all of these locations:**

1. On exterior case label
2. On label inserted inside the master case
3. On the inner bag

6. Storage Conditions:

- Store at room temperature in normal warehouse conditions
- Protect from any damage to the packaging

7. Recommended Use:

- Follow chemical resistance chart recommendations
- For use in automated equipment, follow the equipment manufacturer's instructions

***OWNERSHIP OF MATERIALS**:*

*Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.*

DOMINIQUE DUTSCHER SAS