AF43C

Sicherheitsschrank mit Filtration - Hoch 2 Türen - 3 Innenfächer

ÜBEREINSTIMMUNG

CE



ADVANTAGES

- CE certified
- NF X 15-211 compliant
- Storage of flammables, corrosives and toxics

SONDERN AUCH...

- Perforated shelves
- Lighting control allowing to survey the proper working of the fan
- Front control window to see immediately the filter
- Active coal filters adsorption capacity and filtration system certified NF X 15-211
- Compliant to the Public Health Code articles R. 5132-66 and R. 5132-68
- Konform INRS Empfehlungen
- Available with different configurations : 1, 2, 3 or 4 compartments
- Active coal filter tested to the standard NF X 15-211
- Easy replacement of the active coal filter
- Normalized labelling provided with the equipment
- No modification of building's structure required
- Fan in compliance with CE specifications

TECHNISCHE DATEN

Referenz	**AF43C**	Verriegelung der Türen	**handbetätigt**
Übereinstimmung	**CE**	Versandabmessungen HxBxT (mm)	**2150 x 1200 x 800**
Baustoffe der Sicherheitschränke	**Stahl 15/10**	Belüftung	**lateral zuluftöffnung und abluftöffnung auf dem dach**
Türfarbe	**weiß RAL 9010**	Anzahl der Abteile / Fächer	**3**
Anzahl der Türen	**2**	Auffangwanne	**3**
Art der Türen	**flügeltüren**	Codenummer	**94032080**
Scharniere	**rechts und links**		

PRODUITS COMPLÉMENTAIRES

- Aktivkohlefilter für organische und korrosive Dämpfe - for cabinets range 12.X since 2008 (Réf : CORG301)
- Aktivkohlefilter für Formaldehyd Dämpfe - for cabinets range 12.X since 2008 (Réf : FOR300)
- Aktivkohlefilter für organische Dämpfe - for cabinets range 12.X since 2008 (Réf : ORG300)

OPTIONS

- Halb-perforiert Regal für Serie 12.X (Réf : ESAF2-2X)
- Perforiert Regal für Serie 12.X (Réf : ESAF2X)

Referenz	Äußere Abmessungen HxBxT (mm)	Innere Abmessungen HxBxT (mm)	Gewicht (Kg)
AF43C	1950 x 1600 x 545	1660 x (1 x)780+(2 x)380 x 500	285.00

DOMINIQUE DUTSCHER SAS

TRIONYX
1er FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr