Hoja de Datos

Mezclar / Agitadores Magnéticos



lab disc white

Ultra-flat compact magnetic stirrer, guaranteed with modern magnet coil technology. Wear-free drive with no moving parts. To ensure better mixing, the lab disc can reverse direction of rotation automatically every 30 seconds.
- High IP protection class (IP 65)
- Set-up plate and casing made from chemically resistant materials
- Slip-proof, safe stand

Accesorios: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse

Información Técnica	
Número de puestos de agitación	1
Max. cantidad a agitar (H2O) [l]	0.8
Potencia del suministro del motor [W]	3
Rango de velocidad [rpm]	15 - 1500
Longitud max. varilla magnética [mm]	25
Material de la superficie de la placa	poliester
Dimensiones de la superficie de la placa [mm]	Ø 100
Dimensiones (An x Al x Pr) [mm]	117 x 12 x 180
Peso [kg]	0.3
Temperatura ambiental permitida [°C]	5 - 40
Humedad relativa permitida [%]	80
Clase de protección de acuerdo al DIN EN 60529	IP 65
Voltaje [V]	100 - 240
Frecuencia [Hz]	50/60
Consumo de energia [W]	5
No. ref.	**0003907500**

© IKA® Werke Staufen/Germany 2017 www.ika.com
Sujeto a modificaciones ténicas

DUNIQUE DUTSCHER SAS

PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE Extractor de varillas agitadoras, BC 1000 Tapa para Beaker

DOMINIQUE DUTSCHER SAS

© IKA® Werke Staufen/Germany 2017 www.ika.com
Sujeto a modificaciones ténicas