CAPP Aero 96

MULTICHANNEL PIPETTES

The CAPPAero96 multichannel pipette combines the accuracy and precision of a single-channel pipette across all channels with ergonomic aspects that minimise thumb strain, a common cause of repetitive stress injuries during multichannel pipetting.

Features

- External ejection lever reduces thumb strain for easier tip mounting and ejection
- Double O-rings ensure tip placement on nose cone requires only light pressure
- Lightweight ergonomic construction
- Robust design through aluminium and metal tip cones
- Stainless steel pistons ensure stability and a constantly reliable, precise performance
- Colour-coded pipette counter for quick selection of the right volume for liquid transfer
- Interchangeable fixed and variable counter-mechanism
- Fully autoclavable pipette body, except volume knob
- Easy volume control through volume controller that requires 50% fewer turns
- Lockable volume controller
- Display is fully visible during hand-held operations



DoubleSafe O-rings | Interchangeable knobs | Fully Autoclavable | 3 YEAR Warranty

Ordering Information

CAPPAero 96 Multichannel Pipettes - Variable Volume

Cat. No.	Channel	Volume	Increments	Inaccuracy %	Imprecision %	Colour
C10-8	8	0.5-10 µL	0.1 µl	5.00 /2.00	3.60 /1.00	○
C20-8	8	2-20 µL	0.2 µL	5.00 /2.00	3.60 /1.00	●
C50-8	8	5-50 µL	0.5 µL	3.20 /1.40	1.60 /0.60	●
C100-8	8	10-100 µL	1.0 µL	2.50 /1.30	1.20 /0.50	●
C200-8	8	20-200 µL	2.0 µL	1.80 /1.20	0.80 /0.40	●
C300-8	8	30-300 µL	2.0 µL	1.66 /1.40	0.60 /0.30	●
C10-12	12	0.5-10 µL	0.1 µl	5.00 /2.00	3.60 /1.00	○
C20-12	12	2-20 µL	0.2 µL	5.00 /2.00	3.60 /1.00	●
C50-12	12	5-50 µL	0.5 µL	3.20 /1.40	1.60 /0.60	●
C100-12	12	10-100 µL	1.0 µL	2.50 /1.30	1.20 /0.50	●
C200-12	12	20-200 µL	2.0 µL	1.80 /1.20	0.80 /0.40	●
C300-12	12	30-300 µL	2.0 µL	1.66 /1.40	0.60 /0.30	●

DOMINIQUE DUTSCHER SAS