Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description

6

Catalog Number: 3340

Product Description: Coming ® 96-well, Corning ® CellBIND® surface, black plate with clear flat bottom,

with low evaporation lid

Component Materials:

Plate walls - Medium Impact Polystyrene, meets USP, Class VI requirements for plastic containers

and closures. Black concentrate

Plate bottom - Virgin Polystyrene, meets *USP, Class VI* requirements for plastic containers and

closures.

Lid - Virgin Polystyrene, meets *USP, Class VI* requirements for plastic containers and

closures.

Product Dimensions:

Length of Plate - 5.030 in. Diameter of Well @ top - .270 in. Width of Plate - 3.365 in. Diameter of Well @ - .250 in.

bottom

Depth of Well - .420 in. Height with Lid - .650 in. Tolerances of - +/- .010 in. Volume per Well - .36 mL

Dimensions

Sterilization:

This lot has been irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.*Sterility Assurance Level: SAL 10⁻³

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72:2002/(R)2010 Bacterial Endotoxins - Test methodologies, routine monitoring, and alternative to batch testing. Results: < 0.1 EU/mL (< 4EU/device)

Surface Characterization:

Surface is characterized to be hydrophilic and negatively charged, composed of ≥20% oxygen atoms. This surface composition has been developed for cell attachment and growth.

Cell Attachment and Growth Characteristics:

The product has been tested for the attribute of cell attachment and growth utilizing an attachment-dependent mammalian cell line in a serum supplemented media.

Bovine Spongiform Encephalopathy and Transmissible Spongiform Encephalopathy:

This product is manufactured with animal free materials.

Optical Characteristics:

The product is made of opaque black polystyrene walls to minimize well to well crosstalk and background fluorescence and /or luminescence. The bottom is made of clear polystyrene to permit direct microscopic viewing.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Visual Attributes:

Visual and microscopic examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling and correct

product configuration

Cell Culture Treatment: Wettability test using water to insure the presence of a hydrophilic

surface.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian Date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 10