Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description



Catalog Number: 3473

Product Description: Costar ® 24-well Ultra Low Attachment multiple well plate, flat bottom, with lid

Component Materials:

Plate/Lid Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures.

Surface Proprietary hydrogel.

Product Dimensions:

Length of Plate Diameter of Well @ top .640 in. 5.030 in. Width of Plate 3.365 in. Diameter of Well @ .615 in. bottom Depth of Well .685 in. Height with Lid .891 in. Tolerances of Growth Area +/- .050 in. 1.9 cm²

Dimensions

Sterilization:

The product is irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization. Sterility Assurance Level: SAL 10⁻³

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72:2002/(R)2010 Bacterial Endotoxins - Test methodologies, routine monitoring, and alternative to batch testing. Results: < 0.1 EU/mL (< 4EU/device)

Surface Characterization:

Surface is characterized to be hydrophilic and neutrally charged, composed of a covalently bound hydrogel layer that is biologically inert and non-degradable. This surface composition has been optimized for cell attachment inhibition.

Cell Attachment and Growth Characteristics:

The product has been tested for the attribute of cell attachment inhibition utilizing an attachment- dependent mammalian cell line in a serum supplemented media. Cell attachment inhibition must be ≥ 98% as compared to a standard tissue culture treated surface.

Bovine Spongiform Encephalopathy and Transmissible Spongiform Encephalopathy:

This product is manufactured and packaged with animal free materials.

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures. Visual Attributes: Visual and microscopic examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling, and correct

product configuration.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 15