

Corning® Disposable Spinner Flasks

Ready-to-Use Convenience

CORNING

Convenience

The Corning disposable spinner flasks come ready-to-use with paddle and integrated magnet, eliminating the need for time-consuming assembly or cleaning and reassembly.

Confidence

Made of materials to comply with USP Class VI and ISO 10993-18 standards. Each spinner flask is assembled in a Class 10,000 clean room and gamma irradiated to assure a clean and sterile unit. No more concerns with detergent residues or contamination.

Compatibility

Vessels were designed to be comparable to conventional glass spinner flasks for growth of suspension cell lines and any attachment-dependent cultures using microcarrier beads.

Performance

The paddle size and height are optimized for each vessel size. A unique integrated magnet provides a smooth, even rotation at required speeds on any laboratory slow speed stirrer.



125 mL and 500 mL Disposable Spinner Flasks



1L and 3L Disposable Spinner Flasks, Solid Cap

Corning® 125 and 500 mL Disposable Spinner Flasks



3152, 3153 125 mL and 500 mL Disposable Spinner Flasks

Materials of Construction

- ▶ Vessel, shaft and paddle are constructed of polystyrene (USP Class VI and ISO 10993-18 compliant).
- ▶ Single use only. Flasks cannot be autoclaved or resterilized with alcohol. Any attempt to do so will result in degradation of the materials.
- ▶ Teflon® Paddle Bushing was life tested for 2.5 months/24 hours/day at 125 rpm.
- ▶ Gamma-irradiated. Product meets USP XXIV: 71 Bacteriostasis, Fungistasis and Sterility Standards.
- ▶ Each system is supplied in double bagged Tyvek® breathable pouches, individually packed in a box.
- ▶ Product is sterile unless Tyvek pouch has been compromised.
- ▶ Three-year shelf life from date of manufacture

Technical Specifications

Parameter	125 mL	500 mL
Recommended Working Volumes	30 – 75 mL	100 – 300 mL
Vessel Height	145 mm	203.2 mm
Vessel Diameter	63.5 mm	87.3 mm
Flange Diameter	114.8 mm	139.7 mm
Center Cap Diameter	70 mm	100 mm
Sidearm Opening	18.8 mm	38.1 mm
Sidearm Cap Diameter	25 mm (GL 25 Threads)	45 mm (GL 45 Threads)
Paddle Size (W x H)	39.9 x 50.0 mm	50.3 x 61.0 mm
Minimum Drive Coupling (rpm)	2	2
ALNICO Magnet (Gauss induction)	12,800	12,800

Corning 1L and 3L Disposable Spinner Flasks



3561, 3563 1L and 3L Disposable Spinner Flasks, Flat Cap

- ▶ Vessel and Impeller are constructed of USP Class VI and ISO 10993-18 compliant materials.
- ▶ All Corning Disposable Spinner Flasks, Aseptic Transfer Caps and replacement caps have the highest standard Sterility Assurance Level (SAL) of 10⁻⁶.
- ▶ Assembled in a Class 10,000 clean room
- ▶ Gamma-irradiated. Product meets USP XXIV: 71 Bacteriostasis, Fungistasis and Sterility Standards.
- ▶ Each system is supplied individually double bagged.
- ▶ Vented, solid cap, and preassembled Closed System Solution vessels available
- ▶ Replacement caps and Aseptic Transfer Caps also sold separately
- ▶ Preassembled Closed System Solution vessels have one aseptic connector assembled to one side arm. Opposite side arm has a solid cap.
- ▶ Three-year shelf life from date of manufacture

Technical Specifications

Parameter	1L (Cat. No. 3561)	3L (Cat. No. 3563)
Vessel Height	245 mm	259 mm
Vessel Diameter	137 mm	188 mm
Vessel Width	203 mm	256 mm
Sidearm Opening (ID)	39 mm	39 mm
Sidearm Cap Diameter (OD)	54 mm (GL 45 Threads)	54 mm (GL 45 Threads)
Paddle Size (W x H)	69 x 215 mm	105 x 227 mm
Maximum Drive Speed	150 rpm	150 rpm
Magnet	ALNICO	ALNICO

Corning® Disposable Spinner Flasks Ordering Information

Corning 125 and 500 mL Disposable Spinner Flasks



3153 500 mL Disposable Spinner Flask

Cat. No.	Description	Capacity (mL)	Center Neck (mm)	Sidearm Neck (mm)	Qty/Cs
3152	Disposable Spinner Flask	125	70	25	12
3153	Disposable Spinner Flask	500	100	45	12
3578	Disposable Spinner Flask, Vent Cap	500	100	45	12

Replacement Caps and Aseptic Transfer Caps

Cat. No.	Description	Compatible with Cat. No.	Qty/Cs
3567	Vent Cap, 0.2 µm Pore	3153, 3561, 3580, 3563, 3581	4
3568	Flat Cap	3153, 3561, 3580, 3563, 3581	4
3565	Side Arm Aseptic Transfer Cap, 1/8" Dip Tube with 0.2 µm Pore, Vent, MLL*	3153	2
3528	Side Arm Aseptic Transfer Cap, 1/4" Dip Tube with 0.2 µm Pore, Vent, MPC**	3153	2



3580, 3581 1L and 3L Disposable Spinner Flasks with Vent Cap

Corning 1L and 3L Disposable Spinner Flasks

Cat. No.	Description	Capacity (L)	Qty/Cs
3561	Disposable Spinner Flask,	1	6
3580	Disposable Spinner Flask, Vent Cap	1	6
3563	Disposable Spinner Flask	3	4
3581	Disposable Spinner Flask, Vent Cap	3	4

Replacement Caps and Aseptic Transfer Caps

Corning Disposable Spinner Flask Aseptic Transfer Caps are available separately. Each arrive sterile and individually doubled bagged. Caps are available for 500 mL, 1L and 3L flask sizes.



3546, 3559 1L and 3L Disposable Spinner Flasks, MPC Quick Connect

Cat. No.	Description	Compatible with Cat. No.	Qty/Cs
3567	Vent Cap, 0.2 µm Pore	3153, 3561, 3580, 3563, 3581	4
3568	Flat Cap	3153, 3561, 3580, 3563, 3581	4
3562	Side Arm Aseptic Transfer Cap, 1/8" Dip Tube with 0.2 µm Pore, Vent, MLL*	3561	2
3545	Side Arm Aseptic Transfer Cap, 1/4" Dip Tube with 0.2 µm Pore, Vent, MPC**	3561	2
3564	Side Arm Aseptic Transfer Cap, 1/8" Dip Tube with 0.2 µm Pore, Vent, MLL*	3563	2
3558	Side Arm Aseptic Transfer Cap, 1/4" Dip Tube with 0.2 µm Pore, Vent, MPC**	3563	2

Preassembled Closed System Solution Disposable Spinner Flasks

Preassembled Flasks have one aseptic connector preassembled to one side arm. Opposite side arm has a flat cap.



3569, 3579 1L and 3L Disposable Spinner Flasks, Luer Lock

Cat. No.	Description	Capacity (L)	Preassembled with One Aseptic Transfer Cap Cat. No.	Qty/Cs
3569	Disposable Spinner Flask, Preassembled	1	3562	6
3546	Disposable Spinner Flask, Preassembled	1	3545	6
3579	Disposable Spinner Flask, Preassembled	3	3564	4
3559	Disposable Spinner Flask, Preassembled	3	3558	4

*Male luer lock

**Medical grade polycarbonate



3565, 3562 and 3564 Aseptic Transfer Cap, Luer Lock



3528, 3545 and 3558 Aseptic Transfer Cap, MPC Quick Connect



3568 Flat Cap



3567 Vent Cap

CORNING

Corning Incorporated Life Sciences

Tower 2, 4th Floor
900 Chelmsford St.
Lowell, MA 01851
t 800.492.1110
t 978.442.2200
f 978.442.2476

www.corning.com/lifesciences

Worldwide Support Offices

ASIA/PACIFIC

Australia/New Zealand
t 0402-794-347

China
t 86 21 2215 2888
f 86 21 6215 2988

India
t 91 124 4604000
f 91 124 4604099

Japan

t 81 3-3586 1996
f 81 3-3586 1291

Korea

t 82 2-796-9500
f 82 2-796-9300

Singapore

t 65 6733-6511
f 65 6861-2913

Taiwan

t 886 2-2716-0338
f 886 2-2716-0339

EUROPE

France

t 0800 916 882
f 0800 918 636

Germany

t 0800 101 1153
f 0800 101 2427

The Netherlands
t 31 20 655 79 28
f 31 20 659 76 73

United Kingdom

t 0800 376 8660
f 0800 279 1117

All Other European Countries

t 31 (0) 20 659 60 51
f 31 (0) 20 659 76 73

LATIN AMERICA

Brasil
t (55-11) 3089-7419
f (55-11) 3167-0700

Mexico
t (52-81) 8158-8400
f (52-81) 8313-8589