



Corning® Stripettor™ Ultra Pipet Controller

Completely redesigned with more features, greater reliability, and improved ergonomics

This light, ergonomic, motorized pipet controller is designed for use with glass and plastic serological pipets from 0.5 to 100 mL. Conveniently positioned switches change operating modes and speeds quickly to handle different liquid volumes and various viscosities. Aspirating and dispensing speed is controlled through the finger triggers. When fully charged, the batteries enable up to 8 hours of continuous use. The large LCD display clearly indicates battery status, pipetting mode, and speed.

Features

- ▶ LCD display for continuous visualization of speed, modes, and battery status
- ▶ Colored nose pieces for user or application identification
- ▶ Well positioned function buttons



Extra nose pieces



LCD display



Mode buttons

Ordering Information

Corning® Stripettor™ Ultra Pipet Controller

Cat. No.	Description
4099	Corning Stripettor Ultra Pipet Controller, with universal power supply, three 0.2 µm filters, 3 colored nose pieces and wall hanger

Accessories

4991	Hydrophobic PTFE filter 0.2 µm (5 pcs)
4992	Hydrophobic PTFE filter 0.45 µm (5 pcs)
4993	Silicone pipet holder
4994	Battery set, 3 x AAA, NiHM
4995	Battery cover with wings
4996	Universal power supply, 9V with set of adaptors (EU, US, UK, and AUS)
4997	Colored nose pieces, set of 4 (orange, yellow, green, red)



Shorty Stripette with pipet controller

Related Products

Shorty Stripette® serological pipets, paper/plastic wrap

Cat. No.	Capacity (mL)	Graduations (mL)	Negative Grads (mL)	Color Strip	Qty/Pk	Qty/Cs
4102	5	1/10	3.0	Black	200	200
4103	10	2/10	8.0	Black	100	100

Serological pipets, individually wrapped, paper/plastic wrap

4485	1	1/100	0.2	Yellow	50	1,000
4486	2	1/100	0.2	Green	50	1,000
4487	5	1/10	2.5	Blue	50	200
4488	10	1/10	3.0	Orange	50	200
4489	25	2/10	10.0	Red	25	200
4490	50	1/2	10.0	Purple	25	100
4491	100	1/1	N/A	Aqua	10	100

For more specific information on claims, visit the Certificates page at www.corning.com/lifesciences.

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

For additional product or technical information, please visit www.corning.com/lifesciences. You can contact our Scientific Support Team at ScientificSupportEMEA@corning.com.

Corning Incorporated Life Sciences Europe

Corning BV
Fogostraat 12
1060 LJ Amsterdam
The Netherlands
Phone: +31 (0) 20 659 60 51
Fax: +31 (0) 20 659 76 73
cceurnl@corning.com
www.corning.com/lifesciences

Support Offices

EUROPE

France
t 0800 916 882
f 0800 918 636

Germany
t 0800 101 1153
f 0800 101 2427

The Netherlands
t 31 20 655 79 28
f 31 20 659 76 73

United Kingdom
t 0800 376 8660
f 0800 279 1117

All Other European Countries
t 31 (0) 20 659 60 51
f 31 (0) 20 659 76 73

CORNING | **FALCON**® | **AXYGEN**® | **GOSELIN**™

For a listing of trademarks, visit www.corning.com/dstrademarks. All other trademarks are the property of their respective owners.