Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description

Catalog Number: 7369

Product Description: Corning ® HTS Transwell ® 96 Well, TC Treated, 0.4 µm pore size, PET, with barcode

label, in a reservoir plate with lid, with separate receiver plate

Component Materials:

Receiver & Reservoir

 Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and closures.

plate Lid

Virgin Polystyrene, meets *USP*, *Class VI* requirements for plastic containers and

closures.

Transwell body - Virgin P

- Virgin Polystyrene, meets *USP, Class VI* requirements for plastic containers and

closures.

Transparent PET membrane, meets *USP*, *Class VI* requirements for plastic containers

Filter - Transparent PET membrane, meet and closures.

Adhesive - Proprietary Acrylate, meets *ISO 10993* Biocompatibility requirements.
- Virgin Polystyrene, meets *USP, Class VI* requirements for plastic containers and

Stabilizer closures

Barcode Label: - White polypropylene base, acrylic adhesive

Special Format:

Barcode label (format 128) on A1 short side

Product Dimensions:

Length of Plate - 5.030 in.

Bottom of Transwell to - .050 in.

receiver plate

Width of Plate - 3.365 in.

Apical volume added/ - 75μL Transwell per well

Height in receiver with lid - .770 in.

Volume added per

reservoir plate

30mL 235μL

Height in a reservoir w/lid - .770 in.

Bisolateral volume added - per receiver plate well

per receiver plate well Suggested working

75μL to 235μL

Tolerances of Dimensions +/-.010 in.

volume

Maximum volume - 100μL to 290μL

Sterilization:

The lot has been irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.*Sterility Assurance Level: SAL 10⁻³

Cell Attachment and Growth Characteristics:

This product has been tested for the attribute of Cell Attachment and Growth utilizing an attachment-dependent mammalian cell line in a serum supplemented media.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Visual Attributes: Visual examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling, and correct

product configuration.

Cell Culture Treatment of Membrane: Wettability test using water to insure the presence of a hydrophilic

surface.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 1