

Edition Date: Revision Date : Revised by: 2005-10-08 2020-05-08 Annette Roy, Regulatory

Product Name: Micrewtube[®] Catalogue No.: T332-2

This document replaces any previous version

- **1.** Product Description:
 - O.5 ml Micrewtube[®]: Non-Sterile, Disposable, self-standing tube with Silicone washer seal screw cap and attachment loop. Caps are pre-attached and not screwed on.
- 2. Packaging:
 - > Case:

10 bags of 50 for a total of 500 units per case

3. Product Specifications:

- > Material:
 - Polypropylene tube
 - Polypropylene cap
 - Silicone washer seal
- Certified RNase, DNase, Pyrogen and DNA Free
- Temperature range: -196°C to +121°C. Autoclavable at 121°C, for up to 30 minutes

Sampling and inspection procedures

CONEG standards for heavy metals

Resin conforms to USP Class VI

Material is Latex Free Material is BSE / TSE Free

Resin conforms to FDA 21 CFR 177.1520

Plastics and colorants are in conformity with

Plastic is in conformity to REACH standards

Centrifuged up to 17 000g

4. Standards and Conformity:

- > ISO 2859-1:
- > FDA:
- > USP:
- > CONEG:
- > REACH (SVHC):
- > LATEX:
- BSE / TSE:

5. Quality Assurance:

- Clear, no presence of contamination in plastic
- Visual attributes
- Volume measurements
- Closure verification
- Leak proof testing in vacuum at 71.3cm Hg
- Gas phase of Liquid Nitrogen resistance



Edition Date: Revision Date : Revised by: 2005-10-08 2020-05-08 Annette Roy, Regulatory

6. Traceability:

- Lot No. Composition: 8 or 9 digits
- > The lot number can be found in one or all of these locations:
 - 1. On exterior case label
 - 2. On label inserted inside the master case
 - 3. On the inner bag

7. Storage Conditions:

- Store at room temperature in normal warehouse conditions
- Avoid temperature variations and humidity
- Protect from any possible contamination
- Protect from any damage to the packaging

8. Recommended Use:

- > Verify proper cap closure when using biohazard material and / or chemical reagents
- > Follow chemical resistance chart recommendations
- > For use in automated equipment, follow the equipment manufacturer's instructions
- Should be used only in the gas phase of Liquid Nitrogen

OWNERSHIP OF MATERIALS:

Materials and information contained in this document are **Simport Scientific**'s copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.