

Product Data Sheet for JACKSON SAFETY* G80 Neoprene Chemical Resistant Gloves - 30 cm Hand-specific pairs / Yellow & Blue

Product Information

| | |
|-----------------------------|--|
| Customer Facing Code | 38741 - 38744 |
| Description | JACKSON SAFETY* G80 Neoprene Chemical Resistant Gloves - 30 cm Hand-specific pairs / Yellow & Blue |
| PDS Reference | 23/05/2017 |
| Status | On Sale |



Packaging Configuration

| | |
|----------------------------|------------------------------|
| Case Contents | 5 Bags x 12 Pairs = 60 Pairs |
| Outer Pack Material | Paper |
| Commodity Code | 40151900 |

Packaging and Palletisation

| Code/Size | ITF Barcode | EAN Barcode | Case LWH (cm) | Net/Gross Weight (kg) | Pallet Type | Pallet LWH (m) | Cases per Pallet | Inner Gross Weight (Kg) |
|-----------|----------------|--------------|--------------------|-----------------------|-------------|--------------------|------------------|-------------------------|
| 38741-7 | 10036000387411 | 036000387414 | 42.4 x 37.4 x 16.8 | 5.04/5.6 | E5 | 1.20 x 0.80 x 1.33 | 8 x 7 =56 | |
| 38742-8 | 10036000387428 | 036000387421 | 42.4 x 37.4 x 16.8 | 5.52/6.08 | E5 | 1.20 x 0.80 x 1.33 | 8 x 7 =56 | |
| 38743-9 | 10036000387435 | 036000387438 | 42.4 x 37.4 x 16.8 | 6.12/6.68 | E5 | | 8 x 7 =56 | |
| 38744-10 | 10036000387442 | 036000387445 | 42.4 x 37.4 x 16.8 | 6.78/7.34 | E5 | 1.20 x 0.80 x 1.33 | 8 x 7 =56 | |

Product Description

JACKSON SAFETY* G80 Neoprene/Latex Chemical Resistant Gloves are suitable for various applications and offer reliable protection against a wide range of chemicals.

Ideal for: providing PPE Category 3 protection and also basic mechanical protection in many different segments when handling chemicals, oils, grease, acids, caustics or solvents.

Available as: pairs of hand specific gloves of 0.70mm thickness, made of neoprene over latex formulation to maximise protection but also enhance flexibility with straight cuff and honeycomb structure on the palm to provide excellent grip in wet and dry conditions; cotton flocked liner for easy donning and extra comfort in extended use. It is chlorinated for low extractable proteins and residual chemicals.

Product Data Sheet for JACKSON SAFETY* G80 Neoprene Chemical Resistant Gloves - 30 cm Hand-specific pairs / Yellow & Blue

Features and Benefits

| Features | Benefits |
|--|--|
| 0.70mm thickness | To increase protection |
| Anatomic shape | To increase comfort and dexterity |
| Anti-slip pattern with honeycomb structure | To provide excellent grip in wet and dry conditions |
| Chlorinated | To harden and cleanse the surface of the glove |
| Neoprene over Latex formulation | To maximise protection but also flexibility and elasticity |
| Palm strengthened by special dip | For extra protection |
| Pure cotton flocked | To absorb perspiration |

Product Configuration

| | | | |
|-----------------------------|---------------------|--------------------|---------------|
| Sterile | No | Latex Free | No |
| Main Protection Type | CE Complex | Application | Industrial |
| Ambidextrous | No | Powdered | No |
| Material | Neoprene Over Latex | Coated | No |
| Liner | Pure cotton flocked | Coating | No |
| Colour | Yellow & Blue | AQL | 1.5 |
| Chlorinated | Yes | Cuff Style | Straight cuff |
| Glove Shape | Hand Specific | Length | 305 mm |
| Thickness | 0.70 mm | | |

Product Data Sheet for JACKSON SAFETY* G80 Neoprene Chemical Resistant Gloves - 30 cm Hand-specific pairs / Yellow & Blue

International Standards and Symbols

Solution

Safer Workplace

We know staff safety is your top priority. You can rely on our solutions to protect them, their environment and your important work.



Productive Workplace

The success of your business hinges on your work efficiency. That's why our solutions are designed to help improve your productivity.



Standard R+E

EN 374-2: 2003 Microorganisms Protection

This European Standard specifies test method for the penetration resistance of gloves that protect against chemicals and/or microorganisms.



EN 374-3: 2003

Resistance to permeation by chemicals under the conditions of continuous contact.



EN 388:2003

This standard which is designed to assess the performance of a fabric or layers of fabric for their ability to resist mechanical risks of abrasion, blade cut, tear and puncture. The test procedure includes a separate test for each of these properties, and a performance level is awarded according to each test result. This standard is only applicable in conjunction with EN420



CE Mark

Simple - CAT I, Intermediate - CAT II or Complex - CAT III



Trade

ISO 9001

This gives the requirements for quality management systems, is now firmly established as the globally implemented standard for providing assurance about the ability to satisfy quality requirements and to enhance customer satisfaction in supplier-customer relationships.



Packaging

| | | | |
|----------------------------------|--------------------|----------------------------|--------------------------|
| Unit Of Sale | Case | Max Weight(kg) | 8.07 |
| Case Dimension(LXWXH)(cm) | 42.4 x 37.4 x 16.8 | Inner Pack Material | Low Density Polyethylene |

Product Data Sheet for JACKSON SAFETY* G80 Neoprene Chemical Resistant Gloves - 30 cm Hand-specific pairs / Yellow & Blue

Information

It is the employer's responsibility to assess the risk of the task to be undertaken and determine the correct choice of personal protective equipment for the task. The manufacturer, Kimberly-Clark, does not accept any responsibility for the incorrect choice or misuse of the personal protective equipment shown in this brochure. All care has been taken to ensure that the information contained herein is as accurate as possible at the time of publication, however errors may occur and legislation concerning personal protective equipment is under constant review and may change in the lifetime of this brochure. Accordingly, the specification for the products may be subject to change. We would advise you to contact INFOFAX if you have any queries concerning the products shown or the suitability of such products for a particular task. Always dispose of used protective equipment in a safe and appropriate manner in accordance with European, National and Local environmental regulations.

Infobox Details

infofax@kcc.com

Websites

www.kcprofessional.co.uk

Storage conditions

Keep dry. Store in a cool dry place and shield from exposure to direct sunlight, intense artificial light or exposure to sources of radiation or ozone.

Durability

This product has a five years shelf life from the date of manufacture.

Customer Service Number

For more information please contact Customer Service during regular office hours-0870 551 044

Country of Origin

SRI LANKA