

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 8.4 Revision Date 12.08.2022 Print Date 01.09.2022

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : MCE 0.1UM WH PL 25MM 100/PK

MF-Millipore ® Membrane Filter, 0.1 µm pore size

Product Number : VCWP02500 Catalogue No. : 638147 Brand : Millipore

REACH No. :

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Filtration

1.3 Details of the supplier of the safety data sheet

Company : Merck KGaA

Frankfurter Str. 250 D-64271 DARMSTADT

Telephone : +49 (0)6151 72-0 Fax : +49 6151 727780

E-mail address : TechnicalService@merckgroup.com

1.4 Emergency telephone

Emergency Phone #: +(44)-870-8200418 (CHEMTREC (GB))

+(353)-19014670 (CHEMTREC Ireland) 001-803-017-9114 (CHEMTREC India)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable solids (Category 1), H228

Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Millipore- VCWP02500 Page 1 of 11



Hazard statement(s)

H228 Flammable solid.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Supplemental Hazard

Statements

none

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard statement(s)

H412 Harmful to aquatic life with long lasting effects.

Precautionary

statement(s)

none

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
Octylphenol polyethoxyethanol Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)			
CAS-No.	9036-19-5	Acute Tox. 4; Skin Irrit. 2;	>= 0,25 - < 1
		Eye Dam. 1; Aquatic Acute	%
		1; Aquatic Chronic 1;	
	*	H302, H315, H318, H400,	
		H410	
		M-Factor - Aquatic Acute:	
		10 - Aquatic Chronic: 1	

^{*}A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006,

Millipore- VCWP02500 Page 2 of 11



the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Spontaneous ignition at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:

nitrogen oxides, nitrous gases

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Millipore- VCWP02500 Page 3 of 11



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep away from heat and sources of ignition. Keep away from direct sunlight.Performing regular visual inspections of membranes and keeping accurate records of recommended shelf life can reduce the risk of membrane deterioration. Shelf-life limited when kept above +25°C. Recommended storage humidity: 30 - 70 %. Verify on a regular basis housekeeping, temperature and humidity. Designated "Flammable Material" storage areas must be engineered according to local regulations. Rotate stock. Improper storage conditions can accelerate deterioration of the membrane in advance of expiration date. Perform regular visual inspections of stored materials to ensure early stages of deterioration does not advance. Early stages of deterioration: Amber or yellow discoloration. Advanced stages of deterioration: visible liquid or solid brown resin. If membrane shows visual indications of deterioration, safely dispose of product according to local regulations. Storage under improper conditions could lead to the membrane self-decomposing at ambient temperatures with the formation of nitrous vapors or self ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

Millipore- VCWP02500 Page 4 of 11



7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Respiratory protection

Recommended Filter type: Filter P 1 (acc. to DIN 3181) for solid particles of inert substances

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state solidb) Color colored

Millipore- VCWP02500

Page 5 of 11

A

The life science business of Merck operates as MilliporeSigma in the US and Canada

c) Odor No data available No data available d) Melting point/freezing point Initial boiling point No data available and boiling range Flammability (solid, The substance or mixture is a flammable solid with the category gas) g) Upper/lower No data available flammability or explosive limits

h) Flash point No data available Autoignition No data available temperature No data available Decomposition j)

No data available k) pH

Viscosity Viscosity, kinematic: No data available I) Viscosity, dynamic: No data available

m) Water solubility No data available n) Partition coefficient: No data available n-octanol/water o) Vapor pressure No data available

No data available p) Density No data available Relative density Relative vapor No data available

density

No data available

r) Particle characteristics

temperature

Not classified as explosive.

Oxidizing properties none

9.2 Other safety information

s) Explosive properties

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

Product is sensitive to light and moisture. Prolonged exposure to air may cause discolouration.

Millipore- VCWP02500 Page 6 of 11

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Oxidizing agents

Bases

Strong acids

10.4 Conditions to avoid

Heating (decomposition). Exposure to sunlight.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available

Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Carcinogenicity - No data available

Reproductive toxicity

No data available

Reproductive toxicity - No data availableDevelopmental Toxicity - No data available**Specific** target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Millipore- VCWP02500 Page 7 of 11



11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain

components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Risk of methaemoglobin formation.

After uptake:

Risk of methaemoglobin formation.

However, when the product is handled appropriately, hazardous effects are unlikely to occur.

Handle in accordance with good industrial hygiene and safety practice.

Components

Octylphenol polyethoxyethanol

Acute toxicity

LD50 Oral - Rat - 1.900 - 5.000 mg/kg

Remarks: (External MSDS)

Symptoms: Vomiting, Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Risk of aspiration upon vomiting., Aspiration

may cause pulmonary edema and pneumonitis.

Inhalation: No data available

LD50 Dermal - Rabbit - > 3.000 mg/kg

Remarks: (External MSDS)

Skin corrosion/irritation

Skin - Rabbit

Result: irritating - 4 h (OECD Test Guideline 404)

Remarks: The value is given in analogy to the following substances: 4-(1,1,3,3-

tetramethylbutyl)phenol

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Risk of serious damage to eyes.

(Draize Test)

Risk of corneal clouding.

Respiratory or skin sensitization

Sensitisation test: - Human

Result: negative

Remarks: (External MSDS)

Patch test on human volunteers did not demonstrate sensitization properties.

Germ cell mutagenicity

No data available

Millipore- VCWP02500 Page 8 of 11



Carcinogenicity

No data available

Reproductive toxicity

Ingestion of excessive amounts by pregnant animals resulted in maternal and fetal toxicity. Did not show teratogenic effects in animal experiments.

Specific target organ toxicity - single exposure

Acute oral toxicity - Vomiting, Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

Toxicity to daphnia

and other aquatic

invertebrates

Toxicity to algae Re

Remarks: No data available

Remarks: No data available

Toxicity to bacteria Remarks: No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : This substance/mixture contains components

considered to have endocrinedisrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission

Delegated Regulation (EU) 2017/2100.

12.7 Other adverse effects

Discharge into the environment must be avoided.

Millipore- VCWP02500 Page 9 of 11

A

Components

Octylphenol polyethoxyethanol

Toxicity to fish semi-static test LC50 - Leuciscus idus (Golden orfe) - 0,26 mg/l

- 96 h

(OECD Test Guideline 203)

Remarks: The value is given in analogy to the following

substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - 0,011 mg/l -

48 h

invertebrates Remarks: (ECOTOX Database)

The value is given in analogy to the following substances: 4-

(1,1,3,3-tetramethylbutyl)phenol

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata (green algae)

- 1,9 mg/l - 96 h Remarks: (ECHA)

The value is given in analogy to the following substances: 4-

(1,1,3,3-tetramethylbutyl)phenol

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 3270 IMDG: 3270 IATA: 3270

14.2 UN proper shipping name

ADR/RID: NITROCELLULOSE MEMBRANE FILTERS IMDG: NITROCELLULOSE MEMBRANE FILTERS

IATA: Nitrocellulose membrane filters

14.3 Transport hazard class(es)

ADR/RID: 4.1 IMDG: 4.1 IATA: 4.1

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

Millipore- VCWP02500 Page 10 of 11

A

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Candidate List of Substances of Very : Octylphenol polyethoxyethanol High Concern for Authorisation (Article 59).

This product contains a substance listed on Annex XIV of the REACH Regulation (EC) Nr. 1907/2006.

Listed substance / Sunset Date : Octylphenol polyethoxyethanol / 04.01.2021

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

National legislation

Seveso III: Directive 2012/18/EU of the European : ENVIRONMENTAL HAZARDS Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Other regulations

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Millipore- VCWP02500 Page 11 of 11

