

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Revision Date 11.11.2019

Version 2.0

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Catalogue No.	618873
Millipore Ref.	AAWG047S6
Product name	0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.
REACH Registration Number	Not applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Filtration For additional information on uses please refer to the Merck Chemicals portal (www.merckgroup.com).
-----------------	---

1.3 Details of the supplier of the safety data sheet

Company	Merck KGaA * 64271 Darmstadt * Germany * Phone: +49 6151 72-0
Responsible Department	LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone number **Please contact the regional company representation in your country.****SECTION 2. Hazards identification****2.1 Classification of the substance or mixture**
Classification (REGULATION (EC) No 1272/2008)

Flammable solid, Category 1, H228
Eye irritation, Category 2, H319
Short-term (acute) aquatic hazard, Category 1, H400
Long-term (chronic) aquatic hazard, Category 2, H411
For the full text of the H-Statements mentioned in this Section, see Section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word
Danger

Hazard statements

H228 Flammable solid.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use powder for extinction.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word
Danger

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370 + P378 In case of fire: Use powder for extinction.

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature Contains nitrocellulose.

3.1 Substance

Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

3.2 Mixture

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No.	Registration number	Classification
---------	---------------------	----------------

Octylphenol polyethoxyethanol (>= 2,5 % - < 3 %)

9036-19-5 *)

Acute toxicity, Category 4, H302
Skin irritation, Category 2, H315
Serious eye damage, Category 1, H318
Short-term (acute) aquatic hazard, Category 1, H400
Long-term (chronic) aquatic hazard, Category 1, H410
M-Factor: 10

*) A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

Risk of methaemoglobin formation., irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water, Foam, Carbon dioxide (CO₂), Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Spontaneous ignition at elevated temperatures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.	618873
Product name	0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:
nitrogen oxides, nitrous gases

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

Tightly closed. Dry. Keep away from heat and sources of ignition. Keep away from direct sunlight.

Performing regular visual inspections of membranes and keeping accurate records of recommended shelf life can reduce the risk of membrane deterioration. Shelf-life limited when kept above +25°C. Verify on a regular basis expiry dates of stored materials, housekeeping, temperature and humidity. Designated "Flammable Material" storage areas must be engineered according to local regulations. Rotate stock. Improper storage conditions can accelerate deterioration of the membrane in advance of expiration date. Storage humidity: 30 - 70 %. Perform regular visual inspections of stored materials to ensure early stages of deterioration does not advance. Early stages of deterioration: Amber or yellow discoloration. Advanced stages of deterioration: visible liquid or solid brown resin. If membrane shows visual indications of deterioration, safely dispose of product according to local regulations.

Storage under improper conditions could lead to the membrane self-decomposing at ambient temperatures with the formation of nitrous vapors or self ignition. Observe the expiration date!

Recommended storage temperature see product label.

Advice on common storage

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Safety glasses

Hand protection

full contact:

Glove material:	Nitrile rubber
Glove thickness:	0,11 mm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

Break through time: 480 min
splash contact:
Glove material: Nitrile rubber
Glove thickness: 0,11 mm
Break through time: 480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment
protective clothing

Respiratory protection

required when dusts are generated.

Recommended Filter type: Filter P 2 (acc. to DIN 3181) for solid and liquid particles of harmful substances

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	solid
Colour	coloured
Odour	No strong odour known.
Odour Threshold	No information available.
pH	No information available.
Melting point	No information available.
Boiling point	No information available.
Flash point	No information available.
Evaporation rate	No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

Flammability (solid, gas)	The substance or mixture is a flammable solid with the category 1. The substance or mixture is a flammable solid with the category 1.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Vapour pressure	No information available.
Relative vapour density	No information available.
Density	No information available.
Relative density	No information available.
Water solubility	No information available.
Partition coefficient: n-octanol/water	No information available.
Auto-ignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	No information available.
Explosive properties	Not classified as explosive. Not classified as explosive.
Oxidizing properties	none none

9.2 Other data

none

SECTION 10. Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

Product is sensitive to light and moisture.
Prolonged exposure to air may cause discolouration.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Oxidizing agents, Bases, Strong acids

10.4 Conditions to avoid

Heating (decomposition).

Exposure to sunlight.

10.5 Incompatible materials

no information available

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Mixture

Acute oral toxicity

Acute toxicity estimate: > 2.000 mg/kg

Calculation method

Acute inhalation toxicity

Symptoms: Possible damages: , mucosal irritations

Acute dermal toxicity

This information is not available.

Skin irritation

This information is not available.

Eye irritation

Mixture causes serious eye irritation.

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

11.2 Further information

After uptake:
Risk of methaemoglobin formation.
Other dangerous properties can not be excluded.
Handle in accordance with good industrial hygiene and safety practice.

Components

Octylphenol polyethoxyethanol

Acute oral toxicity
LD50 Rat: 1.900 - 5.000 mg/kg
(External MSDS)

Acute dermal toxicity
LD50 Rabbit: > 3.000 mg/kg
(External MSDS)

Skin irritation
Rabbit
Result: irritating
OECD Test Guideline 404

The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Sensitisation
Sensitisation test: human
Result: negative

(External MSDS)

SECTION 12. Ecological information

Mixture

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII, or a PBT/vPvB assessment was not conducted.

12.6 Other adverse effects

Additional ecological information
Discharge into the environment must be avoided.

Components

Octylphenol polyethoxyethanol

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

Toxicity to fish

semi-static test LC50 *Leuciscus idus* (Golden orfe): 0,26 mg/l; 96 h
Analytical monitoring: yes
OECD Test Guideline 203
The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Toxicity to daphnia and other aquatic invertebrates

static test EC50 *Daphnia magna* (Water flea): 0,011 mg/l; 48 h
(ECOTOX Database) The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Toxicity to algae

static test EC50 *Pseudokirchneriella subcapitata* (green algae): 1,9 mg/l; 96 h
(ECHA) The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Toxicity to fish (Chronic toxicity)

flow-through test *Danio rerio* (zebra fish): 0,012 mg/l
Analytical monitoring: yes
OECD Test Guideline 210
The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

semi-static test NOEC *Daphnia magna* (Water flea): 0,03 mg/l; 21 d

Analytical monitoring: yes

OECD Test Guideline 202

The value is given in analogy to the following substances: 4-(1,1,3,3-tetramethylbutyl)phenol

Biodegradability

22 %; 28 d; aerobic
OECD Test Guideline 301C

Not readily biodegradable.

M-Factor

10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 3270
14.2 Proper shipping name NITROCELLULOSE MEMBRANE FILTERS
14.3 Class 4.1
14.4 Packing group II
14.5 Environmentally hazardous yes
14.6 Special precautions for user yes
Tunnel restriction code E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number UN 3270
14.2 Proper shipping name NITROCELLULOSE MEMBRANE FILTERS
14.3 Class 4.1
14.4 Packing group II
14.5 Environmentally hazardous yes
14.6 Special precautions for user no

Sea transport (IMDG)

14.1 UN number UN 3270
14.2 Proper shipping name NITROCELLULOSE MEMBRANE FILTERS
14.3 Class 4.1
14.4 Packing group II
14.5 Environmentally hazardous yes
14.6 Special precautions for user yes
EmS F-A S-I

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard SEVESO III
Legislation ENVIRONMENTAL HAZARDS
E1
Quantity 1: 100 t
Quantity 2: 200 t

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at work.

Regulation (EC) No 1005/2009 on substances not regulated
that deplete the ozone layer

Regulation (EC) No 850/2004 of the not regulated
European Parliament and of the Council of 29
April 2004 on persistent organic pollutants
and amending Directive 79/117/EEC

Substances of very high concern (SVHC) This product does contain substances
of very high concern according to
Regulation (EC) No 1907/2006
(REACH), Article 59 above the
respective regulatory concentration
limit of > 0.1 % (w/w).

Contains: Octylphenol polyethoxyethanol

This product contains a substance listed on Annex XIV of the REACH Regulation (EC) Nr.
1907/2006.

Listed substance / Sunset Date: Octylphenol
polyethoxyethanol /
04.01.2021

After the sunset date the use of this substance requires either an authorization or can only be
used for exempted uses, e.g. use in scientific research and development which includes routine
analytics or use as intermediate.

National legislation

Storage class 4.1B

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 618873
Product name 0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word

Danger

Hazard statements

H228 Flammable solid.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P273 Avoid release to the environment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use powder for extinction.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.	618873
Product name	0.8µm 47mm white gridded S-Pak filter membrane made of mixed ester cellulose.

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.