

TECHNICAL DATA SHEET ITEM 1082

Mod. AQ 001 Rev. 0 del 25/09/2003

TECHNICAL SPECIFICATIONS

| Trade Name | Graduated tall form measuring cylinders - | |
|----------------|--|--|
| Use | Volumetric measures | |
| Material | Polypropylene PP | |
| Other Features | Permanent graduations are moulded in for reproducibility | |

DIMENSIONAL SPECIFICATIONS

| Height | 439,00 mm |
|------------------------------|-------------|
| External diameter | 66,00 mm |
| General dimesional tolerance | ISO 6706 |
| Capacity | 1000 ml |
| Graduated | 100 ml each |
| Graduation Class | В |



GENERAL FEATURES

| CE Mark | No |
|---------------------------------|--|
| Foodstuff suitability | Yes |
| No wetting | Yes |
| Chemically cleaner than glass | Yes |
| Chemically non absorbant | Yes |
| Manufactured in compliance with | ISO 6706 -1981 and BS 5404 part 2 - 1977 |
| Aspect | Translucent |

STERILIZATION OF THE BOTTLE

| Autoclavability + 121°C | Yes |
|-------------------------|-----|
| Gas (Ethylene Oxide) | Yes |
| Dry Heat (+160°C) | No |
| Chemical (Formalin) | Yes |
| Irradiation | No |
| Microwave | Yes |

CLEANING OPERATIONS

| Slight contamination | Wash with neutral detergent (pH 7) |
|--------------------------|---|
| Consistent contamination | Wash with alkalin detergent (pH up to 12) |

Quality Assurance

Massimiliano Capitanio

Technical DirectionGuido Borona



TECHNICAL DATA SHEET ITEM 1082

Mod. AQ 001 Rev. 0 del 25/09/2003

CHEMICAL RESISTANCES (Polypropylene)

| Categories of substances | Reference | Concentrazione % | T. 20° C | T. 40° C | T. 60° C |
|---------------------------|-------------------|------------------|----------|----------|----------|
| Inorganic Acid | Sulphuric acid | 98 | В | C | = |
| Organic Acid | Benzoic acid | 100 | Α | В | В |
| Alcohol | Ethanol | 100 | Α | Α | Α |
| Aldehydes | Acetaldeyde | 100 | В | С | = |
| Inorganic alkali | Isodium hydroxide | 50 | Α | Α | Α |
| Organic alkali | Aniline | 100 | Α | В | С |
| Ketone | Acetone | 100 | • | - | |
| Esther | Ethyl acetate | 100 | В | В | С |
| Hydrocarbons, halogenated | Dichloroethylene | 100 | С | - | |
| Hydrocarbons, aromatic | Benzene | 100 | В | С | = |
| Hydrocarbons, linear | Hexane | 100 | В | В | С |
| Supersolvent | Tetrahydrofuran | 100 | В | В | С |

Legenda (not applicable if neglected):

- A: fair resistence; exposure (30 days) to the chemical does not cause any damage.
- B: sufficient resistence; exposure causes damage of poor importance, which sometimes is only temporary.
- C: poor resistence; exposure to chemical is not allowed, or causes immediate permanent damages.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing.

Information about resistance of plastic materials to temperatures, steriization and washing treatments are based on bulletins issued by the Producers of raw materials, on literature data and on the experience gained in using the products

PACKAGING

| Quantity for each bag | 6 pcs |
|-----------------------|--------|
| Quantity in each box | 48 pcs |

Quality Assurance Massimiliano Capitanio **Technical Direction**Guido Borona

