

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code HI93754H-0
Product name COD LR Reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Determination of Chemical Oxygen Demand in Water Samples.

1.3. Details of the supplier of the safety data sheet

Name Hanna Instruments S.R.L.
Full address str. Hanna Nr 1
District and Country 457260 loc. Nusfalau (Salaj)
Romania
Tel. +40 260607700
Fax +40 260607700

e-mail address of the competent person responsible for the Safety Data Sheet msds@hanna.ro

1.4. Emergency telephone number

For urgent inquiries refer to Emergency Number - International: +1 7035273887 - UK, London: +44 8708200418 - CHEMTREC 24 hours/365 days

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Substance or mixture corrosive to metals, category 1	H290	May be corrosive to metals.
Acute toxicity, category 2	H300	Fatal if swallowed.
Acute toxicity, category 3	H311	Toxic in contact with skin.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

SECTION 2. Hazards identification ... / >>

Hazard statements:

H290	May be corrosive to metals.
H300	Fatal if swallowed.
H311	Toxic in contact with skin.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P201	Obtain special instructions before use.
P260	Do not breathe dust, fume, gas, mist, vapours, spray.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.
P391	Collect spillage.

Contains: **MERCURY (II) SULFATE**
SULPHURIC ACID

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
SULPHURIC ACID		
CAS	7664-93-9 50 \leq x < 100	Met. Corr. 1 H290, Skin Corr. 1A H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B
EC	231-639-5	Met. Corr. 1 H290: \geq 0.1%, Skin Corr. 1A H314: \geq 15%, Skin Irrit. 2 H315: \geq 5%, Eye Dam. 1 H318: \geq 15%, Eye Irrit. 2 H319: \geq 5%
INDEX	016-020-00-8	
REACH Reg.	01-2119458838-20	
MERCURY (II) SULFATE		
CAS	7783-35-9 0.5 \leq x < 1	Acute Tox. 1 H300, Acute Tox. 1 H310, Acute Tox. 2 H330, STOT RE 2 H373, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1, Classification note according to Annex VI to the CLP Regulation: 1, A
EC	231-992-5	STOT RE 2 H373: \geq 0.1%
INDEX	080-002-00-6	STA Oral: 0.5 mg/kg, STA Dermal: 5 mg/kg, STA Inhalation mists/powders: 0.051 mg/l
SILVER SULFATE		
CAS	10294-26-5 0.25 \leq x < 0.5	Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1000, Aquatic Chronic 1 H410 M=100
EC	233-653-7	
INDEX		
POTASSIUM DICHROMATE		
CAS	7778-50-9 0 \leq x < 0.1	Ox. Sol. 2 H272, Carc. 1B H350, Muta. 1B H340, Repr. 1B H360FD, Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 4 H312, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1, Classification note according to Annex VI to the CLP Regulation: 3
EC	231-906-6	STOT SE 3 H335: \geq 5%
INDEX	024-002-00-6	LD50 Oral: 90.5 mg/kg, STA Dermal: 1100 mg/kg, LC50 Inhalation mists/powders: 0.088 mg/l/4h
REACH Reg.	01-2119454792-32	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

POTASSIUM DICHROMATE

Irritation and corrosion, Allergic reactions, Cough, Shortness of breath Chromium(VI) is highly toxic. It is absorbed via both the lungs and the gastrointestinal tract. Being strong oxidisers, chromates/ bichromates can cause burns and ulcerations on the skin and mucous membranes and also irritations in the upper respiratory tract. Poorly healing ulcers occur after wound contact. In predisposed persons the substance rapidly leads to sensitisation and allergic reactions of the respiratory tract (risk of pneumonia!) and damage to nasal mucous membranes (under given circumstances perforation of the septum). After swallowing severe symptoms in the gastrointestinal tract such as bloody diarrhoea, vomiting (aspiration pneumonia!), spasms, circulatory collapse, unconsciousness, formation of methaemoglobin. Absorption may result in hepatic and renal damage. Inhalable chromium(VI) compounds gave clear evidence to be carcinogenic in animal experiments. Lethal dose (man): 0.5g. Antidotes: chelating agents such as EDTA, DMPS (Demaval®). Risk of blindness!.

MERCURY (II) SULFATE

Mercury compounds have a cytotoxic and protoplasmatoxic effect. Intoxication symptoms: acute: contact with eye causes severe lesions. Swallowing and inhalation of dusts damages mucous membranes of gastrointestinal and respiratory tract (metallic taste, nausea, vomiting, abdominal pain, bloody diarrhoea, intestinal burns, glottal oedema, aspiration pneumonia); drop in blood pressure, cardiac dysrhythmia, circulatory collapse, and renal failure; chronic: inflammation of the mouth with loss of teeth and mercurial line. The principal signs manifest themselves in the CNS (impaired speech, vision, hearing, and sensitivity, loss of memory, irritability, hallucinations, delirium inter alia).

SILVER SULFATE

Irritant effects. Risk of permanent damage due to staining of the cornea.

SULPHURIC ACID

SULPHURIC ACID 98%: Irritation and corrosion, Cough, Shortness of breath, Nausea, Vomiting, Diarrhoea, Pain, Risk of blindness.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

POTASSIUM DICHROMATE

Not combustible, has a fire-promoting effect due to release of oxygen.

MERCURY (II) SULFATE

Not combustible. Avoid shock and friction. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: mercury vapours, iodine, hydrogen iodide.

SILVER SULFATE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

SULPHURIC ACID

SULPHURIC ACID 98%: Not combustible, Fire may cause evolution of Sulphur oxides.

SECTION 5. Firefighting measures ... / >>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1A

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

AUS	Österreich	Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021 , Fassung vom 17.06.2021
BEL	Belgique	Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und

SECTION 8. Exposure controls/personal protection ... / >>

DNK	Danmark	Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
EST	Eesti	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piinormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FIN	Suomi	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
HUN	Magyarország	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξίνονους παράγοντες κατά την εργασία"»
HRV	Hrvatska	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemičkim na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
IRL	Éire	Decreto Legislativo 9 Aprile 2008, n.81
LTV	Lietuva	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
LVA	Latvija	Jsakymas dėl lietuvis higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
NOR	Norge	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NLD	Nederland	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
POL	Polska	Arbeidsomstandighedsregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
ROU	România	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SWE	Sverige	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVN	Slovenija	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
EU	OEL EU	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	TLV-ACGIH	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
		ACGIH 2021

SECTION 8. Exposure controls/personal protection ... / >>

POTASSIUM DICHROMATE

Threshold Limit Value						Remarks / Observations
Type	Country	TWA/8h		STEL/15min		
		mg/m ³	ppm	mg/m ³	ppm	
MAK	AUS	0.05		0.2		INHAL
VLEP	BEL	0.05				
MAK	CHE	0.05				INHAL
TLV	DNK	0.005		0.01		
VLA	ESP	0.05				Cr
VLEP	FRA	0.001		0.005		
HTP	FIN	0.005				Cr
AK	HUN			0.05		
OELV	IRL	0.05				Water Soluble
TLV	ROU	0.05				
NGV/KGV	SWE	0.005		0.015		
WEL	GBR	0.05				
TLV-ACGIH		0.05				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0	mg/l
Normal value for fresh water sediment	0.15	mg/kg/d
Normal value for marine water sediment	0.15	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					0,01 mg/m ³	VND	0,01 mg/m ³	VND

MERCURY (II) SULFATE

Threshold Limit Value						Remarks / Observations
Type	Country	TWA/8h		STEL/15min		
		mg/m ³	ppm	mg/m ³	ppm	
MAK	AUS	0.02		0.08		Hg compound
VLEP	BEL	0.02				Hg compound
MAK	CHE	0.02		0.16		INHAL
AGW	DEU	0.02		0.16		INHAL
TLV	DNK	0.025		0.05		Hg compound
VLA	ESP	0.02				Hg compound
VLEP	FRA	0.02				Hg compound
AK	HUN	0.08		0.32		Hg compound
OELV	IRL	0.02				Hg compound
NDS/NDSch	POL	0.02				Hg compound
TLV	ROU	0.02				Hg compound
NGV/KGV	SWE	0.03				Hg compound
WEL	GBR	0.025				Hg compound
OEL	EU	0.02				Hg compound
TLV-ACGIH		0.025				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							0,02 mg/m ³ 8h	VND

SECTION 8. Exposure controls/personal protection ... / >>

SILVER SULFATE

Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
MAK	AUS	0.01				INHAL	
VLEP	BEL	0.01				Ag compound	
MAK	CHE	0.01				Ag compound	
AGW	DEU	0.01				Ag compound	
TLV	DNK	0.01		0.02			
VLA	ESP	0.01				Ag compound	
VLEP	FRA	0.01				Ag compound	
AK	HUN	0.01				Ag compound	
NDS/NDSch	POL	0.05				Ag compound	
TLV	ROU	0.01				Ag compound	
NGV/KGV	SWE	0.01				Ag compound	
WEL	GBR	0.01				Ag compound	
OEL	EU	0.01				Ag compound	
TLV-ACGIH		0.01				Ag compound	
Predicted no-effect concentration - PNEC							
Normal value in fresh water						0.04	µg/L
Normal value in marine water						0.86	µg/L
Normal value for fresh water sediment						438	mg/kg
Normal value for marine water sediment						438	mg/kg
Normal value of STP microorganisms						0.025	mg/l
Normal value for the terrestrial compartment						0.794	mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

SULPHURIC ACID

Threshold Limit Value		SULPHURIC ACID				Remarks / Observations
Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	0.1		0.3		INHAL
VLEP	BEL	1		3		
TLV	BGR	1				
MAK	CHE	0.1		0.1		INHAL
TLV	CZE	1		2		
AGW	DEU	0.1		0.1		INHAL
MAK	DEU	0.1		0.1		INHAL
TLV	DNK	1				
VLA	ESP	0.05				
TLV	EST	1		3		
VLEP	FRA	0.05		3		THORA
HTP	FIN	0.05		0.1		
TLV	GRC	0.05				
AK	HUN	1		1		
GVI/KGVI	HRV	1		3		
VLEP	ITA	0.05				THORA
OELV	IRL	0.05	1			
RD	LTU	1		3		
RV	LVA	1				
TLV	NOR	0.1				
TGG	NLD	0.05				THORA
NDS/NDSch	POL	1		3		
TLV	ROU	0.5		1		
NGV/KGV	SWE	0.1		0.2		
NPEL	SVK	0.1		0.1		
MV	SVN	0.1				INHAL
WEL	GBR	0.05				THORA
OEL	EU	0.05				
TLV-ACGIH		0.2				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0.0025	mg/l
Normal value in marine water	0.00025	mg/l
Normal value for fresh water sediment	0.002	mg/kg
Normal value for marine water sediment	0.002	mg/kg
Normal value of STP microorganisms	8.8	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					0,1 mg/m3	VND	0,05 mg/m3	VND

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

POTASSIUM DICHROMATE

Cr (VI) - Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms ISO 16740 / NIOSH 7605 - Biological Values, ACGIH: 25 µg/L Total chromium in urine, GBR: 10 µmol chromium/mol creatinine in urine (Post shift), DEU: 20 µg/L Alkalichromate in Urin bei 0.05 mg/Kubikmeter in der Luft (Schichtende), ESP: 10 µg/L cromo total en orina (Principio y final dela jornada laboral), ROU: 10 µg/L crom total in urină (în timpul lucrului).

MERCURY (II) SULFATE

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norm ISO 17733 - Biological Values, ACGIH: 20 µg mercury/g creatinine in urine, GBR: 20 µmol mercury/mol creatinine in urine (Random), DEU: 25 µg Quecksilber/g Kreatinin Urin (keine Beschränkung) , ESP: 30 µg Mercurio inorgánico total/g creatinina en orina (Antes de la jornada laboral), ROU: 35 µg mercur/g creatină in urină (începutul schimbului următor).

SULPHURIC ACID

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norm OSHA ID-113.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

SECTION 8. Exposure controls/personal protection ... / >>

Personal protective equipment must be CE marked, showing that it complies with applicable standards.
Provide an emergency shower with face and eye wash station.
Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION
Protect hands with category III work gloves (see standard EN 374).
The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION
Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION
Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).
In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION
If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.
Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	dense liquid	
Colour	orange	
Odour	odourless	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	Not applicable	
Auto-ignition temperature	Not available	
pH	0.2	Method:ASTM D1293-18 Temperature: 25 °C
Kinematic viscosity	Not available	
Solubility	partially soluble in water	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1.66	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	86.32 %
Explosive properties	not applicable

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

SILVER SULFATE

Has a corrosive effect.

SULPHURIC ACID

SULPHURIC ACID 98%: Decomposes at 450°C/842°F, has a corrosive effect, strong oxidising agent.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

MERCURY (II) SULFATE

Sensitivity to light.

SILVER SULFATE

Sensitivity to light. Decomposes on exposure to light.

SULPHURIC ACID

SULPHURIC ACID 98%: Stable under standard ambient condition.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

POTASSIUM DICHROMATE

Risk of explosion with Iron, magnesium, hydrazine and derivatives, hydroxylamine, ammonium nitrate, Boron, Acetic anhydride, oxidisable substances, Reducing agents, sulphuric acid, silicon. Exothermic reaction with: anhydrides, phosphides, Sulphides, nitrides, Fluorine. Risk of ignition or formation of inflammable gases or vapours with organic combustible substances, glycerol, Powdered metals, hydrides, alkali compounds, Acetone, with, sulphuric acid. Generates dangerous gases or fumes in contact with hydrochloric acid.

MERCURY (II) SULFATE

Violent reactions possible with: Hydrogen halides.

SULPHURIC ACID

SULPHURIC ACID 98%: Violent reactions possible with: Water, Alkali metals, alkali compounds, Ammonia, Aldehydes, acetonitrile, Alkaline earth metals, alkalines, Acids, alkaline earth compounds, Metals, metal alloys, Oxides of phosphorus, phosphorus, hydrides, halogen-halogen compounds, oxyhalogenic compounds, permanganates, nitrates, carbides, combustible substances, organic solvent, acetylidene, Nitriles, organic nitro compounds, anilines, Peroxides, picrates, nitrides, lithium silicide, iron(III) compounds, bromates, chlorates, Amines, perchlorates, hydrogen peroxide.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

POTASSIUM DICHROMATE

Strong heating.

MERCURY (II) SULFATE

Strong heating.

10.5. Incompatible materials

SILVER SULFATE

Aluminium, Mild steel.

SULPHURIC ACID

SULPHURIC ACID 98%: Animal/vegetable tissues, Metals. Contact with metals liberates hydrogen gas.

10.6. Hazardous decomposition products

SULPHURIC ACID

SULPHURIC ACID 98%: Sulphur oxide.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

POTASSIUM DICHROMATE

Skin irritation, Rabbit, result: Irritating, Causes burns - Eye irritation: Causes serious eye damage, Risk of blindness! - Sensitisation test (Magnusson and Kligman) result: positive, Patch test human result: positive, May cause allergy or asthma symptoms or breathing difficulties if inhaled, May cause an allergic skin reaction - Carcinogenicity: May cause cancer - Mutagenicity: May cause genetic defects - Teratogenicity: May damage the unborn child - Reproductive toxicity: May damage fertility - Specific target organ toxicity, repeated exposure: Causes damage to organs through prolonged or repeated exposure.

MERCURY (II) SULFATE

Acute inhalation toxicity, absorption, Symptoms: Lung oedema, The substance has delayed effects - Acute dermal toxicity, LD50 rat: 625 mg/kg (Regulation (EC) No 1272/2008, Annex VI), absorption - Specific target organ toxicity, repeated exposure: May cause damage to organs through prolonged or repeated exposure.

SILVER SULFATE

Acute inhalation toxicity, Symptoms: Possible damages:, mucosal irritations - Acute dermal toxicity, Symptoms: After long-term exposure to the chemical, discolouration - Skin irritation rabbit, Result: No irritation - Eye irritation, rabbit, Result: Causes burns, Risk of permanent damage due to staining of the cornea. Causes serious eye damage.

SULPHURIC ACID

SULPHURIC ACID 98% - Skin irritation: causes severe burns - Eye irritation: causes serious eye damage, risk of blindness!

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	50.00 mg/kg
ATE (Dermal) of the mixture:	500.00 mg/kg

POTASSIUM DICHROMATE

LD50 (Oral):	90.5 mg/kg Rat
LD50 (Dermal):	14 mg/kg Rabbit
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation mists/powders):	0.088 mg/l/4h Rat

MERCURY (II) SULFATE

LD50 (Oral):	57 mg/kg Rat
STA (Oral):	0.5 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Dermal):	625 mg/kg Rat
STA (Dermal):	5 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

SILVER SULFATE

LD50 (Oral):	5000 mg/kg Rat - OECD 401
--------------	---------------------------

SULPHURIC ACID

LD50 (Oral):	2140 mg/kg Rat
--------------	----------------

SKIN CORROSION / IRRITATION

SECTION 11. Toxicological information ... / >>

Corrosive for the skin
Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

May cause damage to organs

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

MERCURY (II) SULFATE

Toxicity to algae, IC5 M.aeruginosa: 0.005 mg/l (maximum permissible toxic concentration).

POTASSIUM DICHROMATE

LC50 - for Fish	0.131 mg/l/96h <i>Lepomis macrochirus</i>
EC50 - for Crustacea	0.035 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0.31 mg/l/72h <i>Pseudokirchneriella subcapitata</i>
Chronic NOEC for Fish	6 mg/l/7d <i>Pimephales promelas</i>
Chronic NOEC for Crustacea	0.016 mg/l/7d <i>Daphnia</i>

MERCURY (II) SULFATE

LC50 - for Fish 0.19 mg/l/96h *Pimephales promelas*

SILVER SULFATE

EC50 - for Crustacea 0.004 mg/l/48h

SULPHURIC ACID

LC50 - for Fish	42 mg/l/96h <i>Gambusia affinis</i>
EC50 - for Crustacea	42.5 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h

12.2. Persistence and degradability

POTASSIUM DICHROMATE

Solubility in water > 10000 mg/l
Degradability: information not available

SULPHURIC ACID

Solubility in water 1000 - 10000 mg/l
Degradability: information not available

12.3. Bioaccumulative potential

POTASSIUM DICHROMATE

BCF 17.4

SILVER SULFATE

BCF 2.5

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

POTASSIUM DICHROMATE

Discharge into the environment must be avoided.

SECTION 12. Ecological information ... / >>

MERCURY (II) SULFATE
Discharge into the environment must be avoided.

SULPHURIC ACID
SULPHURIC ACID 98%: Biological effect: Forms corrosive mixture with water even if diluted, Harmful effect due to pH shift, Endangers drinking-water supplies if allowed to enter soil or water, Discharge into the environment must to be avoid.

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2922

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE, POTASSIUM DICHROMATE) MIXTURE

IMDG: CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE, POTASSIUM DICHROMATE) MIXTURE

IATA: CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE, POTASSIUM DICHROMATE) MIXTURE

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8 (6.1)



IMDG: Class: 8 Label: 8 (6.1)



IATA: Class: 8 Label: 8 (6.1)



14.4. Packing group

ADR / RID, IMDG, IATA: II

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 86 Limited Quantities: 1 L Tunnel restriction code: (E)

Special provision: -

IMDG: EMS: F-A, S-B Limited Quantities: 1 L

IATA: Cargo: Maximum quantity: 30 L

Pass.: Maximum quantity: 1 L

Special provision: A3, A803

Packaging instructions: 855
Packaging instructions: 851

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: H2-E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product		
Point	3	
Contained substance		
Point	75	
Point	47-72	POTASSIUM DICHROMATE REACH Reg.: 01-2119454792-32
Point	18	MERCURY (II) SULFATE

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Restricted explosives precursor

The acquisition, introduction, possession or use of that restricted explosives precursor by members of the general public is subject to a restriction as set out in Article 5(1) and (3). Restricted explosives precursors shall not be made available to, or introduced, possessed or used by members of the general public.

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

POTASSIUM DICHROMATE
REACH Reg.: 01-2119454792-32

Substances subject to authorisation (Annex XIV REACH)

POTASSIUM DICHROMATE
REACH Reg.: 01-2119454792-32
Sunset Date: 9/21/2017

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

MERCURY (II) SULFATE - (MERCURY COMPOUNDS)

Substances subject to the Stockholm Convention:

None

SECTION 15. Regulatory information ... / >>

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 3: Severe hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

SULPHURIC ACID

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Sol. 2	Oxidising solid, category 2
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Carc. 1B	Carcinogenicity, category 1B
Muta. 1B	Germ cell mutagenicity, category 1B
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 1	Acute toxicity, category 1
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Eye Dam. 1	Serious eye damage, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H350	May cause cancer.
H340	May cause genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H300	Fatal if swallowed.
H310	Fatal in contact with skin.
H300	Fatal if swallowed.
H330	Fatal if inhaled.
H311	Toxic in contact with skin.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

SECTION 16. Other information ... / >>

- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.