HI764-0 - Nitrite Ultra LR Reagent

Revision nr.5 Dated 13/03/2023 Printed on 13/03/2023 Page n. 1 / 10 Replaced revision:4 (Dated 10/09/2022) ΕN

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code HI764-0

Product name Nitrite Ultra LR Reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Determination of Nitrite in Water Samples.

1.3. Details of the supplier of the safety data sheet

Name Hanna Instruments S.R.L.

Full address str. Hanna Nr 1

District and Country 457260 loc. Nusfalau (Salaj)

Romania
Tel. +40 260607700
Fax +40 260607700

e-mail address of the competent person

responsible for the Safety Data Sheet msds@hanna.ro

1.4. Emergency telephone number

For urgent inquiries refer to International: +1 7035273887 - UK, London: +44 2038073798 - CHEMTREC 24

hours/365 days

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H332 Harmful if inhaled.

Skin corrosion, category 1A H314 Causes severe skin burns and eye damage.

Serious eye damage, category 1 H318 Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

EUH071 Corrosive to the respiratory tract.

Precautionary statements:

P260 Do not breathe dust, fume, gas, mist, vapours, spray.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

EN



Hanna Instruments S.R.L.

HI764-0 - Nitrite Ultra LR Reagent

Dated 13/03/2023 Printed on 13/03/2023 Page n. 2 / 10 Replaced revision:4 (Dated 10/09/2022)

SECTION 2. Hazards identification

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P310

Immediately call a POISON CENTER or doctor.

Contains:

POTASSIUM DISULFATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

POTASSIUM DISULFATE

INDEX 9 ≤ x < 17 Acute Tox. 3 H331, Skin Corr. 1A H314, Eye Dam. 1 H318, EUH071

EC 232-216-8 LC50 Inhalation mists/powders: 0,85 mg/l/4h

CAS 7790-62-7 REACH Reg. 01-2119987095-26 CHROMOTROPIC ACID DISODIUM SALT

INDEX 1 ≤ x < 5 Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335

EC 204-972-9 CAS 5808-22-0

TRANS-1,2-DIAMINOCYCLOHEXANE-N,N,N',N'-TETRACETIC ACID

INDEX $1 \le x < 5$ Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 236-308-9 CAS 125572-95-4

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

POTASSIUM DISULFATE

Irritation and corrosion, Cough, Shortness of breath. Risk of blindness!.

TRANS-1,2-DIAMINOCYCLOHEXANE-N,N,N',N'-TETRACETIC ACID Irritant effects, Nausea, Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available



HI764-0 - Nitrite Ultra LR Reagent

Revision nr.5 Dated 13/03/2023 Printed on 13/03/2023 Page n. 3 / 10 Replaced revision:4 (Dated 10/09/2022)

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

POTASSIUM DISUI FATE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)



HI764-0 - Nitrite Ultra LR Reagent

Pated 13/03/2023 Printed on 13/03/2023 Page n. 4 / 10 Replaced revision:4 (Dated 10/09/2022)

mg/m3

mg/m3

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

POTASSIUM DISULFATE

1 O I ROOI OIL BIOCEI TALE										
Predicted no-effect conc	entration - F	PNEC								
Normal value in fresh water							mg/l			
Normal value in marine water							mg/l			
Normal value for fresh water sediment							mg/kg/d			
Normal value for marine water sediment							mg/kg/d			
Normal value for water, intermittent release						6,8	mg/l			
Normal value of STP microorganisms						800	mg/l			
Normal value for the terrestrial compartment						0,092	mg/kg/d			
Health - Derived no-effect level - DNEL / DMEL										
	Effects on consumers Effects on work					vorkers				
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic		
	local	systemic	local	systemic	local	systemic	local	systemic		
Inhalation							0,13	0,13		

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYÉ PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Information

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Appearance solid powder Colour white Odour odourless Melting point / freezing point not available Initial boiling point not applicable Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point not applicable Auto-ignition temperature not available

ΕN

HI764-0 - Nitrite Ultra LR Reagent

SECTION 9. Physical and chemical properties

Decomposition temperature not available

2.9 - 3.2 Method:ASTM D1293-18

not available

Concentration: 2.8 % Temperature: 25 °C

Kinematic viscosity not available soluble in water Solubility Partition coefficient: n-octanol/water not available not available Vapour pressure Density and/or relative density 22 Relative vapour density not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

Particle characteristics

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 100,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

TRANS-1,2-DIAMINOCYCLOHEXANE-N,N,N',N'-TETRACETIC ACID Violent reactions possible with: Oxidizing agents.

10.4 Conditions to avoid

Avoid environmental dust build-up.

POTASSIUM DISULFATE Exposure to moisture.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

POTASSIUM DISULFATE

Acute inhalation toxicity, absorption, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages, damage of respiratory tract, Lung oedema, Symptoms may be delayed - Skin irritation (in analogy to similar products), Causes severe burns. -Eye irritation (in analogy to similar products), Causes serious eye damage. Risk of blindness!

TRANS-1,2-DIAMINOCYCLOHEXANE-N,N,N',N'-TETRACETIC ACID

Acute oral toxicity, Symptoms: Nausea, Vomiting - Symptoms: Possible damages, mucosal irritations - Skin irritation, Causes skin irritation - Eye irritation, Causes serious eye irritation.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available



HI764-0 - Nitrite Ultra LR Reagent

Revision nr.5 Dated 13/03/2023 Printed on 13/03/2023 Page n. 6 / 10 Replaced revision:4 (Dated 10/09/2022)

SECTION 11. Toxicological information

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

Corrosive to the respiratory tract.

POTASSIUM DISULFATE

LD50 (Oral): 2140 mg/kg Rat LC50 (Inhalation mists/powders): 0,85 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.



HI764-0 - Nitrite Ultra LR Reagent

Revision III: 5 Dated 13/03/2023 Printed on 13/03/2023 Page n. 7 / 10 Replaced revision:4 (Dated 10/09/2022)

SECTION 12. Ecological information

... / >>

12.1. Toxicity

POTASSIUM DISULFATE

LC50 - for Fish 680 mg/l/96h Pimephales promelas EC50 - for Crustacea 720 mg/l/48h Daphnia magna

12.2. Persistence and degradability

CHROMOTROPIC ACID DISODIUM SALT

Solubility in water > 10000 mg/l

12.3. Bioaccumulative potential

CHROMOTROPIC ACID DISODIUM SALT

Partition coefficient: n-octanol/water -4,48 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1759

14.2. UN proper shipping name

ADR / RID: CORROSIVE SOLID, N.O.S. (Potassium Disulfate mixture) IMDG: CORROSIVE SOLID, N.O.S. (Potassium Disulfate mixture) IATA: CORROSIVE SOLID, N.O.S. (Potassium Disulfate mixture)

HI764-0 - Nitrite Ultra LR Reagent

Revision nr.5 Dated 13/03/2023 Printed on 13/03/2023 Page n. 8 / 10 Replaced revision 4 (Dated 10/09/2022) ΕN

SECTION 14. Transport information

14.3. Transport hazard class(es)

ADR / RID: Class: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited Quantities: 5 kg Tunnel restriction code: (E)

Special provision: -

IMDG: EMS: F-A, S-B Limited Quantities: 5 kg

Label: 8

IATA: Cargo: Maximum quantity: 100 Kg Packaging instructions: 864
Pass.: Maximum quantity: 25 Kg Packaging instructions: 860

Special provision: A3, A803

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.



HI764-0 - Nitrite Ultra LR Reagent

Dated 13/03/2023 Printed on 13/03/2023 Page n. 9 / 10 Replaced revision:4 (Dated 10/09/2022)

SECTION 15. Regulatory information

... / >:

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3
Acute toxicity, category 3
Acute Tox. 4
Acute toxicity, category 4
Skin Corr. 1A
Eye Dam. 1
Eye Irrit. 2
Skin corrosion, category 1
Eye Irrit. 2
Eye irritation, category 2
Skin Irrit. 2
Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H331 Toxic if inhaled. H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H315 Causes skin irritation.

H335 May cause respiratory irritation. EUH071 Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament



HI764-0 - Nitrite Ultra LR Reagent

Revision nr.5 Dated 13/03/2023 Printed on 13/03/2023 Page n. 10 / 10 Replaced revision:4 (Dated 10/09/2022)

SECTION 16. Other information

- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

03 / 08 / 09 / 11 / 12.