

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Revision Date 27.03.2020

Version 1.2

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MCE 5.0UM WH PL 25MM 100/PK

REACH Registration

Number

Not applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

For additional information on uses please refer to the Merck

Chemicals portal (www.merckgroup.com).

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone: +49

6151 72-0

Responsible Department LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone Please contact the regional company representation in

number your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Flammable solid, Category 1, H228

For the full text of the H-Statements mentioned in this Section, see Section 16.

Catalogue No. Product name

INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

2.2 Label elements

Labelling.(REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word Danger

Hazard statements H228 Flammable solid.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Response

P370 + P378 In case of fire: Use powder for extinction.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word Danger

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P370 + P378 In case of fire: Use powder for extinction.

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature

Contains nitrocellulose.

3.1 Substance

Not applicable

3.2 Mixture

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration Classification

number

Octylphenol polyethoxyethanol (< 0,25 %)

9036-19-5 *)

Acute toxicity, Category 4, H302 Skin irritation, Category 2, H315 Serious eye damage, Category 1, H318

Short-term (acute) aquatic hazard, Category 1, H400 Long-term (chronic) aquatic hazard, Category 1, H410

M-Factor: 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Remove contact lenses.

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

Risk of methaemoglobin formation.

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water, Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Spontaneous ignition at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:

Page 3 of 26

^{*)} A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

Catalogue No. 638183

Product name

INDUSTRIAL PATCH TEST KIT

MCE 5.0UM WH PL 25MM 100/PK

nitrogen oxides, nitrous gases

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep away from heat and sources of ignition. Keep away from direct sunlight.

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Performing regular visual inspections of membranes and keeping accurate records of recommended shelf life can reduce the risk of membrane deterioration. Shelf-life limited when kept above +25°C. Verify on a regular basis expiry dates of stored materials, housekeeping, temperature and humidity. Designated "Flammable Material" storage areas must be engineered according to local regulations. Rotate stock. Improper storage conditions can accelerate deterioration of the membrane in advance of expiration date. Storage humidity: 30 - 70 %. Perform regular visual inspections of stored materials to ensure early stages of deterioration does not advance. Early stages of deterioration: Amber or yellow discoloration. Advanced stages of deterioration: visible liquid or solid brown resin. If membrane shows visual indications of deterioration, safely dispose of product according to local regulations.

There is an 18 month expiration date given to all triton-free nitrocellulose membranes. Storage under improper conditions could lead to the membrane self-decomposing at ambient temperatures with the formation of nitrous vapors or self ignition.

Recommended storage temperature see product label.

Advice on common storage

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

The data applies to the entire pack.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection Safety glasses

Hand protection

full contact:

Glove material: Nitrile rubber Glove thickness: 0,11 mm

Page 5 of 26

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Break through time: 480 min

splash contact:

Glove material: Nitrile rubber Glove thickness: 0,11 mm
Break through time: 480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment protective clothing

Respiratory protection

required when dusts are generated.

Recommended Filter type: Filter P 1 (acc. to DIN 3181) for solid particles of inert substances

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form solid

Colour white

Odour No strong odour known.

Odour Threshold No information available.

pH No information available.

Melting point No information available.

Boiling point No information available.

Flash point No information available.

Evaporation rate No information available.

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Flammability (solid, gas) The substance or mixture is a flammable solid with the

category 1.

The substance or mixture is a flammable solid with the

category 1.

Lower explosion limit No information available.

Upper explosion limit No information available.

Vapour pressure No information available.

Relative vapour density No information available.

Density No information available.

Relative density No information available.

Water solubility No information available.

Partition coefficient: n-

octanol/water

No information available.

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Not classified as explosive.

Oxidizing properties none

none

9.2 Other data

none

SECTION 10. Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

Product is sensitive to light and moisture.

Prolonged exposure to air may cause discolouration.

Catalogue No. 638183

Product name

INDUSTRIAL PATCH TEST KIT

MCE 5.0UM WH PL 25MM 100/PK

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Oxidizing agents, Bases, Strong acids

10.4 Conditions to avoid

Heating (decomposition). Exposure to sunlight.

10.5 Incompatible materials

no information available

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects Mixture

Acute oral toxicity

This information is not available.

Acute inhalation toxicity

This information is not available.

Acute dermal toxicity

This information is not available.

Skin irritation

This information is not available.

Eye irritation

This information is not available.

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

11.2 Further information

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

After uptake:

Risk of methaemoglobin formation.

However, when the product is handled appropriately, hazardous effects are unlikely to occur.

Handle in accordance with good industrial hygiene and safety practice.

Components

Octylphenol polyethoxyethanol

Acute oral toxicity

LD50 Rat: 1.900 - 5.000 mg/kg (External MSDS)

Acute dermal toxicity

LD50 Rabbit: > 3.000 mg/kg (External MSDS)

Skin irritation Rabbit Result: irritating

OECD Test Guideline 404

The value is given in analogy to the following substances:

Sensitisation

Sensitisation test: human

Result: negative (External MSDS)

SECTION 12. Ecological information

Mixture

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

Additional ecological information

Discharge into the environment must be avoided.

Components

Octylphenol polyethoxyethanol

Toxicity to fish

semi-static test LC50 Leuciscus idus (Golden orfe): 0,26 mg/l; 96 h

Analytical monitoring: yes

OECD Test Guideline 203 The value is given in analogy to the following substances:

Toxicity to daphnia and other aquatic invertebrates

static test EC50 Daphnia magna (Water flea): 0,011 mg/l; 48 h (ECOTOX Database) The value is

given in analogy to the following substances:

Page 9 of 26

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Toxicity to algae

static test EC50 Pseudokirchneriella subcapitata (green algae): 1,9 mg/l; 96 h (ECHA) The value is given in analogy to the following substances:

Toxicity to fish (Chronic toxicity)

flow-through test Danio rerio (zebra fish): 0,012 mg/l

Analytical monitoring: yes

OECD Test Guideline 210 The value is given in analogy to the following substances:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) semi-static test NOEC Daphnia magna (Water flea): 0,03 mg/l; 21 d

Analytical monitoring: yes

OECD Test Guideline 202 The value is given in analogy to the following substances:

Biodegradability 22 %; 28 d; aerobic OECD Test Guideline 301C

Not readily biodegradable.

M-Factor

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 3270

14.2 Proper shipping NITROCELLULOSE MEMBRANE FILTERS

name

14.3 Class 4.1 **14.4 Packing group** II **14.5 Environmentally** --

hazardous

14.6 Special precautions yes

for user

Tunnel restriction code E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

14.1 UN number UN 3270

14.2 Proper shipping NITROCELLULOSE MEMBRANE FILTERS

name

14.3 Class 4.1 **14.4 Packing group** II **14.5 Environmentally** --

hazardous

14.6 Special precautions no

for user

Sea transport (IMDG)

14.1 UN number UN 3270

14.2 Proper shipping NITROCELLULOSE MEMBRANE FILTERS

name

14.3 Class 4.1 14.4 Packing group II 14.5 Environmentally --

hazardous

14.6 Special precautions yes

for user

EmS F-A S-I

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

THIS TRANSPORT DATA APPLIES TO THE ENTIRE PACK!

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard 96/82/EC

Legislation Directive 96/82/EC does not apply

SEVESO III Not applicable

Occupational restrictions Take note of Dir 94/33/EC on the protection of young

people at work.

Regulation (EC) No 1005/2009 on substances not regulated

that deplete the ozone layer

Regulation (EC) No 850/2004 of the not regulated

European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

Page 11 of 26

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Substances of very high concern (SVHC)

This product does contain substances

of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 59 above the respective regulatory concentration

limit of > 0.1 % (w/w).

Contains: Octylphenol polyethoxyethanol

National legislation

Storage class 4.1B
The data applies to the entire pack.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

| H228 | Flammable solid. |
|------|-------------------------------------------------------|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word Danger

Hazard statements H228 Flammable solid.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Response

P370 + P378 In case of fire: Use powder for extinction.

Page 12 of 26

Catalogue No. Product name

638183

INDUSTRIAL PATCH TEST KIT MCE 5.0UM WH PL 25MM 100/PK

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org. Millipore Ref. XX6504730

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Revision Date 27.03.2020

Version 1.2

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic,

5.0 µm, 47 mm, white, plain

REACH Registration

Number

Not applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

For additional information on uses please refer to the Merck

Chemicals portal (www.merckgroup.com).

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone: +49

6151 72-0

Responsible Department LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone Please contact the regional company representation in

number your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Flammable solid, Category 1, H228

For the full text of the H-Statements mentioned in this Section, see Section 16.

Catalogue No. 63

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

2.2 Label elements

Labelling.(REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word Danger

Hazard statements H228 Flammable solid.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Response

P370 + P378 In case of fire: Use powder for extinction.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word Danger

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P370 + P378 In case of fire: Use powder for extinction.

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature

Contains nitrocellulose.

3.1 Substance
Not applicable

3.2 Mixture

Catalogue No. 63818

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration Classification

number

Octylphenol polyethoxyethanol (< 0,25 %)

9036-19-5 *)

Acute toxicity, Category 4, H302 Skin irritation, Category 2, H315 Serious eye damage, Category 1, H318

Short-term (acute) aquatic hazard, Category 1, H400 Long-term (chronic) aquatic hazard, Category 1, H410

M-Factor: 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Remove contact lenses.

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

Risk of methaemoglobin formation.

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water, Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Spontaneous ignition at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

Page 16 of 26

^{*)} A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Fire may cause evolution of: nitrogen oxides, nitrous gases

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep away from heat and sources of ignition. Keep away from direct sunlight.

Page 17 of 26

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Performing regular visual inspections of membranes and keeping accurate records of recommended shelf life can reduce the risk of membrane deterioration. Shelf-life limited when kept above +25°C. Verify on a regular basis expiry dates of stored materials, housekeeping, temperature and humidity. Designated "Flammable Material" storage areas must be engineered according to local regulations. Rotate stock. Improper storage conditions can accelerate deterioration of the membrane in advance of expiration date. Storage humidity: 30 - 70 %. Perform regular visual inspections of stored materials to ensure early stages of deterioration does not advance. Early stages of deterioration: Amber or yellow discoloration. Advanced stages of deterioration: visible liquid or solid brown resin. If membrane shows visual indications of deterioration, safely dispose of product according to local regulations.

There is an 18 month expiration date given to all triton-free nitrocellulose membranes. Storage under improper conditions could lead to the membrane self-decomposing at ambient temperatures with the formation of nitrous vapors or self ignition.

Recommended storage temperature see product label.

Advice on common storage

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

The data applies to the entire pack.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection Safety glasses

Hand protection

full contact:

Glove material: Nitrile rubber

Page 18 of 26

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Glove thickness: 0,11 mm Break through time: 480 min

splash contact:

Glove material: Nitrile rubber Glove thickness: 0,11 mm
Break through time: 480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment protective clothing

Respiratory protection

required when dusts are generated.

Recommended Filter type: Filter P 1 (acc. to DIN 3181) for solid particles of inert substances

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form solid

Colour white

Odour No strong odour known.

Odour Threshold No information available.

pH No information available.

Melting point No information available.

Boiling point No information available.

Flash point No information available.

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Evaporation rate No information available.

Flammability (solid, gas) The substance or mixture is a flammable solid with the

category 1.

The substance or mixture is a flammable solid with the

category 1.

Lower explosion limit No information available.

Upper explosion limit No information available.

Vapour pressure No information available.

Relative vapour density No information available.

Density No information available.

Relative density No information available.

Water solubility No information available.

Partition coefficient: n-

octanol/water

No information available.

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic No information available.

Explosive properties Not classified as explosive.

Not classified as explosive.

Oxidizing properties none

none

9.2 Other data

none

SECTION 10. Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

Page 20 of 26

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Product is sensitive to light and moisture.

Prolonged exposure to air may cause discolouration.

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Oxidizing agents, Bases, Strong acids

10.4 Conditions to avoid

Heating (decomposition). Exposure to sunlight.

10.5 Incompatible materials

no information available

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects Mixture

Acute oral toxicity

This information is not available.

Acute inhalation toxicity

This information is not available.

Acute dermal toxicity

This information is not available.

Skin irritation

This information is not available.

Eye irritation

This information is not available.

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Aspiration hazard

This information is not available.

11.2 Further information

After uptake:

Risk of methaemoglobin formation.

However, when the product is handled appropriately, hazardous effects are unlikely to occur.

Handle in accordance with good industrial hygiene and safety practice.

Components

Octylphenol polyethoxyethanol

Acute oral toxicity

LD50 Rat: 1.900 - 5.000 mg/kg (External MSDS)

Acute dermal toxicity

LD50 Rabbit: > 3.000 mg/kg (External MSDS)

Skin irritation Rabbit Result: irritating

OECD Test Guideline 404

The value is given in analogy to the following substances:

Sensitisation

Sensitisation test: human

Result: negative (External MSDS)

SECTION 12. Ecological information

Mixture

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

Additional ecological information

Discharge into the environment must be avoided.

Components

Octylphenol polyethoxyethanol

Catalogue No. Product name

638183

INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

Toxicity to fish

semi-static test LC50 Leuciscus idus (Golden orfe): 0,26 mg/l; 96 h

Analytical monitoring: yes

OECD Test Guideline 203 The value is given in analogy to the following substances:

Toxicity to daphnia and other aquatic invertebrates

static test EC50 Daphnia magna (Water flea): 0,011 mg/l; 48 h (ECOTOX Database) The value is

given in analogy to the following substances:

Toxicity to algae

static test EC50 Pseudokirchneriella subcapitata (green algae): 1,9 mg/l; 96 h (ECHA) The value is

given in analogy to the following substances:

Toxicity to fish (Chronic toxicity)

flow-through test Danio rerio (zebra fish): 0,012 mg/l

Analytical monitoring: yes

OECD Test Guideline 210 The value is given in analogy to the following substances:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) semi-static test NOEC Daphnia magna (Water flea): 0,03 mg/l; 21 d

Analytical monitoring: yes

OECD Test Guideline 202 The value is given in analogy to the following substances:

Biodegradability 22 %; 28 d; aerobic OECD Test Guideline 301C

Not readily biodegradable.

M-Factor 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 3270

14.2 Proper shipping NITROCELLULOSE MEMBRANE FILTERS

name

14.3 Class 4.1 **14.4 Packing group** II **14.5 Environmentally** --

hazardous

14.6 Special precautions yes

for user

Tunnel restriction code E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number UN 3270

14.2 Proper shipping NITROCELLULOSE MEMBRANE FILTERS

name

14.3 Class 4.1 14.4 Packing group II 14.5 Environmentally -hazardous

14.6 Special precautions no

for user

Sea transport (IMDG)

14.1 UN number UN 3270

14.2 Proper shipping NITROCELLULOSE MEMBRANE FILTERS

name

14.3 Class 4.1 **14.4 Packing group** II **14.5 Environmentally** --

hazardous

14.6 Special precautions yes

for user

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

EmS F-A S-I

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

THIS TRANSPORT DATA APPLIES TO THE ENTIRE PACK!

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard

96/82/EC

Legislation

Directive 96/82/EC does not apply

SEVESO III Not applicable

Occupational restrictions

Take note of Dir 94/33/EC on the protection of young

people at work.

Regulation (EC) No 1005/2009 on substances not regulated

that deplete the ozone layer

Regulation (EC) No 850/2004 of the

not regulated

European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

Substances of very high concern (SVHC)

This product does contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 59 above the respective regulatory concentration

limit of > 0.1 % (w/w).

Contains: Octylphenol polyethoxyethanol

National legislation

Storage class 4.1B
The data applies to the entire pack.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

Catalogue No. 638183

Product name INDUSTRIAL PATCH TEST KIT

MF-Millipore Membrane, mixed cellulose esters, Hydrophilic, 5.0

μm, 47 mm, white, plain

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

| H228 | Flammable solid. |
|------|-------------------------------------------------------|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word Danger

Hazard statements H228 Flammable solid.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Response

P370 + P378 In case of fire: Use powder for extinction.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Millipore Ref. XX6504730

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

Page 26 of 26