

USB data logger temperature

testo 184 T1
testo 184 T2
testo 184 T3

- Clear alarm indication
- Easiest operation
- Easiest configuration without software installation
- Convenient readout thanks to automatic PDF report
- Mobile readout by NFC possible
- IT safe (no installation, no download)



Illustration 1:1



With the testo 184 data loggers, you monitor every step of your cold chain in the transport of sensitive goods by rail, in the air or on the road.

testo 184 T1 and testo 184 T2 are designed as loggers with a built-in battery for use over a limited time, and therefore ideal for one-way transports.

testo 184 T3, with its exchangeable battery, is the ideal logger for inhouse logistics.

At their destination, you see at a glance whether the configured limit values have been adhered to. In order to obtain detailed information, it is sufficient to connect the logger to a PC – a PDF report is immediately generated with all relevant data.

In order for you to be able to work even more efficiently and conveniently with the data loggers, all required files and information are stored directly and securely in the respective testo 184: Configuration file, acceptance test certificate, instruction manual and PDF report of your recorded data.


Technical data

testo 184 T1

USB data logger testo 184 T1 for temperature, operating duration 90 days

Available in packages of 1, 10 and 50 off.

Part no. 0572 1841




testo 184 T3

USB data logger testo 184 T3 for temperature, unlimited operating duration thanks to exchangeable battery

Available in packages of 1, 10 and 50 off.

Part no. 0572 1843





testo 184 T2

USB data logger testo 184 T2 for temperature, operating duration 150 days

Available in packages of 1, 10 and 50 off.

Part no. 0572 1842





| Sensor | |
|-----------------------|----------------------|
| Measurement parameter | Temperature |
| Temperature sensor | NTC sensor, internal |
| Measuring range | -35 to +70 °C |
| Accuracy | ±0.5 °C |
| Resolution | 0.1 °C |

General technical data

| | testo 184 T1 | testo 184 T2 | testo 184 T3 |
|-----------------------|--|-----------------------------------|--|
| Power supply | Lithium battery, non-exchangeable | Lithium battery, non-exchangeable | Lithium battery CR2450 3V, exchangeable |
| Operating time | 90 days | 150 days | Unlimited |
| Battery life | — | — | 500 days (at +25 °C and 15 mins measurement rate). |
| Measuring rate | 1 min to 24 h | 1 min to 24 h | 1 min to 24 h |
| Memory | 16,000 readings | 40,000 readings | 40,000 readings |
| Alarm identification | by LEDs | by LEDs and display | by LEDs and display |
| Dimensions | 33 x 9 x 74 mm | 44 x 12 x 97 mm | 44 x 12 x 97 mm |
| Weight | 25 g | 45 g | 45 g |
| Protection class | IP67 | | |
| Operating temperature | -35 to +70 °C | | |
| Storage temperature | -55 to +70 °C | | |
| Scope of delivery | Data logger, temperature calibration certificate (stored as a PDF in the instrument), battery CR2450 | | |
| Tests, certificates | <ul style="list-style-type: none"> · EN 12830-certified (C,D) · Certified by HACCP International · testo ComSoft CFR software (V4.3 SP2 or higher) compatible with CFR 21 Part 11 | | |
| Warranty | testo 184 T1/T2: 12-month warranty from the production date, production date: see circled date code (MMDD) on the identification plate. | | testo 184 T3: 24-month warranty, warranty terms: see website www.testo.com/warranty |


Accessories

| testo 184 T1/T2/T3 | Part no. |
|---|-----------|
| Mobile printer for data loggers testo 175/176/184 | 0572 0576 |
| ComSoft Professional, Pro software incl. data archiving | 0554 1704 |
| ComSoft CFR 21 Part 11, Software for requirements according to CFR 21 Part 11 for Testo data loggers | 0554 1705 |
| ISO calibration certificate/temperature, temperature probe; calibration points -18°C; 0°C; +60°C per channel/instrument | 0520 0151 |

| testo 184 T2/T3 | Part no. |
|----------------------------|-----------|
| Wall bracket for testo 184 | 0554 1841 |

| testo 184 T3 | Part no. |
|----------------------------|-----------|
| Lithium battery CR2450 3 V | 0515 5841 |

Software on board



The screenshot shows the 'testo' configuration tool interface. It includes sections for 'Choose Model' (T1, T2, T3, T4, H1, G1), 'Expert Mode' (YES, NO), 'General Information' (Report Language, Report Title, Report Time Zone, Comment), 'Device Configuration' (Meas. Interval, Start Setting, Start Date/Time, Start Delay, Stop Setting, Stop Date/Time, LCD Enable, LED Enable, Time Mark Enable, NFC, Date/Time Format, MKT Activation Energy, Remaining Battery), and 'Alarm Settings' (Temperature, Humidity, Shock, Limit Value/Unit, Alarm Type, Allowed Time). A button at the bottom says 'Please click here to transfer the configuration data to the data logger:' with an arrow icon.

No software needs to be installed on a PC or notebook in order to configure a testo 184 data logger. The PDF configuration tool is stored on the logger itself and can be opened with a simple double-click.

No download or installation required whatsoever. After setting the relevant parameters, the configuration is simply stored on the logger – and it's ready to use!

When the logger is plugged in to a PC after a completed measurement, a PDF report with all relevant data, the programming and a graph showing the value curve is created and stored in the logger. A double-click allows it to be opened and printed out, or forwarded by e-mail.

If advanced read-out options are required, the customer can obtain these by purchasing ComSoft Professional. In order to achieve the conformity to 21 CFR Part 11 which is often required in the pharmaceutical field, there is a special software available as an accessory.



DOMINIQUE DUTSCHER SAS

Subject to change without notice.

1981 0214/msp/06.2017