



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : ANIOGEL 85 NPC
Product code : 1644000.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Disinfection of healthy skin
For further information on product indication, please see the label.

1.3. Details of the supplier of the safety data sheet

Registered company name : Laboratoires ANIOS.
Address : PAVE DU MOULIN .59260.LILLE - HELLEMMES.FRANCE.
Telephone : + 33 (0)3 20 67 67 67. Fax : + 33 (0)3 20 67 67 68.
e:mail : fds@anios.com
www.anios.com

1.4. Emergency telephone number : + 33(0)1 45 42 59 59.

Association/Organisation : INRS.

Other emergency numbers

New Zealand: 0800 764 766 (National Poisons centre)
Australia : 13 11 26 (National Poisons centre)

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).
Eye irritation, Category 2 (Eye Irrit. 2, H319).
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS02

Signal Word :

DANGER

Hazard statements :

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements - General :

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from sparks and open flames. No smoking.

Precautionary statements - Response :

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements - Storage :

P403

Store in a well-ventilated place.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

No other hazard identified in the current state of knowledge.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43 ETHYL ALCOHOL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1]	50 \leq x % < 100
INDEX: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25 PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 \leq x % < 2.5

Information on ingredients :

Title for H, EUH and R indications: see § 16.

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

Move the person away from the place of exposure and take him/her outside.

In the event of splashes or contact with eyes :

If applicable, remove contact lenses.

Wash thoroughly with soft clean water for 15 minutes, holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist. Show this container or label.

In the event of swallowing :

Rinse out the mouth, do not induce vomiting, keep the person calm and take him/her to a clinic or a doctor's. Show the container or label.

4.2. Most important symptoms and effects, both acute and delayed

Cf. § 11

4.3. Indication of any immediate medical attention and special treatment needed

Refer to the recommendation of the doctor.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Move oxidising products away from the fire.

Move any flammable materials away from the fire.

5.1. Extinguishing media**Suitable methods of extinction**

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Use powder or foam extinguishers.

Special foams for polar liquids, powders and carbon dioxide.

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Full protective suit.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

- Consult the safety measures listed under headings 7 and 8.
- Eliminate any possible source of ignition and ventilate the premises.
- Keep away any unprotected person.
- Move all flammable sources out of danger and keep them away from the scene.

6.2. Environmental precautions

- Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.
- Do not get rid in natural spaces (waterways, ground and vegetations...)

6.3. Methods and material for containment and cleaning up

- Absorb any spilled product with absorbent non-combustible materials, and sweep away or remove with a shovel. Put any waste in drums for disposal. Do not mix with any other waste. Wash the contaminated surface thoroughly with water.
- For small quantities, dilute the product with large quantities of water and rinse away.
- Do not collect the product for re-use.

6.4. Reference to other sections

- Disposal considerations: see section 13.

SECTION 7 : HANDLING AND STORAGE**7.1. Precautions for safe handling**

- Product for external use - do not swallow.
- Handle in accordance with user instructions on label
- Handle at a temperature not exceeding 45° C.
- Handle in well-ventilated premises.

Fire prevention :

- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Do not use tools which may produce sparks. Do not smoke.
- Keep away from flammable materials
- Keep away from sources of ignition - no smoking.

Recommended equipment and procedures :

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Avoid eye contact with this mixture.
- Packages which have been opened must be reclosed carefully and stored in an upright position.
- Water source nearby.

7.2. Conditions for safe storage, including any incompatibilities

- Keep in the original container only, in a cool and well-ventilated place, away from all sources of ignition, heat and direct sunlight.
- Keep the container tightly closed
- Store away from incompatible materials (see section 10)
- Always transport and store the containers upright.
- Recommended storage temperature: from +5°C to +25°C.
- Splash pan for high quantities' storage
- Do not use after the expiry date mentioned on the packaging.
- Keep out of the reach of children

7.3. Specific end use(s)

- Refer to paragraph 1 for product indication

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

The information in this chapter refers to the product specifically described in this document. If the product is handled and/or exposed simultaneously with other chemical agents, these must be taken into consideration when choosing personal safety equipment.

The Exposure Threshold Limit Value and the Average Exposure Value given below are quoted by the CAS number of the substance. Paragraph 3 details the chemical name corresponding to the CAS number.

8.1. Control parameters**Occupational exposure limits :**

- France (INRS - ED984 :2012) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84

67-63-0	-	-	400	980	-	84
---------	---	---	-----	-----	---	----

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1920 mg/m ³				
67-63-0	400 ppm 999 mg/m ³	500 ppm 1250 mg/m ³			

- Belgium (Order of 19/05/2009, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1907 mg/m ³				
67-63-0	200 ppm 500 mg/m ³	400 ppm 1000 mg/m ³			

- Poland (2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1900 mg/m ³				
67-63-0	900 mg/m ³	1200 mg/m ³			

- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), Mayo 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1910 mg/m ³				
67-63-0	400 ppm 998 mg/m ³	500 ppm 1250 mg/m ³			

- Czech Republic (Regulation No. 361/2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 mg/m ³	3000 mg/m ³			
67-63-0	500 mg/m ³	1000 mg/m ³		I	

- Slovakia (Regulation No. 300/2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	500 ppm 960 mg/m ³	1920 mg/m ³			
67-63-0	200 ppm 500 mg/m ³	1000 mg/m ³			

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
64-17-5		500 ppm 960 mg/m ³		2(II)
67-63-0		200 ppm 500 mg/m ³		2(II)

- Switzerland (SUVA 2015) :

CAS	VME	VLE	Valeur plafond	Notations
64-17-5	500 ppm 960 mg/m ³	1000 ppm 1920 mg/m ³		SSC
67-63-0	200 ppm 500 mg/m ³	400 ppm 1000 mg/m ³		B SSC

8.2. Exposure controls

Suitable technical inspections

Ensure the rooms are well-ventilated. Atmospheric concentrations at the workplace must not exceed the limit values given for normal conditions of use.

- Eye / face protection

Avoid contact with eyes.
Water source nearby.

- Hand protection

Not applicable.

- Body protection

Not applicable.

HEALTH MEASURES:

Do not eat, drink or smoke during use.

- Respiratory protection

Not applicable in normal conditions of use.
Avoid product's inhalation

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Viscous liquid.
------------------	-----------------

Important health, safety and environmental information

pH :	5.25 .
	Neutral.
Boiling point/boiling range :	> 35°C
Flash Point :	22.50 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	+/- 0.86
Water solubility :	Soluble.
Viscosity :	+/- 2200 mPa.s
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

9.2. Other information

Colour:	colourless
Odour :	typical of alcohol

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No hazardous reaction if the instructions/indications for storage and handling are respected.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

Cf. § 10.1 and 10.2

10.4. Conditions to avoid

Avoid exposure to heat.

10.5. Incompatible materials

Keep away from :

- combustible material

Do not mix with other products.

10.6. Hazardous decomposition products

At high temperatures, dangerous decomposition products may be produced, such as fumes, carbon dioxide and carbon monoxide, nitrogen oxide.

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****11.1.1. Substances**

Not specified

11.1.2. Mixture**Acute toxicity :**

Acute toxicity estimate (ATE)* :

Oral ATE : > 2000 mg/kg

* according to the method of calculation describe in the CLP regulation (Classification, Labelling, Packaging) Part 3 Chapter 3.1 based on the data of the different components present in the product.

Ingestion may lead to irritation of the digestive system, abdominal pain, headaches and nausea.

Serious damage to eyes/eye irritation :

Ocular irritation: notably redness of the conjunctiva and lacrimation.

Other information

Assessment of cutaneous tolerance in healthy volunteer (similar preparation):

Good cutaneous compatibility (48 h occlusive patch in 10 volunteers)

No evidence of skin sensitization (HRIPT)

SECTION 12 : ECOLOGICAL INFORMATION**12.1. Toxicity**

12.1.2. Mixtures

The mixture has not been classified as an environmental hazard, in compliance with EC regulation 1272/2008.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

The packages must not be reused.

Do not pour into waterways.

13.1. Waste treatment methods**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

20 01 29 * detergents containing dangerous substances

18 01 06 * chemicals consisting of or containing dangerous substances

For information :

The waste code must be determined by the user, according to the application of the product.

The following waste codes are given as guidelines only.

18 = Wastes from human or animal health care and/or related research (except kitchen and restaurant wastes not arising from immediate health care)

20 = Municipal wastes and similar commercial, industrial and institutional wastes including separately collected fractions

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2016).

14.1. UN number

1170

14.2. UN proper shipping name

UN1170=ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	1 L	144 601	E2	2	D/E

ANIOGEL 85 NPC - 1644000

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ		
	3	-	II	1 L	F-E,S-D	144	E2		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	A3 A58 A180	E2
	3	-	II	Y341	1 L	-	-	A3 A58 A180	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Regulation EC 1272/2008 modified by regulation EC 618/2012
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

15.2. Chemical safety assessment

Information from the chemical safety assessment of substances present in the product is included in the appropriate sections of this safety data sheet, whenever necessary.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture.

It is recommended that the information contained in this safety data sheet is provided to the users, if necessary in an appropriate form.

This information relates to the specifically designated product and may not be valid in combination with any another product. The product must not be used for applications other than those specified in heading 1 without having first obtained written handling instructions.

UPDATES SINCE PREVIOUS VERSION

- Implementation of classification and labelling in compliance with EC regulation 1272/2008.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame

GHS07 : Exclamation mark