

BenchMixer™

Benchmark Vortex Mixer



- Powerful Motor for INSTANT Vortexing
- Q-Drive™ Dynamic Balance System
- Touch or Continuous Operation
- Variable Speed Control from 200 to 3200rpm



Technical Data:

Speed Range:	200 to 3200 rpm
Operating Modes:	Touch or continuous
Operating Temp. Range:	+4 C to +65 C
Dimensions:	13 x 16 x 17 cm
	5 x 6.3 x 6.7 in.
Weight:	3.8 kg / 8.4 lb
Electrical:	115V AC, 60 Hz, 1.5A
	230V AC, 50 Hz, 0.75A
Warranty:	2 years

The BenchMixer™ sets the new standard in vortex mixing. With advanced Q-Drive™ technology, the BenchMixer™ provides smooth instant vortexing of even the largest sample sizes, including full 50ml tubes. The unique counter balance system creates maximum vortexing action, while minimizing noise and excessive vibration. This results in quieter, more efficient and longer lasting operation.

Other features include: “no-walk” suction feet, cold room/incubator compatibility and spill-proof electronic controls.

Ordering Information

BV1000* BenchMixer Vortex Mixer

Optional Accessories:

BV1000-FLAT	Optional 3 inch flat head
BV1000-COMBO	Optional head for tubes and microplate. 66 tubes (38 x 1.5ml and 28 x 0.5ml) or 1 microplate
BV1000-H15	Optional head for 12 x 1.5/2.0ml, horizontal
BV1000-H150	Optional head for 4 x 15ml, horizontal
BV1000-H500	Optional head for 2 x 50ml, horizontal

* To order a product in 230V, please add -230 to item number.

Benchmark
Scientific

Benchmark Scientific Inc.
PO Box 709 Edison, NJ 08817
Phone: 908-769-5555
Fax: 908-222-1864
Web: www.BenchmarkScientific.com
Email: Info@BenchmarkScientific.com