

100 μ L, Model 710 N SYR, Cemented NDL, 22s ga, 2 in, point style 3

Specification Sheet (Part# 80665)



Product Specifications

Volume	100 μ L
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	1.13 μ L
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F

Product Specifications

Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.061 inches (1.46 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

HAMILTON 

Web: www.hamiltoncompany.com

USA: +1-800-648-5950

Europe: +41 58 610 10 10

Hamilton Americas & Pacific Rim

Hamilton Company Inc.
4970 Energy Way
Reno, Nevada 89502 U.S.A.
Tel: +1-800-648-5950
Fax: +1-775-856-7259
sales@hamiltoncompany.com

Hamilton Europe, Asia, & Africa

Hamilton Bonaduz A.G.
Via Crusch 8
CH-7402 Bonaduz, Switzerland
Tel: +41 58 610 10 10
Fax: +41-58-610-00-10
contact@hamilton.ch

© 2016 Hamilton Company. All Rights Reserved.

All trademarks are owned and/or registered by Hamilton Company in the U.S. and/or other countries.

Revision: A / 2010-05-11 Printed in the U.S.A.

To find a representative in your area, please visit hamiltoncompany.com/contacts