

# 10 $\mu$ L, Model 901 N SYR, Cemented NDL, 26s ga, 2 in, point style 2

Specification Sheet (Part# 80360)



## Product Specifications

Volume	10 $\mu$ L
Syringe Type	Microliter
Syringe Series	900
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	2
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.005 inches (0.13 mm)
Needle Outer Diameter	0.0187 inches (0.47 mm)
Std. Needle Dead Volume	0.64 $\mu$ L
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes

## Product Specifications

Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.019 inches (0.485 mm)
Barrel Outer Diameter	0.260 inches (6.60 mm)
Sales Quantity	1 syringe per pack

MINIQUÉ DUTSCHER SAS

© 2015 Hamilton Company. All Rights Reserved.

All trademarks are owned and/or registered by Hamilton Company in the U.S. and/or other countries.

Revision: A / 2010-05-11 Printed in the U.S.A.

**HAMILTON** 

Web: [www.hamiltoncompany.com](http://www.hamiltoncompany.com)

USA: +1-800-648-5950

Europe: +41 58 610 10 10

#### Hamilton Americas & Pacific Rim

Hamilton Company Inc.  
4970 Energy Way  
Reno, Nevada 89502 U.S.A.  
Tel: +1-800-648-5950  
Fax: +1-775-856-7259  
[sales@hamiltoncompany.com](mailto:sales@hamiltoncompany.com)

#### Hamilton Europe, Asia, & Africa

Hamilton Bonaduz A.G.  
Via Crusch 8  
CH-7402 Bonaduz, Switzerland  
Tel: +41 58 610 10 10  
Fax: +41-58-610-00-10  
[contact@hamilton.ch](mailto:contact@hamilton.ch)

To find a representative in your area, please visit [hamiltoncompany.com/contacts](http://hamiltoncompany.com/contacts)