

Thermo Scientific SuperNuova+ Series

Our SuperNuova+ series stirrers, hotplates and stirring hotplates are designed to provide reliable performance, dependable safety and simple operation.

SuperNuova+ units are available in two sizes and provide optimized controls and settings for applications that demand advanced precision.



Intuitive design

- Top plate choices in ceramic or aluminum
- Easy-to-read LED display for heating and stirring
- Raised display design protects electronics from spills
- Ability to set programs (ramp/dwell) as well as save settings
- Stainless steel PT1000 temperature probe, supporting rod and clamp kit included with both hotplate and stirring hotplate
- Stir bar comes standard with stirrer and stirring hotplate models
- Optional PT1000 temperature probe and splash guard protection shield

Advanced technology

- StirTrac features innovative engineering for slow-speed stirring, consistent speed control, and stronger magnetic coupling
- HOT TOP warning system designed to protect from accidental burns with prominent display when heating surface is above 50°C (122°F)

Reliable performance. Ease of operation.

Heating Surface: 7.25" x 7.25" (18.4 x 18.4 cm) Overall Dimensions: 8.2" W x 13" D x 3.8" H (20.8 X 33 X 9.7 cm)

7"x7"	Cat. No.	Description	Surface Type	Volts/Hz	Stir Range (RPM)	Max Surface Temp °C	Plug Configuration
	HP88857190	Hotplate	Ceramic	100-120V 50/60Hz	N/A	450	
	HP88857195	Hotplate	Ceramic	230V 50/60Hz	N/A	450	
	S88857190	Stirrer	Ceramic	100-120V 50/60Hz	50-1500	N/A	
	S88857195	Stirrer	Ceramic	230V 50/60Hz	50-1500	N/A	
	SP88857190	Hotplate Stirrer	Ceramic	100-120V 50/60Hz	50-1500	450	
	SP88857195	Hotplate Stirrer	Ceramic	230V 50/60Hz	50-1500	450	
	HP88857194	Hotplate	Aluminum	100-120V 50/60Hz	N/A	300	
	HP88857198	Hotplate	Aluminum	230V 50/60Hz	N/A	300	
	SP88857194	Hotplate Stirrer	Aluminum	100-120V 50/60Hz	50-1500	300	
SP88857198	Hotplate Stirrer	Aluminum	230V 50/60Hz	50-1500	300		

Heating Surface: 10.25" x 10.25" (26.0 x 26.0 cm) Overall Dimensions: 11.3" W x 16.2" D x 4" H (28.7 x 41.1 x 10.2 cm)

10"x10"	Cat. No.	Description	Surface Type	Volts/Hz	Stir Range (RPM)	Max Surface Temp °C	Plug Configuration
	HP88850190	Hotplate	Ceramic	100-120V 50/60Hz	N/A	400	
	HP88850195	Hotplate	Ceramic	230V 50/60Hz	N/A	400	
	S88850190	Stirrer	Ceramic	100-120V 50/60Hz	50-1500	N/A	
	S88850195	Stirrer	Ceramic	230V 50/60Hz	50-1500	N/A	
	SP88850190	Hotplate Stirrer	Ceramic	100-120V 50/60Hz	50-1500	400	
	SP88850195	Hotplate Stirrer	Ceramic	230V 50/60Hz	50-1500	400	

Warranty: Three years **Certifications:** cCSAus (100-120V models), CE (230V models) **RoHS** compliant