

Cole-Parmer[®] Stuart[™] Microplate Shaking Incubator - SI-200

- Incubator with shaker
- Ideal for microplates and microtubes
- Integrated timer
- Digital display for temperature and speed
- Optimised performance to minimise sample evaporation
- Retractable platform for easy loading and unloading
- Three year warranty





Cole-Parmer® Stuart™ Microplate Shaking Incubator - SI-200

The Cole-Parmer® Stuart™ SI-200 incubators have specifically been designed for adequately mixing small volumes of liquids in a temperature-controlled environment. The high-speed shaking action at 250 and 1250rpm, with a tight orbit of 1.5mm, is ideal for microtitre plates and microtubes.

The units feature a microprocessor controller and an LED control panel that allow independent control of speed and temperature, as well as a timer that can be set for any duration from 1 second to 9 days. Careful control of the air distribution within the incubator ensures temperature uniformity, between +7°C to +60°C, throughout the sample chamber.

A retractable platform facilitates easier access to samples at the back of the incubator. During operation it remains securely locked in place. The non-slip mat ensures up to four microtitre plates can comfortably and securely be accommodated at the same time; tube racks for all common tube can sizes are also available for the units.

Strategically placed stainless steel water trays ensures up to 80% humidity, preventing sample evaporation and damage over extended periods of incubation. The built-in USB connection allows the units to be connected to a PC for long term temperature monitoring.

Ordering Information

Description	Ordering Number	Series No.	Model No.	Legacy Sku.
Microtitre plate shaker incubator	79520-10	SI-200	SIM-200D-M	SI505
Microtitre plate shaker incubator 120V/60HZ	79520-08	SI-200	SIM-200D-M-120	SI505/120/60
Microtitre plate shaker incubator with IQOQ document	79520-12	SI-200	SIM-200D-M	SI505/IQOQ

Accessories

Description	Ordering Number	Series No.	Model No.	Legacy Sku.
Tube holder for 1.5ml tubes	51900-97	SI-200	N/A	SSM5/1
Tube holder for 0.5ml tubes	51900-98	SI-200	N/A	SSM5/2
Tube holder for 0.2ml tubes	51900-99	SI-200	N/A	SSM5/3

Technical Specification

Specification	SI-200
Temperature range	Ambient + 7°C to 60°C
Samples	4 x Microtitre plate or 2 x microtube racks
Temperature display resolution	0.1°C
Temperature fluctuation	± 0.5°C at 37°C
Temperature variation	<0.6°C at 37°C
Temperature precision	± 0.5°C at 37°C
Speed range	250 to 1250rpm
Speed control	Digital set in 10rpm increments
Timer	min/sec, hour/min, days/hours
Orbit diameter, mm	1.5
Platform size, mm	220 x 220
Relative humidity	~80% (using water trays)
Internal dimensions, mm (w x d x h)	307 x 300 x 190
Maximum load, kg	1
Overall dimensions, mm (w x d x h)	361 x 405 x 430
Net weight, kg	22.5
Heater power, W 200W	200W
Electrical supply	230V, 50Hz, 250W
IP Rating	31

coleparmer.com

USA:
+1.800.323.4340
+1.847.549.7600

Canada: +1.800.363.5900
China: +86.21.5109.9909
France: +33 (0) 1486 37800
Germany: +49 (0) 9377 92030

India: +1.800.266.1244
Italy: +39 (0) 1313 89513
UK: +44 (0) 1480 272279
All other countries: +1.847.549.7600

Cole-Parmer®
essentials

an antylia scientific company

Find out more at antylia.com