

► Labnet Orbit™ 300

Electric Power Supply

120V	120V ± 10%, 50/60Hz
230V	230V ± 10%, 50/60Hz
Motor Power	15W
Fuse	
120V	2 x T 1A L 250V
230V	2 x T 0.25A L 250V
RPM Regulation	Digital, load independent, from 100 to 1,200 rpm in 10 rpm steps
Shaker Orbit	3 mm
Timer	30 sec. to 99 min. 50 sec. in 10-second steps (under 10 min. in 1 -second steps), timer HOLD function
Maximum Load	4.4 lbs. (2 kg)
Dimensions (W x L x H)	10.3 x 13.3 x 5.1 in. (26.2 x 33.7 x 13 cm)
Weight	12.35 lbs. (5.6 kg)
Ambient Operation Range	5°C to 40°C, up to 85% RH, non-condensing

► Labnet Orbit 1000

Electric Power Supply

120V	120V ± 10%, 50/60Hz
230V	230V ± 10%, 50/60Hz
Motor Power	15W
Fuse	
120V	2 x T 1A L 250V
230V	2 x T 0.25A L 250V
RPM Regulation	Digital, load independent, from 20 to 300 rpm in 1 rpm steps
Shaker Orbit	19 mm
Timer	30 sec. to 99 min. 50 sec. in 10-second steps (under 10 min. in 1-second steps), timer HOLD function
Maximum Load	9 lbs. (4 kg)
Dimensions (W x L x H)	10.3 x 13.3 x 5.1 in. (26.2 x 33.7 x 13 cm)
Weight	16 lbs. (7.3 kg)
Ambient Operation Range	5°C to 40°C, up to 85% RH, non-condensing

► Labnet Orbit 1900

Electric Power Supply

120V	120V ± 10%, 50/60Hz
230V	230V ± 10%, 50/60Hz
Motor Power	50W
Fuse	
120V	2 x T 2A L 250V
230V	2 x T 1A L 250V
RPM Regulation	Digital, load independent, from 25 to 300 rpm in 1 rpm step
Shaker Orbit	19 mm
Timer	30 sec. to 99 min. 50 sec. in 10-second steps (under 10 min. in 1-second steps), timer HOLD function
Maximum Load	22 lbs. (10 kg)
Dimensions (W x L x H)	15.3 x 18.3 x 6.2 in. (39 x 46.5 x 16 cm)
Weight	68.35 lbs. (31 kg)
Ambient Operation Range	5°C to 40°C, up to 85% RH, non-condensing