

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Page 1/12

Printing date 08.07.2025

Revision: 08.07.2025

Version number 11.05 (replaces version 11.04)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** ethyl acetate

· **Article number:** 1318

· **CAS Number:**

141-78-6

· **EC number:**

205-500-4

· **Index number:**

607-022-00-5

· **Registration number** 01-2119475103-46-XXXX

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category**

PC1 Adhesives, sealants

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

PC9c Finger paints

PC18 Ink and toners

PC27 Plant protection products

PC34 Textile dyes, and impregnating products

PC39 Cosmetics, personal care products

· **Process category**

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

(Contd. on page 2)

EU

Trade name: ethyl acetate

(Contd. of page 1)

- PROC14 Tableting, compression, extrusion, pelletisation, granulation
- PROC15 Use as laboratory reagent
- PROC17 Lubrication at high energy conditions in metal working operations
- PROC18 General greasing /lubrication at high kinetic energy conditions
- PROC19 Manual activities involving hand contact
- PROC20 Use of functional fluids in small devices

- **Environmental release category**

- ERC1 Manufacture of the substance
- ERC2 Formulation into mixture
- ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- ERC7 Use of functional fluid at industrial site
- ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
- ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- **Application of the substance / the mixture** Laboratory chemicals

- **1.3 Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

PANREAC QUIMICA S.L.U.
C/Garraf 2
Polígono Pla de la Bruguera
E-08211 Castellar del Vallès (Barcelona)

Tel. (+34) 937 489 400
Fax. (+34) 937 489 401
e-mail: product.safety@itwreagents.com

- **Further information obtainable from:** email: product.safety@panreac.com

- **1.4 Emergency telephone number:**

Single telephone number for emergency calls: 112 (EU)
Tel.: (+34) 937 489 499

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**

- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard statements**

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 3)

Trade name: ethyl acetate

(Contd. of page 2)

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.1 Substances**

- **CAS No. Description**

141-78-6 ethyl acetate

- **Identification number(s)**

- **EC number:** 205-500-4

- **Index number:** 607-022-00-5

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:** Seek medical treatment.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** In cases of frost bites, rinse with plenty of water. Do not remove clothing.

- **After eye contact:** Call a doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Forms explosive mixtures with air at ambient temperatures.

Vapours are heavier than air and may spread along floors.

Beware of backfiring.

Forms explosive mixtures with air on intense heating.

(Contd. on page 4)

EU

Trade name: ethyl acetate

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
In order to avoid contact with skin, keep a safety distance and wear suitable protective clothing.
Wear fully protective suit.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Contain escaping vapours with water.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Avoid substance contact.
Do not inhale steams/aerosols.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Clean up affected area.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**
Wear shoes with conductive soles.
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Away from sources of ignition and heat.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Open receptacle only under localised extractor facilities.
Store receptacle in a well ventilated area.
Store only outside or in explosion proof rooms.
Store under lock and key and with access restricted to technical experts or their assistants only.
- **Recommended storage temperature:** Room Temperature
- **Storage class:** 3

(Contd. on page 5)

Trade name: ethyl acetate

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm
 Long-term value: 734 mg/m³, 200 ppm

· **DNELs**

Oral	Long-term - systemic effects, general population	4.5 mg/kg
Dermal	Long-term - systemic effects, worker	63 mg/kg
	Long term - systemic effects, general population	37 mg/kg
Inhalative	Acute - local effects, worker	1,468 mg/m ³
	Acute - systemic effects, worker	1,468 mg/m ³
	Long-term - systemic effects, worker	734 mg/m ³
	Long-term - local effects, worker	734 mg/m ³
	Acute - systemic effects, general population	734 mg/m ³
	Acute - local effects, general population	734 mg/m ³
	Long-term - systemic effects, general population	367 mg/m ³
	Long-term - local effects, general population	367 mg/m ³

· **PNECs**

Aquatic compartment - freshwater	0.24 mg/L
Aquatic compartment - marine water	0.024 mg/L
Aquatic compartment - water, intermittent releases	1.65 mg/L
Aquatic compartment - sediment in freshwater	1.15 mg/kg
Aquatic compartment - sediment in marine water	0.115 mg/kg
Terrestrial compartment - soil	0.148 mg/kg
Sewage treatment plant	650 mg/L
Oral secondary poisoning	0.2 mg/kg food

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

- Not required.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Use suitable respiratory protective device only when aerosol or mist is formed.

· **Hand protection**

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Trade name: ethyl acetate

(Contd. of page 5)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Recommended thickness of the material: ≥ 0.11 mm

Value for the permeation: Level ≥ 480 min

- **As protection from splashes gloves made of the following materials are suitable:**

Recommended thickness of the material: ≥ 0.11 mm

Value for the permeation: Level ≥ 480 min

- **Eye/face protection**

Face protection



Tightly sealed goggles

- **Body protection:**

Antistatic protective clothing.

Heat-resistant protective clothing

Flame retardant antistatic protective clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Liquid

- **Colour:**

Colourless

- **Odour:**

Fruit-like

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

-84 °C

- **Boiling point or initial boiling point and boiling range**

77 °C

- **Flammability**

Not applicable.

Highly flammable.

- **Lower and upper explosion limit**

- **Lower:**

2.1 Vol %

- **Upper:**

11.5 Vol %

- **Flash point:**

-4 °C

- **Auto-ignition temperature:**

427 °C

- **Decomposition temperature:**

Not determined.

- **pH**

Not determined.

- **Viscosity:**

- **Kinematic viscosity at 20 °C**

0.49 cSt

- **Dynamic at 20 °C:**

0.44 mPas

- **Solubility**

- **water at 20 °C:**

80 g/l

- **Partition coefficient n-octanol/water (log value)**

0.73

- **Vapour pressure at 20 °C:**

97 hPa

- **Density and/or relative density**

- **Density at 20 °C:**

0.9 g/cm³

(Contd. on page 7)

Trade name: ethyl acetate

(Contd. of page 6)

· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	100 %
· Molecular weight	88.11 g/mol
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Keep away from open flames, hot surfaces and sources of ignition.
- **10.5 Incompatible materials:**
alkali compounds
strong bases
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

EU

(Contd. on page 8)

Trade name: ethyl acetate

(Contd. of page 7)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
Quantitative data on the toxicological effect of this product are not available.

Components	Type	Value	Species
Oral	LD50	4,100 mg/kg	(rat)
Dermal	LD50	20,000 mg/kg	(rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **After inhalation:** No irritant effect.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties** Substance is not listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

Type of test	Effective concentration	Method	Assessment
EC50/48 h	3,300 mg/l	(Algae)	
	717 mg/l	(daphnia magna)	
LC50/96 h	230 mg/l	(fish)	

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Chemicals must be disposed of in compliance with the respective national regulations.

(Contd. on page 9)

EU

Trade name: ethyl acetate

(Contd. of page 8)

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN1173

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** ETHYL ACETATE

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.

· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.

· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

33

· **EMS Number:**

F-E,S-D

· **Stowage Category**

B

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

D/E

(Contd. on page 10)

Trade name: ethyl acetate

(Contd. of page 9)

- | | |
|-----------------------------------|---|
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1173 ETHYL ACETATE, 3, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Substance is not listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)** Substance is not listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40, 75
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
Substance is not listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
Substance is not listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS** Substance is not listed.
- **Regulation (EC) No 273/2004 on drug precursors** Substance is not listed.
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
Substance is not listed.
- **REGULATION (EU) 2024/590 on substances that deplete the ozone layer** Substance is not listed.
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Substance is not listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of previous version:** 21.08.2021
- **Version number of previous version:** 11.04
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)

(Contd. on page 11)

Trade name: ethyl acetate

(Contd. of page 10)

PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* **Data compared to the previous version altered.**

Annex: Exposure scenario

- **Short title of the exposure scenario** Formulation and packing/repacking of substances and mixtures
- **Sector of Use**
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**
 - PC1 Adhesives, sealants
 - PC9a Coatings and paints, thinners, paint removers
 - PC9b Fillers, putties, plasters, modelling clay
 - PC9c Finger paints
 - PC18 Ink and toners
 - PC27 Plant protection products
 - PC34 Textile dyes, and impregnating products
 - PC39 Cosmetics, personal care products
- **Process category**
 - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
 - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
 - PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
 - PROC4 Chemical production where opportunity for exposure arises
 - PROC5 Mixing or blending in batch processes
 - PROC7 Industrial spraying
 - PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
 - PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
 - PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
 - PROC10 Roller application or brushing
 - PROC11 Non industrial spraying
 - PROC13 Treatment of articles by dipping and pouring
 - PROC14 Tableting, compression, extrusion, pelletisation, granulation
 - PROC15 Use as laboratory reagent
 - PROC17 Lubrication at high energy conditions in metal working operations
 - PROC18 General greasing /lubrication at high kinetic energy conditions
 - PROC19 Manual activities involving hand contact
 - PROC20 Use of functional fluids in small devices
- **Environmental release category**
 - ERC1 Manufacture of the substance
 - ERC2 Formulation into mixture
 - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
 - ERC7 Use of functional fluid at industrial site
 - ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
 - ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

(Contd. on page 12)

Trade name: ethyl acetate

(Contd. of page 11)

- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity** ≤ 1 tons per day
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
Indoor application.
Outdoor application.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Tightly sealed goggles
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.