

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Page 1/12

Printing date 31.05.2023

Revision: 31.05.2023

Version number 7.08 (replaces version 7.07)

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** xylene, mixture of isomers

· **Article number:** 1769

· **CAS Number:**  
1330-20-7

· **EC number:**  
215-535-7

· **Index number:**  
601-022-00-9

· **Registration number** 01-2119488216-32-XXXX

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8 Manufacture of bulk, large scale chemicals (including petroleum products)

SU9 Manufacture of fine chemicals

SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Process category**

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC6 Calendering operations

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

PROC14 Tableting, compression, extrusion, pelletisation, granulation

PROC15 Use as laboratory reagent

PROC16 Use of fuels

PROC17 Lubrication at high energy conditions in metal working operations

PROC18 General greasing /lubrication at high kinetic energy conditions

(Contd. on page 2)

EU

**Trade name: xylene, mixture of isomers**

(Contd. of page 1)

- PROC19 Manual activities involving hand contact
- PROC20 Use of functional fluids in small devices
- PROC21 Low energy manipulation and handling of substances bound in/on materials or articles
- **Environmental release category**
  - ERC1 Manufacture of the substance
  - ERC2 Formulation into mixture
  - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
  - ERC6a Use of intermediate
  - ERC6d Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
  - ERC7 Use of functional fluid at industrial site
  - ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
  - ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
  - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
  - ERC9a Widespread use of functional fluid (indoor)
  - ERC9b Widespread use of functional fluid (outdoor)
- **Application of the substance / the mixture** Laboratory chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - PANREAC QUIMICA S.L.U. Tel. (+34) 937 489 400
  - C/Garraf 2 Fax. (+34) 937 489 401
  - Polígono Pla de la Bruguera e-mail: product.safety@itwreagents.com
  - E-08211 Castellar del Vallès (Barcelona)
- **Further information obtainable from:** email: product.safety@panreac.com
- **1.4 Emergency telephone number:**
  - Single telephone number for emergency calls: 112 (EU)
  - Tel.: (+34) 937 489 499

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
  - Flam. Liq. 3 H226 Flammable liquid and vapour.
  - Acute Tox. 4 H312 Harmful in contact with skin.
  - Acute Tox. 4 H332 Harmful if inhaled.
  - Skin Irrit. 2 H315 Causes skin irritation.
  - Eye Irrit. 2 H319 Causes serious eye irritation.
  - STOT SE 3 H335 May cause respiratory irritation.
  - STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
  - Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

### · 2.2 Label elements

- **Labelling according to Regulation (EC) No 1272/2008**
  - The substance is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

(Contd. on page 3)

**Trade name: xylene, mixture of isomers**

(Contd. of page 2)

· **Hazard statements**

- H226 Flammable liquid and vapour.
- H312+H332 Harmful in contact with skin or if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

· **3.1 Substances**

· **CAS No. Description**

1330-20-7 xylene, mixture of isomers

· **Identification number(s)**

· **EC number:** 215-535-7

· **Index number:** 601-022-00-9

## SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Involve doctor immediately.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

· **After skin contact:**

Call a doctor immediately.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Trade name: xylene, mixture of isomers

(Contd. of page 3)

- **After eye contact:** Call a doctor immediately.
- **After swallowing:**  
Keep airways free.  
Risk of aspiration!  
Call a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Carbon monoxide and carbon dioxide  
Combustible.  
Forms explosive mixtures with air at ambient temperatures.  
Vapours are heavier than air and may spread along floors.  
Beware of backfiring.  
Forms explosive mixtures with air on intense heating.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.  
Contain escaping vapours with water.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Avoid substance contact.  
Do not inhale steams/aerosols.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Clean up affected area.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Trade name: xylene, mixture of isomers

(Contd. of page 4)

- Prevent formation of aerosols.
- Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Protect from heat.
  - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Away from sources of ignition and heat.
- **Further information about storage conditions:**
  - Keep container tightly sealed.
  - Protect from heat and direct sunlight.
  - Open receptacle only under localised extractor facilities.
  - Store receptacle in a well ventilated area.
  - Store under lock and key and with access restricted to technical experts or their assistants only.
- **Recommended storage temperature:** Room Temperature
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

#### · **Ingredients with limit values that require monitoring at the workplace:**

##### **1330-20-7 xylene, mixture of isomers**

IOELV	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 221 mg/m <sup>3</sup> , 50 ppm
	Skin

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes and skin.
- **Respiratory protection:**
  - Filter ABEK
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
  - Use suitable respiratory protective device only when aerosol or mist is formed.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Trade name: xylene, mixture of isomers

(Contd. of page 5)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.7$  mm

Value for the permeation: Level  $\geq 480$  min

· **As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

Value for the permeation: Level  $\geq 30$  min min

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:**

Use protective suit.

Flame retardant antistatic protective clothing

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Colourless

· **Odour:**

Aromatic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

-25 °C

· **Boiling point or initial boiling point and boiling range**

137-143 °C

· **Flammability**

Not applicable.

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

1 Vol %

· **Upper:**

7 Vol %

· **Flash point:**

24 °C

· **Auto-ignition temperature:**

460 °C

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic at 20 °C:**

0.61 mPas

· **Solubility**

· **water at 25 °C:**

9 g/l

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

8 hPa

· **Density and/or relative density**

· **Density at 20 °C:**

0.87 g/cm<sup>3</sup>

(Contd. on page 7)

Trade name: xylene, mixture of isomers

(Contd. of page 6)

· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Ignition temperature:</b>	Not determined.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent content:</b>	
· <b>VOC (EC)</b>	100 %
· <b>Molecular weight</b>	106.17 g/mol
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**  
Increased reactivity with:  
strong oxidants  
nitric acid / conc. sulfuric acid  
Risk of explosion with:  
Nitric acid

(Contd. on page 8)

Trade name: xylene, mixture of isomers

(Contd. of page 7)

- **10.6 Hazardous decomposition products:** In the event of fire: See chapter 5

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity** Harmful in contact with skin or if inhaled.
- **LD/LC50 values relevant for classification:**  
Quantitative data on the toxicological effect of this product are not available.

· Components	Type	Value	Species
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	1,134 mg/kg (rabbit)	
Inhalative	LC50/4 h	11 mg/l (ATE)	

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **After inhalation:** Irritant to skin and mucous membranes.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties** Substance is not listed.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** May be accumulated in organism
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water  
Danger to drinking water if even small quantities leak into the ground.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Chemicals must be disposed of in compliance with the respective national regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.



(Contd. on page 9)

Trade name: xylene, mixture of isomers

(Contd. of page 8)

- **Uncleaned packaging:**
- **Recommendation:**  
 Disposal must be made according to official regulations.  
 Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## SECTION 14: Transport information

· <b>14.1 UN number or ID number</b> · <b>ADR, IMDG, IATA</b>	UN1307
· <b>14.2 UN proper shipping name</b> · <b>ADR, IMDG, IATA</b>	XYLENES
· <b>14.3 Transport hazard class(es)</b> · <b>ADR</b> 	3 (F1) Flammable liquids. 3
· <b>IMDG, IATA</b> 	3 Flammable liquids. 3
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Category</b>	Warning: Flammable liquids. 30 F-E,S-D A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>  · <b>Transport category</b> · <b>Tunnel restriction code</b>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E

(Contd. on page 10)

Trade name: xylene, mixture of isomers

(Contd. of page 9)

- |                                   |                                                                                                                  |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>IMDG</b>                     |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>  | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b> | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>   | UN 1307 XYLENES, 3, III                                                                                          |

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Substance is not listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**  
Substance is not listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**  
Substance is not listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS** Substance is not listed.
- **Regulation (EC) No 273/2004 on drug precursors** Substance is not listed.
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**  
Substance is not listed.
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Substance is not listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of previous version:** 21.08.2021
- **Version number of previous version:** 7.07
- **Abbreviations and acronyms:**  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern

(Contd. on page 11)

**Trade name: xylene, mixture of isomers**

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

## Annex: Exposure scenario

- **Short title of the exposure scenario** Formulation and packing/repacking of substances and mixtures
- **Sector of Use**
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
  - SU8 Manufacture of bulk, large scale chemicals (including petroleum products)
  - SU9 Manufacture of fine chemicals
  - SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
  - SU8 Manufacture of bulk, large scale chemicals (including petroleum products)
  - SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
- **Process category**
  - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
  - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
  - PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
  - PROC4 Chemical production where opportunity for exposure arises
  - PROC5 Mixing or blending in batch processes
  - PROC6 Calendering operations
  - PROC7 Industrial spraying
  - PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
  - PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
  - PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
  - PROC10 Roller application or brushing
  - PROC11 Non industrial spraying
  - PROC13 Treatment of articles by dipping and pouring
  - PROC14 Tableting, compression, extrusion, pelletisation, granulation
  - PROC15 Use as laboratory reagent
  - PROC16 Use of fuels
  - PROC17 Lubrication at high energy conditions in metal working operations
  - PROC18 General greasing /lubrication at high kinetic energy conditions
  - PROC19 Manual activities involving hand contact
  - PROC20 Use of functional fluids in small devices
  - PROC21 Low energy manipulation and handling of substances bound in/on materials or articles
- **Environmental release category**
  - ERC1 Manufacture of the substance
  - ERC2 Formulation into mixture
  - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
  - ERC6a Use of intermediate
  - ERC6d Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
  - ERC7 Use of functional fluid at industrial site
  - ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

(Contd. on page 12)

Trade name: xylene, mixture of isomers

(Contd. of page 11)

- ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
- ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- ERC9a Widespread use of functional fluid (indoor)
- ERC9b Widespread use of functional fluid (outdoor)

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use**

· **Duration and frequency** 5 workdays/week.

· **Physical parameters**

· **Physical state** Fluid

· **Concentration of the substance in the mixture** Raw material.

· **Used amount per time or activity** ≤ 1 tons per day

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Avoid contact with eyes.

Indoor application.

Outdoor application.

· **Other operational conditions affecting consumer exposure** Keep out of the reach of children.

· **Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures** No special measures required.

· **Technical protective measures** Ensure that suitable extractors are available on processing machines

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Filter ABEK

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device only when aerosol or mist is formed.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Tightly sealed goggles

· **Measures for consumer protection**

Ensure adequate labelling.

Keep locked up and out of the reach of children.

· **Environmental protection measures**

· **Water** No special measures required.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer** Not relevant for this Exposure Scenario.

· **Guidance for downstream users** No further relevant information available.