Dutscher
TOGETHER, HELPING SCIENCE ADVANCE

Technical Data Sheet



Description

CELLULES CE NEUBAUER AMELIOREE DOUBLE SANS PINCES RESEAU FONCE

Part number

140514

Pieces by sales : 1

Description

Counting chambers

- made of special optical glass
- in compliance with DIN 12847
- individually tested according to the German Calibration Ordinance
- planarity and tolerances are strictly observed
- tolerance of depth of chamber max. 2 %
- our counting chambers for investigations of cell suspensions are equipped with 2 sets of grids. In-vitro diagnostic (IVD) applications generally require duplicate determinations. Double counting grids = double check possibility.
- a cover glass with a thickness of 0.4 mm is placed on top of both external stages of the counting chamber to limit the volume over the counting grids. Thinner coverslips cannot be used as they bend because of the capillary forces.
- with 2 haemacytometer cover glasses 20 x 26 mm which are suitable for most counting chambers. For spare cover glasses please see here .
- counting chambers Fuchs-Rosenthal require cover glasses 24 x 24 mm and counting chambers Nageotte require cover glasses 30 x 30 mm.
- individually packed in transparent plastic box, 10 pieces in a carton
- counting grids are structured into two ground and polished surfaces on the central stage (= chamber bottom). This central stage is located between two elevated also ground and polished stages.
- Dark line: Under the microscope the lines of the standard counting chambers appear dark.
- Bright line: Counting chambers with bright lines have counting grids which are structured into a very thin, transparent metal coating. The bright lines contrast well with the dark metallic background and this facilitates evaluating cell suspensions.

For applications according to EU regulation 2017/746 on in vitro diagnostic medical devices (IVDR), with CE-mark and batch number for comprehensive information and traceability

Cat. No with clamps	0640011
Details	Neubauer-improved
Depth of chamber	0,1 mm