FICHE TECHNIQUE

Désignation

- Kit de nettoyage


BRADY
TLS2200™ TLS PC Link™
Cleaning Card
PCK-5
NAED # 18556
2.25" x 9.5" (57 mm x 241 mm)
This pre-saturated, disposable TLS2200™ and TLS PC Link™ printer cleaning card is designed to safely and effectively remove all dirt, ink tape residue, adhesive, and other contaminants from the thermal printhead, paper guide, and paper path. This cleaning card will improve printer quality and legibility. This will also increase output, machine life, printer reliability and performance.
DIRECTIONS:
With printer turned on:
• Remove ribbon cartridge and label roll from printer before cleaning.
• Set cartridge lock lever into locked position ( ) prior to inserting cleaning card.
• Set printer material guide to widest position.
TLS2200 | TLS PC Link
Enter <Setup> menu (<Function> and <Setup>). | Press <Power> + <Feed>.
Choose – Printer. | Insert cleaning card.
Use the down arrow key to select – Clean printer. | Press <Feed> and cut strip. Repeat 3 more times.
Follow instructions on the printer screen. | See "TLS PC Link User's Guide" for details.
• After the cleaning is complete, remove printer cleaning card and dispose of properly.
• Allow 15 seconds for the printhead and label path to dry before loading labels or ribbon cartridge.
120000

Référence

- 167002

Unité de vente

1

Description

Caractéristiques techniques

- Couleur : Noir sur blanc



DOMINIQUE DUTSCHER SAS

Dominique DUTSCHER SAS
2C, rue de Bruxelles - 67176 BERNOLSHEIM
Tél. 03 88 59 33 60 - Fax. 03 88 59 33 99
www.dutscher.com