
CLEANING PROCEDURE
FOR DYCEM FIXED FLOORING

1.




Clean flooring at least once a day to maximise its efficiency. We advise using Inspec N10 detergent and a Vikan squeegee system

2.




If using Inspec N10, spray the surface with detergent, ensuring full coverage of the area. Or, use the appropriate cleaner with warm water

3.




Agitate the surface with the Vikan squeegee, until you begin to see the contamination being lifted

4.




Begin by cleaning in a vertical direction as shown

5.



Continue to agitate the surface in a horizontal direction as shown

6.



Remove the excess liquid or slurry from the edge of the surface, and collect with a microfibre mop or sponge system. If the removed liquid is dirty, repeat process or increase cleaning frequency

TIPS & **ADVICE**

- Clean at least once a day to improve cleaning efficiency, with the following:
  - Vikan squeegee system
  - Inspec N10 pre-diluted
  - Inspec N10 undiluted (with warm water)
- Or, use a Dycem approved cleaner (contact us for a full list) with warm water
- After cleaning, wash out the equipment so that it is ready for re-use
- To remove built-up spots of contamination, clean with a 70/30 ispropyl alcohol wipe
- Where decontamination or sterilisation takes place using a phenolic or hydroxide, rinse off as per the instructions (left). Otherwise, a film can develop, reducing the effectiveness of the Dycem
- For heavily contaminated areas, please contact Dycem's customer service team, who will be happy to discuss the best solution with you
- **Do not use** concentrated bleaching agents, scouring or abrasive powders, or cleaning machines with stiff brushes. Buffing or polishing machines will damage the surface, shortening the active working life of the flooring
- If you have any questions or concerns, or would like a Dycem deep clean, please get in touch:

info@dycem.com

www.dycem-cc.com

UK: +44 (0)117 955 9921


USA: 1-800 458 0060

Asia: asia@dycem.com

DOMINIQUE DUTSCHER SAS


CLEANING PROCEDURE
FOR LOOSE-LAID DYCEM FLOORING

1.




Turn the Dycem onto its underside, and remove to reveal the subfloor

2.




Clean the subfloor, agitating with the Vikan squeegee in a vertical direction, and remove excess residue/liquid. Repeat horizontally

3.



Clean the underside of the Dycem using an alcohol wipe (70/30 IPA recommended)

4.




Ensure both the subfloor and underside of Dycem are completely dry before replacement. Return Dycem to the subfloor, and spray with Inspec N10, ensuring full coverage of the area. Or, use the appropriate cleaner with warm water

5.



Agitate the Dycem surface with the squeegee in a vertical path as before, until you begin to see the contamination being lifted. Repeat this step, continuing the agitation in a horizontal direction

6.



Remove the excess liquid or slurry from the edge of the surface, and collect with a microfibre mop or sponge system. If the removed liquid is dirty, repeat the process or increase cleaning frequency

TIPS & **ADVICE**

- Clean at least once a day to improve cleaning efficiency, with the following:
  - Vikan squeegee system
  - Inspec N10 pre-diluted **OR**
  - Inspec N10 undiluted (with warm water)
- Or, use a Dycem approved cleaner (contact us for a full list) with warm water
- After cleaning, wash out the equipment so that it is ready for re-use
- To remove built-up spots of contamination, clean with a 70/30 ispropyl alcohol wipe
- Where decontamination or sterilisation takes place using a phenolic or hydroxide, rinse off as per the instructions (left). Otherwise, a film can develop, reducing the effectiveness of the Dycem
- For heavily contaminated areas, please contact Dycem's customer service team, who will be happy to discuss the best solution with you
- **Do not use** concentrated bleaching agents, scouring or abrasive powders, or cleaning machines with stiff brushes. Buffing or polishing machines will damage the surface, shortening the active working life of the flooring
- If you have any questions or concerns, or would like a Dycem deep clean, please get in touch:

info@dycem.com

www.dycem-cc.com

UK: +44 (0)117 955 9921

USA: 1-800 458 0060

Asia: asia@dycem.com

DOMINIQUE DUTSCHER