



MY WIPE POLY POLYESTER WIPE

DESCRIPTION

Polyester 100% wipe constructed from continuous-filament with sealed borders and ultrasound. Ideal for very critical environments: abrasion-resistant and absorption capacity. The wipe is highly recommended for cleaning steel, process machine, delicate equipment and optical surfaces. Sterilizable in autoclave. Cleanroom washed and double bagged.

The product is available in the sterile version for irradiation (Gamma ray).

The sterile wipe comprises the sterilization indicator, product code, batch numbering is accompanied by a certificate of conformity and irradiation.



PRODUCT CHARACTERISTICS	SPECIFICS
weight	132 gr ± 5 g/m²
thickness	0.50 ± 0.02 mm
absorption capacity	≥ 300 ml/m²
absorption lapse	≤ 3 s

CONTAMINATION CHARACTERISTICS					
RELEASE ANALYSIS TROUGH TEST IEST-RP-CC004.3		SPECIFICS	TYPICAL VALUE		
NVR (IPA)		≤ 0.6 mg/g	0.10 mg/g		
NVR (DIW)		≤ 0.3 mg/g	0.08 mg/g		
ions concentration (IC)	CI- Na ⁺ NO ₃ -	< 4 ppm < 4 ppm < 4 ppm	0.25 ppm 0.50 ppm 0.28 ppm		
liquid particle counting (LPC)	≥ 0.5µm	≤ 20 (x10 ⁶ particles/m ²)	12 (x10 ⁶ particles/m ²)		
fiber release	> 100µm	< 0.05 fibers/cm ²	0.04 fibers/cm ²		

PRODUCTS			
CODE	DESCRIPTION	PACKAGING	
PH10129	polyester 100% continuous-filament wipe dimensions 9" x 9" (cm 23 x 23)	150 wipes double bagged	
PH10129S	polyester 100% continuous-filament sterile wipe dimensions 9" x 9" (cm 23 x 23)	150 wipes double bagged	

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001:2015 =

