

## filtration at its finest





The new Thermo Scientific™ Nalgene™ Syringe Filters are available in a variety of sizes and membranes for both sterile and non-sterile laboratory applications. Nalgene gives you choices to meet your needs for sterile filtration, laboratory filtration, prefiltration, sample preparation and gas venting.





### Less Waste\*

Nalgene 25mm diameter syringe filters perform as well as 30mm or 33mm diameter products in most applications, but produce less plastic waste.

\*Based on the dry volume of 100 syringe filters measured in a 1000mL Thermo Scientific Nalgene beaker (#1203-1000).

# Improved Sterility Assurance

Nalgene sterile syringe filters have a three-year shelf life, with lot number and expiration date printed on individual syringe filter packages for easy traceability.

### Identify at a Glance

Nalgene syringe filters are color coded, with membrane and pore size printed on each one so you know that you have the right filter for your fluid.









### **Sterile Filtration**

Thermo Scientific Nalgene sterile syringe filters are ideal for sterilizing (0.2 micron) or clarifying biological solutions, such as cell culture and microbial media, reagents and additives, proteinaceous solutions, and buffers.

### Select the best membrane

- PES (polyethersulfone) –
   Lowest protein binding and extractables, fast flow rates;
   best choice for media.
- SFCA (surfactant-free cellulose acetate) Low protein binding, lower extractables than standard CA; useful for cell culture fluids and cellular solutions.
- CA (cellulose acetate) Some protein binding and extractables; good for buffers.
- Nylon Low extractables, high protein binding; recommended for alcohols and weak solvents.

Pore size (µm)	Membrane	Housing	Catalog #	#/Case
13mm diameter fo	or 2 - 10 ml volume			
0.2	PES	Polypropylene	720-1320**	100
25mm diameter fo	or 10 - 100 ml volume			
0.2	PES	Polypropylene	725-2520**	50
0.45	PES	Polypropylene	725-2545**	50
0.2	SFCA	Polypropylene	723-2520**	50
0.2	SFCA	Polypropylene	723-9920**	125
0.45	SFCA	Polypropylene	723-2545**	50
0.45	SFCA	Polypropylene	723-9945**	125
0.8	CA	Polypropylene	723-2580**	50
0.2	Nylon	Polypropylene	726-2520**	50
0.45	Nylon	Polypropylene	726-2545**	50
**sterile				

### **Laboratory Filtration**

Non-sterile syringe filters for filtration, clarification or particle removal from buffers, reagents, DMSO, HPLC/GC solvents.

### Select the best membrane

- SFCA Use for immunological samples and biological fluids.
- CA Ideal for buffers, aqueous reagents and solutions, including EIA and ELISA samples.
- Nylon Good for cryoprotectants such as DMSO, and filtration of aqueous biological solutions, alcoholic solutions and non-aqueous HPLC/GC solvents.

Pore size (µm)	Membrane	Housing	Catalog #	#/Case
4mm diameter fo	r 0.5 - 1 ml volume, Leur	-Lok inlet, male slip <mark>ou</mark> tle	t, autoclavable	
0.2	CA	Polypropylene	171-0020*	100/400
0.45	CA	Polypropylene	171-0045*	100/400
0.2	Nylon	Polypropylene	176-0020*	100/400
0.45	Nylon	Polypropylene	176-0045*	100/400
25mm diameter f	or 10 - 100 ml volume			
0.2	SFCA	Polypropylene	724-2020*	500
0.45	SFCA	Polypropylene	724-2045*	500
0.8	CA	Polypropylene	724-2080*	500
0.2	Nylon	Polypropylene	726-2520**	50
0.45	Nylon	Polypropylene	726-2545**	50
0.2	Nylon	Polypropylene	727-2020*	500
0.45	Nylon	Polypropylene	727-2045*	500

<sup>\*</sup> autoclavable \*\*sterile

### **PreFiltration**

Our Nalgene sterile and non-sterile syringe filters with prefilter membrane or multiple media layers are designed for filtering high particulate or viscous suspensions or solutions.

#### Select the best membrane

- Glass fiber Prefilter.
- CA For buffers, aqueous reagents and solutions.

Pore size (µm)	Membrane	Housing	Catalog #	#/Case
25mm diameter Pre	filter, non-sterile, autoc	lavable		
1.1	Glass Fiber	Polypropylene	722-2000*	50
25mm diameter Pre	filter Plus, sterile, indivi	dual blister packed		
1.1 + 0.2	Glass filter + CA	Polypropylene	722-2520**	50

<sup>\*</sup> autoclavable \*\*sterile

### Air/Gas Filtration and Venting

Use Nalgene non-sterile syringe filters for sterilizing (0.2 micron) or clarifying gases or organic fluids, providing a barrier for sterile venting applications, such as benchtop fermenters, or protecting vacuum pumps from moisture.

### Select the best membrane

• PTFE - Hydrophobic Teflon™ membrane is resistant to aggressive chemicals and solvents.

Pore size (µm)	Membrane	Housing	Catalog #	#/Case
50mm diameter	for gases or 0.2 – 5 L f	luid volume, Stepped hose b	arb inlet and outlet	
0.2	PTFE	Polypropylene	DS0222-0020*	10
0.45	PTFE	Polypropylene	DS0222-0045*	10

<sup>\*</sup> autoclavable



nunc

# **Sample Preparation** for Chromatography

Nalgene non-sterile syringe filters are designed for clarification and particle removal from samples for instrument analysis such as HPLC and GC.

#### Select the best membrane

• PTFE – Hydrophobic Teflon™ for sterile venting applications and filtration of samples in HPLC/GC solvents.



Pore size (µm)	Membrane	Housing	Catalog #	#/Case	
13mm diameter fo	r 2-10 ml volume, Leur-	Lok inlet, male slip outlet			
0.2	PTFE	Polypropylene	721-1320*	100	
0.45	PTFE	Polypropylene	721-1345*	100	
25mm diameter fo	r 10-100 ml volume, Lei	ur-Lok inlet, male slip out	et		
0.2	PTFE	Polypropylene	728-2020*	500	
0.45	PTFE	Polypropylene	728-2045*	500	

<sup>\*</sup> autoclavable

### Thermo Scientific Chromatography Systems Products

Thermo Scientific Nalgene syringe filters can be used in sample preparation and clean up for liquid chromatography analysis—a perfect complement to our complete portfolio of chromatography equipment

#### Thermo Scientific Dionex ICS Systems

For ion analysis, no other solution compares to a Thermo Scientific™ Dionex™ ion chromatography system. Whether you have just a few samples or a heavy workload, or your analytical task is simple or challenging, we have a complete solution based on modern technology and world-class support as the leader in IC for over 30 years.

For more information, visit www.thermoscientific.com/IC





#### Thermo Scientific TSQ 8000 Triple Quadrupole GC-MS/MS

The TSQ™ 8000 system is reliable, easy to use and enables faster, more precise analyses with unstoppable productivity. Designed for routine analysis, the TSQ 8000 system integrates proven triple quadrupole technology with a rich software suite for uncompromised MS/MS simplicity from startup to final report.

For more information, please visit www.thermoscientific.com/tsq8000

### Thermo Scientific UltiMate 3000 LC/UHPLC Platform

The Thermo Scientific™ Dionex™ UltiMate™ 3000 LC/UHPLC platform consists of exceptionally flexible and capable systems—from nano/capillary flow rates as low as 20 nL/min to analytical and semi-prep flow rates up to 100 mL/min—that provide unmatched versatility, precision, and performance for chromatographers in pharmaceutical, bio-pharmaceutical and life science laboratories.

For more information, visit www.thermoscientific.com/uhplc2



#### www.thermoscientific.com/syringefilter

© 2015 Thermo Fisher Scientific Inc. All rights reserved. All (other) trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries.

Asia: Australia: 1300-735-292; New Zealand: 0800-933-966; China +86-21-6865-4588 or +86-10-8419-3588; China Toll-free: 800-810-5118 or 400-650-5118; Singapore +65-6872-9718; Japan: +81-3-5826-1616; Korea +82-2-2023-0640; Taiwan + 886-2-87516655; India: +91-22-6680-3000 Europe: Austria: +43-1-801-40-0; Belgium: +32-2-482-30-30; Denmark: +45-4631-2000; France: +33-2-2803-2180; Germany: +49-6184-90-6000; Germany Toll-free: 0800-1-536-376; Italy: +39-02-95059-554; Netherlands: +31-76-571-4440; Nordic/Baltic/CIS countries: +358-10-329-2200; Russia: +7-(812)-703-42-15; Spain/Portugal: +34-93-223-09-18; Switzerland: +41-44-454-12-22; UK/Ireland: +44-870-609-9203

North America: USA/Canada +1-585-586-8800; USA Toll-free: 800-625-4327

South America: USA sales support: +1-585-586-8800 Countries not listed: +49-6184-90-6000 or +33-2-2803-2000



A Thermo Fisher Scientific Brand