

Page 1/10

Printing date 09.03.2022

Revision: 09.03.2022 Version number 10.04 (replaces version 10.03)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: toluene

· Article number: 1745

• **CAS Number:** 108-88-3

• **EC number:** 203-625-9

· Index number: 601-021-00-3

· Application of the substance / the mixture

Chemical for various applications

Laboratory chemicals

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

PANREAC QUIMICA S.L.U.

C/Garraf 2

Polígono Pla de la Bruguera

E-08211 Castellar del Vallès (Barcelona)

Tel. (+34) 937 489 400 Fax. (+34) 937 489 401

e-mail: product.safety@panreac.com

- · Further information obtainable from: email: product.safety@panreac.com
- · 1.4 Emergency telephone number:

Single telephone number for emergency calls: 112 (EU)

Tel.: (+34) 937 489 499

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation.

Repr. 2 H361d Suspected of damaging the unborn child. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Page 2/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

· Hazard pictograms

(Contd. of page 1)







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310

Specific treatment (see on this label). P321

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

Rinse mouth. P330

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.1 Substances

· CAS No. Description

108-88-3 toluene

· Identification number(s)

· EC number: 203-625-9

· Index number: 601-021-00-3

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Involve doctor immediately.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Call a doctor immediately.

Immediately wash with water and soap and rinse thoroughly.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Risk of aspiration!

Call a doctor immediately.

(Contd. on page 3)

Page 3/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 2)

• **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Combustible.

Forms explosive mixtures with air at ambient temperatures.

Vapours ara heavier than air and may spread along floors.

Beware of backfiring.

Forms explosive mixtures with air on intense heating.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Contain escaping vapours with water.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Avoid substance contact.

Do not inhale steams/aerosols.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (AppliSorb).

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Clean up affected area.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure that suitable extractors are available on processing machines

Work only in fume cupboard.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

(Contd. on page 4)

Page 4/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 3)

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Away from sources of ignition and heat.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Open receptacle only under localised extractor facilities.

Store receptacle in a well ventilated area.

Store only outside or in explosion proof rooms.

Store under lock and key and with access restricted to technical experts or their assistants only.

- · Recommended storage temperature: Room Temperature
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL | Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

(Contd. on page 5)

Page 5/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 4)

Recommended thickness of the material: ≥ 0.11 mm

Value for the permeation: Level ≥ 480 min

· As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.11 mm

Value for the permeation: Level \geq 480 min

· Eye/face protection



Tightly sealed goggles

· Body protection:

Use protective suit.

Flame retardant antistatic protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Fluid
Colourless
Aromatic
Not determined.

· Melting point/freezing point: -95 °C

· Boiling point or initial boiling point and boiling

range 110-111 °C • Flammability Not applicable.

Lower and upper explosion limit

· Lower: 1.2 Vol %
· Upper: 8 Vol %
· Flash point: 4 °C
· Ignition temperature: 535 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic at 20 °C:Not determined.0.6 mPas

· Solubility

water at 15 °C: 0.5 g/l
Partition coefficient n-octanol/water (log value) 2.73
Vapour pressure at 20 °C: 29 hPa

· Density and/or relative density

Density at 20 °C: 0.87 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

· Important information on protection of health and environment, and on safety.

• Auto-ignition temperature: Not determined.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· **VOC (EC)** 100 %

(Contd. on page 6)

Page 6/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 5) · Change in condition · Evaporation rate Not determined. Information with regard to physical hazard · Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Highly flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Warming. A range from approx. 15 Kelvin below the flash point is to be rated as critical.

- **10.3 Possibility of hazardous reactions** Reacts with strong acids and oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Risk of explosion with:

strong acids

halogen-halogen compounds

perchlorates

organic nitro compounds

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if swallowed.
- LD/LC50 values relevant for classification:

Quantitative data on the toxicological effect of this product are not available.

				•		
	· Components		Туре	Value	Species	
ľ	Oral	LD50	636 mg/kg (rat)			
	Dermal	LD50	12,124 mg/kg (rabbit)			

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation
- · After inhalation: Irritant to skin and mucous membranes.
- · Reproductive toxicity

Suspected of damaging the unborn child.

NOAEL (Fertility) 49 mg/kg bw/day (rat)

(Contd. on page 7)

Page 7/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 6)

- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- · Endocrine disrupting properties Substance is not listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration Method Assessment
EC50/72 h	134 mg/l (Algae)
EC50/48 h	3.8 mg/l (daphnia magna)
EC50/96 h	>443 mg/l (Algae)
LC50/96 h	5.5 mg/l (fish)
NOEC/72 h	>10 mg/l (Algae)
NOEC (21 d)	0.74 mg/l (daphnia magna)
	1 mg/l (Aquatic Invertebrata)

- · 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water a worth-mentioning accumulation in organisms is not expected.

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Chemicals must be disposed of in compliance with the respective national regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1294

· 14.2 UN proper shipping name

· ADR, IMDG, IATA TOLUENE

(Contd. on page 8)

Page 8/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 7) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-D Stowage Category В · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UN 1294 TOLUENE, 3, II

· Directive 2012/18/EU

UN "Model Regulation":

- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)

Page 9/10

Printing date 09.03.2022 Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 8)

- National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Substance is not listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

Annex: Exposure scenario

- · Short title of the exposure scenario Formulation and packing/repacking of substances and mixtures
- Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting worker exposure

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure No special measures required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

(Contd. on page 10)

Printing date 09.03.2022

Revision: 09.03.2022

Version number 10.04 (replaces version 10.03)

Trade name: toluene

(Contd. of page 9)

Page 10/10

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Measures for consumer protection Ensure adequate labelling.
- Environmental protection measures
- Water No special measures required.
- Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

GB