

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Methanol  
SDS-number : 000000020240  
Type of product : Substance  
Remarks : SDS according to Art. 31 of Regulation (EC) 1907/2006.  
Chemical name : methanol  
Index-No. : 603-001-00-X  
REACH Registration Number : no data available

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Laboratory chemicals  
Uses advised against : none

#### 1.3. Details of the supplier of the safety data sheet

Company : Honeywell International Inc.      Honeywell International, Inc.  
115 Tabor Road      115 Tabor Road  
07950-2546 Morris Plains      Morris Plains, NJ 07950-2546  
USA      USA  
Telephone :  
For further information, please contact: : [SafetyDataSheet@Honeywell.com](mailto:SafetyDataSheet@Honeywell.com)

#### 1.4. Emergency telephone number

Emergency telephone number : +1-703-527-3887 (ChemTrec-Transport)  
+1-303-389-1414 (Medical)  
Country based Poison Control Center : see chapter 15.1

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### REGULATION (EC) No 1272/2008

Flammable liquids Category 2  
H225 Highly flammable liquid and vapour.  
Acute toxicity Category 3 - Inhalation  
H331 Toxic if inhaled.  
Acute toxicity Category 3 - Dermal  
H311 Toxic in contact with skin.  
Acute toxicity Category 3 - Oral  
H301 Toxic if swallowed.  
Specific target organ toxicity - single exposure Category 1  
H370 Causes damage to organs.

#### 2.2. Label elements

##### REGULATION (EC) No 1272/2008

Hazard pictograms



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H301 + H311 + H331 Toxic if swallowed, in contact with skin  
or if inhaled.  
H370 Causes damage to organs.

Precautionary statements : P210 Keep away from heat, hot surfaces,  
sparks, open flames and other ignition  
sources. No smoking.  
P243 Take precautionary measures against  
static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/  
vapours/ spray.  
P280 Wear protective gloves/protective  
clothing/eye protection/face protection.  
P284 Wear respiratory protection.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

P304 + P340

NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

### 2.3. Other hazards

Aspiration hazard if swallowed - can enter lungs and cause damage. Results of PBT and vPvB assessment, see chapter 12.5.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Chemical name	CAS-No. Index-No. REACH Registration Number EC-No.	Classification 1272/2008	Concentration	Remarks
methanol	67-56-1 603-001-00-X 200-659-6	Flam. Liq. 2; H225 Acute Tox. 3; H331; Inhalation Acute Tox. 3; H311; Dermal Acute Tox. 3; H301; Oral STOT SE 1; H370	100 %	STOT SE 2; H371:3 - < 10 % STOT SE 1; H370:>= 10 % STOT SE 1; H370:>= 10 % STOT SE 2; H371:3 - < 10 %

### 3.2. Mixture

Not applicable

Occupational Exposure Limit(s), if available, are listed in Section 8.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

*General advice:*

First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately. Show this safety data sheet to the doctor in attendance.

*Inhalation:*

Call a physician immediately. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present.

*Skin contact:*

After contact with skin, wash immediately with plenty of water. Call a physician immediately.

*Eye contact:*

Rinse thoroughly with plenty of water, also under the eyelids. Protect unharmed eye. Call a physician immediately.

*Ingestion:*

Immediately give large quantities of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

See Section 11 for more detailed information on health effects and symptoms.

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

*Suitable extinguishing media:*

Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder

*Extinguishing media which shall not be used for safety reasons:*

Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be produced such as:

Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Formaldehyde

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Use water spray to cool unopened containers. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Remove all sources of ignition. Wear personal protective equipment. Unprotected persons must be kept away.

#### 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Discharge into the environment must be avoided. Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water courses.

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

### 6.3. Methods and materials for containment and cleaning up

Ventilate the area.

No sparking tools should be used.

Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4. Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### *Advice on safe handling:*

Exhaust ventilation at the object is necessary. Use explosion-proof equipment. Wear suitable protective clothing and gloves.

#### *Advice on protection against fire and explosion:*

The heavy vapours can overcome a considerable distance up to the source of ignition. Use only in explosion-proof areas. Keep product and empty container away from heat and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

#### *Hygiene measures:*

When using do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Keep working clothes separately. Do not swallow. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

#### *Temperature class:*

T1

### 7.2. Conditions for safe storage, including any incompatibilities

#### *Requirements for storage areas and containers:*

Keep only in the original container, tightly closed, in a well ventilated place. Store at room temperature. (Ambient temperature:  $> 0 < 35^{\circ}\text{C}$ ) Protect from atmospheric moisture and water.

### 7.3. Specific end use(s)

**Methanol**

14262-1L

Version 1.7

Revision Date 11.06.2022

no additional data available

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits:**

Components	Basis / Value type	Value / Form of exposure	Exceeding Factor	Remarks
methanol	EH40 WEL STEL	333 mg/m3 250 ppm		
methanol	EH40 WEL TWA	266 mg/m3 200 ppm		
methanol	EH40 WEL SKIN_DES			Can be absorbed through the skin.
methanol	EU ELV SKIN_DES			Can be absorbed through the skin.
methanol	EU ELV TWA	260 mg/m3 200 ppm		Indicative
methanol	EH40 WEL STEL	333 mg/m3 250 ppm	15 minutes	
methanol	EH40 WEL STEL	333 mg/m3 250 ppm	15 minutes	

STEL - Short term exposure limit  
TWA - Time weighted average  
SKIN\_DES - Skin designation:

**DNEL/ PNEC-Values**

Component	End-use/impact	Exposure duration	Value	Exposure routes	Remarks
methanol	Consumers / Acute systemic effects		8mg/kg bw/d	Skin contact	
methanol	Workers / Acute systemic effects		40mg/kg bw/d	Skin contact	

**Methanol**

14262-1L

Version 1.7

Revision Date 11.06.2022

methanol	Consumers / Long-term systemic effects		8mg/kg bw/d	Skin contact	
methanol	Workers / Long-term systemic effects		40mg/kg bw/d	Skin contact	
methanol	Consumers / Acute local effects		50 mg/m3	Inhalation	
methanol	Workers / Acute local effects		260 mg/m3	Inhalation	
methanol	Consumers / Acute systemic effects		50 mg/m3	Inhalation	
methanol	Workers / Acute systemic effects		260 mg/m3	Inhalation	
methanol	Consumers / Long-term local effects		50 mg/m3	Inhalation	
methanol	Workers / Long-term local effects		260 mg/m3	Inhalation	
methanol	Consumers / Long-term systemic effects		50 mg/m3	Inhalation	
methanol	Workers / Long-term systemic effects		260 mg/m3	Inhalation	
methanol	Consumers / Acute systemic effects		8mg/kg bw/d	Ingestion	
methanol	Consumers / Long-term		8mg/kg bw/d	Ingestion	



**Methanol**

14262-1L

Version 1.7

Revision Date 11.06.2022

	systemic effects			
--	------------------	--	--	--

Component	Environmental compartment / Value	Remarks
methanol	Sewage treatment plant: 100 mg/l	
methanol	Fresh water: 20,8 mg/l	Assessment factor: 10
methanol	Marine water: 2,08 mg/l	Assessment factor: 100
methanol	Fresh water sediment: 77 mg/kg	
methanol	Marine sediment: 7,7 mg/kg	
methanol	Soil: 100 mg/kg	Assessment factor: 100

**8.2. Exposure controls**

**Occupational exposure controls**

Do not breathe vapours/dust.  
Take off all contaminated clothing immediately.  
The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345.

**Engineering measures**

Use with local exhaust ventilation.  
Electrical equipment should be protected to the appropriate standard.

**Personal protective equipment**

*Respiratory protection:*  
In the case of vapour formation use a respirator with an approved filter.  
Recommended Filter type:  
Organic gas and low boiling vapour type

*Hand protection:*  
Glove material: butyl-rubber  
Break through time: > 480 min  
Glove thickness: 0,7 mm

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

Butoject® 898

Gloves must be inspected prior to use.

Replace when worn.

Remarks: Supplementary note: The specifications are based on information and tests from similar substances by analogy.

Due to varying conditions ( e.g.temperature or other strains) it must be considered that the usage of a chemical protective glove in practice may be much shorter than the permeation time determined in accordance with EN 374.

Since actual conditions of practical use often deviate from standardised conditions according EN 374 the glove manufacturer recommends to use the chemical protective glove in practice not longer than 50% of the recommended permeation time.

Manufacturer's directions for use should be observed because of great diversity of types .

Suitable gloves tested according EN 374 are supplied e.g. from KCL GmbH, D-36124 Eichenzell, Vertrieb@kcl.de

*Eye protection:*

Safety goggles

*Skin and body protection:*

Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

### Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
molecular weight	:	32,04 g/mol
Melting point/range	:	-98 °C

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

Boiling point/boiling range	:	64 - 65 °C at 1.013 hPa
Flammability	:	Not applicable
Upper explosion limit	:	50 %(V)
Lower explosion limit	:	5,5 %(V)
Flash point	:	11 °C Method: DIN 51755
Auto-ignition temperature	:	455 °C Method: DIN 51794
Decomposition temperature	:	At normal pressure may be distilled without decomposition.
pH	:	Not applicable
Auto-ignition temperature	:	not auto-flammable
Viscosity, kinematic	:	No data available
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	log Pow -0,71
Vapour pressure	:	128 hPa at 20 °C
Vapour pressure	:	532 hPa at 50 °C
Density	:	0,79 g/cm <sup>3</sup> at 20 °C
Relative vapour density	:	No data available

### 9.2 Other Information

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

---

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

Viscosity, dynamic : ca. 0,55 mPa.s  
at 25 °C

---

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under recommended storage conditions.

#### 10.2. Chemical stability

At normal pressure may be distilled without decomposition.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4. Conditions to avoid

Heat, flames and sparks.  
Keep away from direct sunlight.

#### 10.5. Incompatible materials

Oxidizing agents

#### 10.6. Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Formaldehyde

---

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

*Acute oral toxicity:*

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

---

Classification based on Annex VI of regulation 1272/2008/EC.

*Acute dermal toxicity:*

Classification based on Annex VI of regulation 1272/2008/EC.

*Acute inhalation toxicity:*

Classification based on Annex VI of regulation 1272/2008/EC.

*Skin irritation:*

Species: Rabbit

Result: No skin irritation

*Eye irritation:*

Species: Rabbit

Result: No eye irritation

*Respiratory or skin sensitisation:*

No data available

*Germ cell mutagenicity:*

Note: In vitro tests did not show mutagenic effects

Note: In vivo tests did not show mutagenic effects

*Aspiration hazard:*

No data available

### 11.2. Information on other hazards

Endocrine disrupting properties

No data available

*Other information:*

Solvent vapours have a narcotic effect if inhaled in high concentrations.

When swallowed, there is a danger of blindness.

Causes damage to organs (eyes, nervous system, systemic toxicity)

---

## SECTION 12: Ecological information

### 12.1. Toxicity

*Toxicity to fish:*

LC50

Species: *Lepomis macrochirus* (Bluegill sunfish)

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

Value: 15.400 mg/l  
Exposure time: 96 h

*Toxicity to aquatic plants:*  
No data available

*Toxicity to Microorganisms:*  
EC50  
Species: Bacteria  
Value: ca. 71.000 mg/l

*Toxicity to aquatic invertebrates:*  
EC50  
Species: Daphnia magna (Water flea)  
Value: > 10.000 mg/l  
Exposure time: 48 h

### 12.2. Persistence and degradability

*Biodegradability:*  
Biodegradation: 99 %  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Endocrine disrupting properties

No data available

### 12.7. Other adverse effects

Biochemical Oxygen : Value: 1.120 mg/g  
Page 14 / 19

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

Demand (BOD)  
Chemical Oxygen Demand : Value: 1.500 mg/g  
(COD)  
Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

*Product:*  
Dispose according to legal requirements.

*Packaging:*  
Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

*Further information:*  
Provisions relating to waste:  
EC Directive 2006/12/EC; 2008/98/EEC  
Regulation No. 1013/2006

For personal protection see section 8.

### SECTION 14: Transport information

#### 14.1 UN number

ADR/RID:1230

IMDG:1230

IATA:1230

#### 14.2 UN proper shipping name

ADR/RID:METHANOL

IMDG:METHANOL

IATA:Methanol

#### 14.3 Transport hazard class(es)

ADR/RID: 3 (6.1)

IMDG: 3 (6.1)

IATA: 3 (6.1)

#### 14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

#### 14.5 Environmental hazards

ADR/RID:no

Marine pollutant: no

#### 14.6 Special precautions for user

IMDG Code segregation group according chapter 3.1.4.4 : NONE,

**Methanol**

14262-1L

Version 1.7

Revision Date 11.06.2022

**14.7 Maritime transport in bulk according to IMO instruments**

No data available

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Basis	Value	Remarks
Directive 2012/18/EC SEVESO III Listed in Regulation : Methanol	<b>Quantity:</b> 500.000 kg <b>Quantity:</b> 5.000.000 kg	
Regulation (EC) No. 1907/2006, Annex XVII		This product contains an ingredient according to Annex XVII of the REACH Regulation1907/2006/EC.
Substances of very high concern (SVHC)		This product does not contain substances of very high concern according to Regulation (EC) No Article 57 above the respective regulatory 1907/2006 (REACH), concentration limit of $\geq 0.1$ % (w/w).

**Poison Control Center**

Country	Phone Number
Austria	+4314064343
Belgium	070 245245
Bulgaria	(+)35929154233
Croatia	(+3851)23-48-342
Cyprus	+357 2240 5611
Czech Republic	+420224919293; +420224915402
Denmark	82121212
Estonia	16662; (+372)6269390
Finland	9471977

Country	Phone Number
Liechtenstein	+41 442515151
Lithuania	+370532362052
Luxembourg	070245245; (+352)80002-5500
Malta	+356 2395 2000
Netherlands	030-2748888
Norway	22591300
Poland	+48 42 25 38 400
Portugal	800250250
Romania	+40 21 318 3606



## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

France	+33(0)145425959
Greece	+30 210 779 3777
Hungary	(+36-80)201-199
Iceland	5432222
Ireland	+353(1)8092166
Italy	0382 24444
Germany	Berlin : 030/19240
	Bonn : 0228/19240
	Erfurt : 0361/730730
	Freiburg : 0761/19240
	Göttingen : 0551/19240
	Homburg : 06841/19240
	Mainz : 06131/19240
Munich : 089/19240	
Latvia	+37167042473

Slovakia (NTIC)	+421 2 54 774 166
Slovenia	+386 1 400 6051
Spain	+34915620420
Sweden	112 (begär Giftinformation);+46104566786
Switzerland	145
United Kingdom	(+44) 844 892 0111

### Other inventory information

US. Toxic Substances Control Act  
On TSCA Inventory

Australia. Industrial Chemicals Act (AIC), as amended  
On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)  
All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List  
On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)  
On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS)  
On the inventory, or in compliance with the inventory

## Methanol

14262-1L

Version 1.7

Revision Date 11.06.2022

China. Inventory of Existing Chemical Substances (IECSC)  
On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand  
On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI)  
On the inventory, or in compliance with the inventory

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

### Text of H-statements referred to under heading 3

methanol : H225 Highly flammable liquid and vapour.  
H331 Toxic if inhaled.  
H311 Toxic in contact with skin.  
H301 Toxic if swallowed.  
H370 Causes damage to organs.

### Further information

All directives and regulations refer to amended versions.  
Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

#### Abbreviations:

EC European Community  
CAS Chemical Abstracts Service  
DNEL Derived no effect level  
PNEC Predicted no effect level  
vPvB Very persistent and very bioaccumulative substance  
PBT Persistent, bioaccumulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

**Methanol**

14262-1L

Version 1.7

Revision Date 11.06.2022

---

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.

---