

The New MA37 Moisture Analyzer for Daily Routine Operation



Your Reliable Partner for Routine Tasks

MA37 is a next-generation moisture analyzer that continues the success story of the MA35. The MA37 delivers fast, accurate results and is easy to operate. Moreover, this compact device features a BetterClean design for effortless cleaning. The status light makes it easy to track the current progress of a measurement. Therefore, the MA37 is ideal for users who require a fast, 100% reliable moisture analyzer that is easy to operate.

Fast measurements

Display of the measurement status

User-friendly operation

Effortless cleaning

Downward compatibility with predecessor model MA35



DESIGN
AWARD
2015

Your Reliable Partner for Routine Tasks

MA37 is a next-generation moisture analyzer that continues the success story of the MA35. The MA37 delivers fast, accurate results and is easy to operate. Moreover, this compact device features a BetterClean design for effortless cleaning. The status light makes it easy to track the current progress of a measurement. Therefore, the MA37 is ideal for users who require a fast, 100% reliable moisture analyzer that is easy to operate.

Fast measurements

The new, high-performance heating unit integrated into the MA37 ensures fast and uniform drying of the sample.

Display of the measurement status

The light indicates the status of the analyzer. As a result, you will have everything under control – even from a distance.

User-friendly operation

The intuitive user interface, including the touch screen, and easy-to-understand menu prompts considerably simplify operation of the MA37.

Effortless cleaning

The BetterClean design makes it so easy to thoroughly clean the parts of the sample chamber. You can even remove the chamber hood and the sample chamber plate to clean them in a laboratory washer.

MA35 mode

This mode lets you readily use method parameters already developed for the MA35.

Technical Specifications

Max. weighing capacity	70 g
Reproducibility, typical	Starting at an initial sample weight of approx. 1 g: ± 0.2% Starting at an initial sample weight of approx. 5 g: ± 0.05%
Repeatability	1 mg, 0.01%
Typical sample quantity	5 g ± 15 g
Display modes for results	Moisture content in % M and % g dry weight in % S and g AIPO (ratio) in % M/S
Temperature range and settings	40°C – 200°C, in increments of 1°C Standby temperature selectable: from 50°C – 120°C
Sample heating	Infrared heating using a metal tube heater
Heating programs	Standard drying, sterile drying, MA35 mode
Shutoff parameter	Fully automatic, semi-automatic, manual and with timer settings
Access to sample chamber	Removable hood with wide opening angle; SoftClose mechanism
Measuring program	1 program saved in the non-volatile memory (user-definable method parameters)
Memory for data storage	Results are saved until the start of the next measurement
Sample inspection	LED-illuminated sample chamber; inspection window with grid above the hood
Interface	1/mini USB port; automatic printer detection; direct data transfer to Microsoft Office programs
Housing dimensions (W x D x H)	215 x 400 x 210 mm (8.5" x 15.7" x 8.3")
Weight	Approx. 6.2 kg (approx. 13.6 lbs.)

Accessories

6965542	Disposable sample pans, 80 units, aluminum, 90 mm Ø
6906940	Glass fiber pads for analysis of fatty and fatty samples, hard quality, 80 units, 90 mm Ø
6906941	Glass fiber pads for analysis of liquid and fatty samples, soft quality, 200 units, 90 mm Ø
YHP01MA	Reprosys pads, 10 units for performance testing to check the functionality of the analyzer's heating unit and weighing system
YCWA52-AC-02	External calibration weight, 50 g (E2) with DAKS calibration certificate*
YDP40	Standard data printer
YCC03-I09	Premium G1P laboratory printer
YDP26-0CE	Adapter cable for connecting the YDP20-0CE printer
YS101MA	Date printer
YM007B (incl. short report)	Forcups for samples

*Customer-specific service for individual method development for the MA37 at the Sartorius Application Laboratory in Göttingen, Germany, or in the USA

*DAKS = German accreditation body recognized throughout Europe



DOMINIQUE BÜSCHER SAS

Sales and Service Contacts

For further contacts, visit www.sartorius.com

Europe

Germany

Sartorius Lab Instruments
GmbH & Co. KG
Otto-Brenner-Strasse 20
37079 Goettingen
Phone +49.551.308.0
Fax +49.551.308.3289

France & Suisse Romande

Sartorius France
2, rue Antoine Laurent de Lavoisier
ZA de la Gaudrée
91410 Dourdan
Phone +33.1.70.62.50.00
Fax +33.1.64.59.76.39

Austria

Sartorius Austria GmbH
Modecenterstrasse 22
1030 Vienna
Phone +43.1.7965760.0
Fax +43.1.7965760.24

Belgium

Sartorius Belgium N.V.
Rue Colonel Bourg 105
1030 Bruxelles
Phone +32.2.756.06.90
Fax +32.2.481.84.11

Finland & Baltics

Sartorius Biohit Liquid Handling Oy
Laippatie 1
00880 Helsinki
Phone +358.9.755.951
Fax +358.9.755.95.200

Hungary

Sartorius Hungária Kft.
Kagyló u. 5.
2092 Budakeszi
Phone +3623.457.227
Fax +3623.457.147

Ireland

Sartorius Ireland Ltd.
Unit 41, The Business Centre
Stadium Business Park
Ballycoolin Road
Dublin 11
Phone +353.1.8089050
Fax +353.1.8089388

Italy

Sartorius Italy S.r.l.
Viale A. Casati, 4
20835 Muggiò (MB)
Phone +39.039.4659.1
Fax +39.039.4659.88

Netherlands

Sartorius Netherlands B.V.
Phone +31.30.60.53.001
Fax +31.30.60.52.917
info.netherlands@sartorius.com

Poland

Sartorius Poland sp.z o.o.
ul. Wrzesinska 70
62-025 Kostrzyn
Phone +48.61.6473830
Fax +48.61.6473839

Russian Federation

LLC "Sartorius RUS"
Uralskaya str. 4, Lit. B
199155 St. Petersburg
Phone +7.812.327.53.27
Fax +7.812.327.53.23

Spain & Portugal

Sartorius Spain, S.A.
Avda. de la Industria, 32
Edificio PAYMA
28108 Alcobendas (Madrid)
Phone Spain +34.913.586.095
Phone Portugal +351.800.855.800
Fax Spain +34.913.589.623
Fax Portugal +351.800.855.799

Switzerland

Sartorius Mechatronics Switzerland AG
Ringstrasse 24a
8317 Tagelswangen (ZH)
Phone +41.44.746.50.00
Fax +41.44.746.50.50

U.K.

Sartorius UK Ltd.
Longmead Business Centre
Blenheim Road, Epsom
Surrey KT19 9QQ
Phone +44.1372.737159
Fax +44.1372.726171

Ukraine

LLS "Sartorius RUS"
Post Box 440 "B"
01001 Kiev, Ukraine
Phone +380.44.411.4918
Fax +380.50.623.3162

Americas

USA

Sartorius Corporation
5 Orville Drive, Suite 200
Bohemia, NY 11716
Phone +1.631.254.4249
Toll-free +1.800.635.2906
Fax +1.631.254.4253

Argentina

Sartorius Argentina S.A.
Int. A. Ávalos 4251
B1605ECS Munro
Buenos Aires
Phone +54.11.4721.0505
Fax +54.11.4762.2333

Brazil

Sartorius do Brasil Ltda
Avenida Senador Vergueiro 2962
São Bernardo do Campo
CEP 09600-000 - SP- Brasil
Phone +55.11.4362.8900
Fax +55.11.4362.8901

Canada

Sartorius Canada Inc.
2179 Dunwin Drive #4
Mississauga, ON L5L 1X2
Phone +1.905.569.7977
Toll-Free +1.800.668.4234
Fax +1.905.569.7021

Mexico

Sartorius de México, S.A. de C.V.
Libramiento Norte de Tepetzotlan s/n,
Colonia Barrio Tlacateco,
Municipio de Tepetzotlan,
Estado de México,
C.P. 54605
Phone +52.55.5562.1102
Fax +52.55.5562.2942
leadsmex@sartorius.com

Peru

Sartorius Peru S.A.C.
Av. Emilio Cavenecia 264 San Isidro
15073 Lima, Perú
Phone +51.1.441 0158
Fax +51.1.422 6100

Asia Pacific

Australia

Sartorius Australia Pty. Ltd.
Unit 5, 7-11 Rodeo Drive
Dandenong South Vic 3175
Phone +61.3.8762.1800
Fax +61.3.8762.1828

China

Sartorius (Shanghai) Trading Co., Ltd.
3rd Floor, North Wing, Tower 1
No. 4560 Jinke Road
Zhangjiang Hi-Tech Park
Pudong District
Shanghai 201210, P.R. China
Phone +86.21.6878.2300
Fax +86.21.6878.2882

Hong Kong

Sartorius Hong Kong Ltd.
Unit 1012, Lu Plaza
2 Wing Yip Street
Kwun Tong
Kowloon, Hong Kong
Phone +852.2774.2678
Fax +852.2766.3526

India

Sartorius Weighing India Pvt. Ltd.
#69/2-69/3, NH 48, Jakkasandra,
Nelamangala Tq
562 123 Bangalore, India
Phone +91.80.4350.5250
Fax +91.80.4350.5253

Japan

Sartorius Japan K.K.
4th Fl., Daiwa Shinagawa North Bldg.
8-11, Kita-Shinagawa 1-chome
Shinagawa-ku, Tokyo, 140-0001 Japan
Phone +81.3.3740.5408
Fax +81.3.3740.5406

Malaysia

Sartorius Malaysia Sdn. Bhd
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur, Malaysia
Phone +60.3.8996.0622
Fax +60.3.8996.0755

Singapore

Sartorius Singapore Pte. Ltd
1 Science Park Road,
The Capricorn, #05-08A,
Singapore Science Park II
Singapore 117528
Phone +65.6872.3966
Fax +65.6872.2494

South Korea

Sartorius Korea Ltd.
8th Floor, Solid Space B/D,
PanGyoYeok-Ro 220, Bundang-Gu
SeongNam-Si, GyeongGi-Do, 463-400
Phone +82.31.622.5700
Fax +82.31.622.5799

Thailand

Sartorius (Thailand) Co. Ltd.
129 Rama 9 Road,
Huaykwang
Bangkok 10310
Phone +66.2643.8361-6
Fax +66.2643.8367



◀ www.sartorius.com

Microsoft® is a registered trademark of Microsoft Corporation, USA.