FICHE TECHNIQUE



Désignation

- CENTRIFUGEUSE X2T IVD-MD 100-240V

Référence

- 229323

Unité de vente

1

Caractéristiques techniques

- Certifications/Conformité : EN/UL/IEC 61010-1, EN/UL/IEC 61010-2-020 and 61010-2-101, EN/UL/IEC 61326-1, EN/UL/IEC 61326-2-6, FCC part 15
- Dimensions (H x l x P) : 36.2 x 44.5 x 66 cm (14.3 x 17.5 x 26 in.)
- Type d'affichage : Full Color Touch Screen Interface
- Fréquence : 50/60 Hz
- Matériau : Front, top, sides: PC-ABS plastic painted with 2K PUR-based lacquer; metal housing: cold rolled steel with powder paint; centrifuge bowl: stainless steel; centrifuge feet: rubber
- Modèle : IVD-MD
- Poids net : 61 kg / 136 lb.
- Niveau sonore : <42 dB(A)
- Type de produit : Thermo Scientific X2T General Purpose Centrifuge
- Profil (accélération / freinage) : 9 accel/10 decel rates
- Stockage de programmes : Up to 100 Programs, including multi-step programming via Touch Screen; Including customizable Pulse options
- Rotor : 17 rotor options available, select rotor separately
- Rotor inclus : No
- Durée de fonctionnement : Max 99h, 59min, 59sec; also with continuous and customizable pulse
- Étalons : ISO 14971, ISO 13485, ISO 9001, FDA listed, Device Class 1



Dominique DUTSCHER SAS
2C, rue de Bruxelles - 67170 BERNOLSHEIM
Tél. 03 88 59 33 90 - Fax. 03 88 59 33 99
www.dutscher.com

FICHE TECHNIQUE

- Ventilée : Yes
- Tension : 100/115/220/240 V
- Garantie : 5 Year Limited (2 years standard warranty plus 3 additional years on motor and refrigeration)
- Capacité : 4 x 400 mL BioBottles, 76 x 5/7 mL Blood Tubes, 56 x 9/10 mL Blood Tubes, 36 x 15 mL Conical Tubes, 16 x 50 mL Conical Tubes with TX-400 Rotor
- FCR max. : 25,830 x g (Microliter 30 x 2 Rotor)
- Vitesse max. : 15,200 rpm (F21-48 x 2, Microliter 48 x 2 or Microliter 30 x 2 rotor)
- Réfrigéré : No



Dominique DUTSCHER SAS
2C, rue de Bruxelles - 67176 BERNOLSHEIM
Tél. 03 88 59 33 60 - Fax. 03 88 59 33 99
www.dutscher.com