CO_2 Incubators

Evolve. Expand. Excel.

Thermo Scientific™ Vios™ iDx CO_2 Incubators



DOMINIQUE DUTSCHER SAS

thermo scientific

Expanding discovery with every evolution

The Thermo Scientific™ Vios™ line of CO_2 Incubators has been the global leader in cell culture incubation technology for over 10 years. Robust performance based on product innovation has cemented Vios CO_2 Incubators as the number one choice for cell scientists. At every stage of research and development, and every stage of your career, you can count on Vios iDx CO_2 Incubators to help you tackle the ever-evolving challenges of your most critical applications.

DOMINIQUE DUTSCHER SAS

Ready to excel

As a cell scientist shaping the future of human health, ensuring the integrity of your work is paramount. Choose any Vios iDx CO_2 Incubator with confidence, knowing it is meticulously designed for optimal cell growth and minimal contamination risk.

Proven performance and protection for sensitive cell cultures

Designs that are ready for where your discoveries take you

Seamless operations for modern labs

- Thermo Scientific™ THRIVE™ Active Airflow technology for homogenous growth conditions
- Thermo Scientific™ Steri-Run™ High-Temperature Sterilization cycle delivers 12-log sterility assurance
- In-chamber HEPA filtration to achieve ISO Class 5 air quality conditions within only five minutes after a 30-second door opening



DOMIN... UTER SAS



Contents

Proven performance

Designs ready for discovery

Seamless operation

Protect and expand

Specifications for 165 and 255 models

Selecting a 165 or 255 model

Factory-installed options

Accessories

Navigate quickly using these buttons

And these buttons

DOMINIQUE DUTSCHER SAS

Proven performance and protection for sensitive cell cultures

We know that performance and culture quality are paramount. That's why each Vios iDx CO_2 Incubator features active airflow, high-temperature sterilization, and in-chamber HEPA filtration so that you're always ready to excel.

Achieve optimal culturing conditions with THRIVE Active Airflow technology

Your cells experience total recovery of all critical growth parameters in 10 minutes or less after a 30-second door opening.* The in-chamber fan ensures consistent results by evenly distributing filtered, conditioned air for homogeneous culturing throughout the chamber.



* Based on internal testing standards for a 30-second door opening, recovery time calculated to 98% of starting value for temperature and CO_2 and 95% of starting value for humidity.

Eliminate microbial contaminants with high-temperature sterilization when using the Steri-Run High Temperature Sterilization Cycle

This simple overnight routine provides fast, easy elimination of microbial contaminants and eliminates the need for separate autoclaving of parts.

- Fully automated cycle is shown to reach 180 °C at 48 locations, ensuring all chamber surfaces achieve a 12-log sterility assurance level.
- Avoids the physical constraints and variation associated with UV germicidal lamps and the ongoing costs, handling, and storage of potentially toxic germicides.
- The Steri-Run High-Heat Sterilization Cycle has been proven by independent third-party tests.

Read the data

Read how it works | Why choose heat?

Protect cells from airborne contaminants with in-chamber HEPA filtration

Airborne particulates are a primary source of contamination in most lab settings. Our advanced HEPA filtration technology protects cultures, providing ISO Class 5 air quality conditions within only 5 minutes after a 30-second door opening. The entire chamber air volume is filtered every 60 seconds, the filter lasts for one year and is easily replaced without tools.

Read the data | Find out more



DOMINIQUE DUTSCHER SAS



Designs that are ready for where your discoveries take you


Your Vios iDx CO_2 Incubator is carefully designed with technologies based on decades of innovation to help ensure ultra-consistent growth conditions – so your precious cells flourish.

Culture confidently with our exclusive condensation-free humidification system

Our covered, integrated humidity reservoir maximizes relative humidity without condensation. The incubation chamber stays dry, and the design helps limit contamination in the water.

Read more





Sensor options help you manage cultures your way

Temperature and gas sensors are strategically positioned within the incubation chamber to swiftly respond to any deviations in desired conditions.

- Our Thermo Scientific IR180Si infrared CO_2 sensor features silicon MEMS emitter technology for improved stability and long service life. This sensor is recommended for labs working under good manufacturing practices (GMP) or conducting time course studies with many door openings.
- Our proprietary TC180 sensor offers the performance advantages of traditional IR technologies without the limiting lifespan, and is excellent for everyday cell culture applications.

Why IR180Si | Why location matters

DOMINIQUE DUTSCHER SAS

Seamless operations in modern labs

Vios iDx CO_2 Incubator features

Simplified interior maintenance

- Choose electropolished stainless steel or 100% pure copper interior, both with easy-to-install shelving systems and easy-to-clean curved chamber corners.
- Electropolishing significantly reduces surface roughness, decreasing bacterial attachment by up to 90%, enhancing corrosion resistance, and easing manual cleaning and disinfection.
- 100% pure natural copper option can help you combat contamination. Copper is easily maintained with mild detergent and 70% ethanol, improves through oxidation over time, and is safe for incubated cells. This makes it an excellent solution for busy research labs.

Read more


Ease of use and ergonomics

- Large 7-inch touchscreen display for quicker at-a-glance monitoring of chamber conditions. Set language* and programmable access code for added security.
- Ergonomic door design to make routine loading, unloading, and checking on cultures easy. Electromagnetic door lock comes standard.
- Integrated, covered 3-L water reservoir may be filled or drained without removing shelves or cultures.

***Available language options include: English, Spanish, German, French, Italian, Japanese, and Mandarin.**

Flexibility and customization

- Tri-gas options offer variable oxygen control for full culturing flexibility. Simulate hypoxic (1-21% O_2) or hyperoxic (5-90% O_2) conditions based on application need and cell type.
- Connectivity-ready for data management including front-access USB port and optional 4-20 mA signal output or Gateway for OPC-UA for remote monitoring with external data collection solutions, ideal for GMP environments meeting CFR-21 compliance.
- 165 L models offer enhanced protection for valuable samples when configured for Thermo Scientific Cell Locker Systems. Find out more
- 255 L models offer increased culturing capacity when configured for Thermo Scientific CultiMaxx Shelving Systems. Find out more





DOMINIQUE DUTSCHER

Protect and expand

Configurations for valuable cell culture

Protected chambers for your most sensitive cells

You'll gain enhanced culture security and protection when using the Cell Locker System. It divides the CO_2 incubator into six individual segregated chambers, with individual glass doors, uniquely preserving critical conditions for sensitive cells by isolating cultures from door openings.

The Cell Locker System should be ordered as a factory-installed option. Individual Cell Locker Chambers sold separately.

In-depth look **Preventing entry of microorganisms**

Cell Locker and stem cells

Expand your incubation capacity with specialized shelving

As you scale out your cell therapy manufacturing, our special CultiMaxx Shelving System – available for the Vios iDx 255 CO_2 Incubator in standard, CR, and AD models – offers additional vessel capacity and/or improved access for specialized cell culture vessels such as Wilson Wolf G-Rex® 500M-CS bioreactors, Thermo Scientific™ Nunc™ Cell Factory systems, or 1 L cell culture bags. This allows you to expand your incubation.

The electropolished stainless-steel reinforced shelves can be ordered as accessory and can be self-installed.

Learn more **G-Rex bioreactors & Vios Incubation**



Cell Locker System | CultiMaxx Shelving System | CultiMaxx for select vessels

DOMINIQUE DU

Vios iDx CO_2 Incubators specifications

	Vios iDx 165	Vios iDx 255
Exterior housing	Powder-coated cold-rolled steel	
External dimensions (w x h x d)	637 x 900 x 880 mm (25.1 x 35.4 x 34.6 in.)	774 x 969 x 934 mm (30.5 x 38.2 x 36.8 in.)
Internal dimensions (w x h x d)	470 x 607 x 576 mm (18.5 x 23.9 x 22.7 in.)	607 x 670 x 629 mm (23.9 x 26.4 x 24.8 in.)
Capacity	165 L (5.8 cu. ft.)	255 L (9.0 cu. ft.)
Operating weight (without accessories)	82 kg (180.8 lbs.)	105 kg (231 lbs.)
Shelving dimensions (w x d)	423 x 465 mm (16.7 x 18.3 in.)	560 x 500 mm (22.05 x 19.68 in.)
Shelving no.	3 std. / 11 max., perforated, adjustable	3 std. / 12 max., perforated, adjustable
Max. load per shelf	10 kg (22 lbs.) CU & SST models	10 kg (22 lbs.) CU models, 14 kg (30.9 lbs.) SST models
Temperature control	±0.1°C	
Temperature range	3 °C above ambient to 55 °C	
Temperature uniformity	< ±0.3 °C	
Sterilization cycle temperature	180 °C on all internal surfaces	
Sterilization cycle duration	≤12 hrs	
Constant humidity at 37 °C	High humidity mode: approx. 93 %, Low humidity mode: approx. 90 %	
CO_2 control	± 0.1%	
CO_2 range	1-20 %	
O_2 control*	± 0.1%	
O_2 range*	1-21% or 5-90%	

* O_2 control available as a factory-installed option.

DOMINIQUE DUTSCHER SAS

Selecting a Vios iDx CO_2 Incubator

120 V | 230 V | 100 V

Ordering information

			Vios iDx 165 CO_2 Incubators	Vios iDx 255 CO_2 Incubators
			Specifically designed to deliver the performance reliability, ease of operation, and value required to support a range of culturing needs from basic research to demanding and advanced applications, so you're ready for whatever comes next.	
Configuration			**230 V, 50/60 Hz**	
Single chamber	TC180 sensor	Electropolished stainless steel	51036153	51036273
		100% pure copper	51036156	51036276
	IR180Si sensor	Electropolished stainless steel	51036159	51036279
		100% pure copper	51036162	51036282
Expand your culturing capacity without increasing your lab footprint with a roller base and stacking kit:				
Low-profile roller base for stacked incubators			50171152	50171157
Stacking adapter kit			50171244	50171746
CultiMaxx Shelving System 255 L stainless steel models only	Increase vessel capacity and accessibility specialized reinforced shelving	1 L cell culture bags	–	50166275
		4- or 5-layer culture vessels	–	50166268
		10- or 13-layer culture vessels	–	50166285
		G-Rex bioreactors	–	50164781
Add oxygen control when you select one of the following systems with your incubator:				
Tri-Gas O_2 Control single incubator* 165 model comes with 3 segment inner door and 3 shelves	1-21 % O_2 Control	Made with chamber materials	51901145	51901133
Tri-Gas O_2 Control single incubator* 255 model comes with 6 segmented inner doors and 6 half-width shelves	5-90 % O_2 Control		51901146	51901134
Cell Locker System divides the incubator into 6 individual chambers for enhanced culture protection and security for inside a single CO_2 incubator:				
Available for 165 IR180Si sensor models only	Incubator with 6 segmented inner glass doors	Electropolished stainless steel	51036538	–
		100% pure copper	51036540	–
Each unit fits up to 6 Cell Locker Chambers*	Set of 6 Cell Locker Chambers with sliding tray and transport cover	Electropolished stainless steel	50151650X6	–
		100% pure copper	50154739X6	–

*** Cell Locker Chambers can be ordered as individual units. Chambers are not included with the Cell Locker System configuration.**
Product ships with 230 V EU cord and plug. Full options available in accessories and options pages.

DOMINIQUE DUTSCHER

Factory-installed options

	Vios iDx 165	Vios iDx 255
Door hinge side		
Right hinge door configuration	included	
Left hinge door configuration ← ONLY factory installed	51900293	
Outer casing material		
Powder-coated cold rolled steel	included	
Brushed stainless steel ← Option updated AD model in the future	–	
Inner door		
Single glass door	included	
3-segment inner door	51901144	–
6-segment inner door	51901221	51901127
Shelving configurations		
6 half-width shelves each, stainless steel	–	51901123
6 half-width shelves each, copper	–	51901122
3 reinforced shelves with 3 clip bars for installation, stainless steel	51901375	51901377
3 reinforced shelves with 3 clip bars for installation, copper	51901374	51901376
O_2 Control		
1–21% O_2 control	51901137	
5–90% O_2 control	51901138	





DOMINIQUE DUTSCHER SAS

Factory-installed options, continued

	Vios iDx 165	Vios iDx 255
Combined options		
1-21% O_2 control with 6-segment inner door and 3 shelves with 2 half-width shelves each (made of chamber material)	–	51901133
5-90% O_2 control with 6-segment inner door and 3 shelves with 2 half-width shelves each (made of chamber material)	–	51901134
Gas-tight 6-segment inner door with 3 Cell Locker System shelves*, stainless steel	51901222	–
Gas-tight 6-segment inner door with 3 Cell Locker System shelves*, copper	51901223	–
Other		
Internal 4-20 mA analog data output	51901143	
Active CO_2 reduction	51901491	
Rear water access	–	
Power cord options		
Switzerland	51900300	
Great Britain	51900303	
Italy	51900306	
Australia	51900449	
Denmark	51900481	
China	51900900	

Option updated AD model in the future

*** Cell Locker Chambers are not automatically included with the Cell Locker System configuration and are available as accessories.**
All incubators ship with a standard power cord – 100 V, 120 V, or 230 V EU version. Additional power cord options fit 230 V models only.

DOMINIQUE DUTSCHER SAS

Accessories

	Vios iDx 165	Vios iDx 255
Support frames and stacking adapters		
Support frame for dual stack with castors, 182 mm height	50170980	–
Low-profile roller base for dual stack with castors, 85 mm height	50171152	50171157
Cleanroom-compatible low-profile roller base for dual stack with castors, 76 mm height	–	–
Support frame for single incubator, without casters, 780 mm height	50171568	50171747
Stacking adapter kit	50171244	50171746
Stacking adapter kit for stacking Vios iDx model on top of Heracell 150i	50148172	–
Stacking adapter kit for stacking Vios iDx model on top of Heracell 240i	–	50148175
O_2/CO_2 control accessories, including filters		
Replacement in-chamber HEPA filter	50141920	
Replacement pre-filter	50144774	
CO_2 gas regulator, 2-stage, for gas tank	3429937	
N_2 gas regulator, 2-stage for gas tank	3429942	
O_2 gas regulator, 2-stage for gas tank	3429943	
External gas guard automatic change-over to reserve tank, 120 V, 50/60 Hz	50059043	
External gas guard automatic change-over to reserve tank, 230 V, 50/60 Hz	50046033	
Infrared gas tester with travel case, for advanced calibration and testing purposes for CO_2 model	50121515	










DOMINIQUE DUTSCHER SAS

	Vios iDx 165	Vios iDx 255
O_2/CO_2 control accessories, including filters, continued		
Infrared tester for CO_2/O_2	50145789	
Infrared gas tester interface kit	50122015	
5 inlet port filters for infrared testers	50060287	
Cell Locker System accessories		
Single Cell Locker Chamber with sliding tray and transport cover, stainless steel	50151650	–
Single Cell Locker Chamber with sliding tray and transport cover, copper	50154739	–
Set of 6 Cell Locker Chambers, stainless steel	50151650X6	–
Set of 6 Cell Locker Chambers, copper	50154739X6	–
Shelving		
Additional shelf, full width with 2 support rails for installation, stainless steel	50051909	50065793
Additional shelf, full width with 2 support rails for installation, copper	50051910	50065794
Reinforced clip bar shelf, stainless steel	50160246	50160234
Reinforced clip bar shelf, copper	50160247	50160245
Set of 4 HERAtrays, 1/4 width, stainless steel	–	50065807
Set of 4 HERAtrays, 1/4 width, copper	–	50065808
Set of 3 HERAtrays, 1/3 width, stainless steel	50051913	50065805
Set of 3 HERAtrays, 1/3 width, solid copper	50051914	50065806







DOMINIQUE DUTSCHER SAS

	Vios iDx 165	Vios iDx 255
Shelving, continued		
Set of 2 HERAtrays, 1/2 width, stainless steel	50058672	–
Set of 2 HERAtrays, 1/2 width, copper	50061050	–
Set of 2 HERAtrays, 1/2 width for half width shelves, stainless steel	–	50065809
Set of 2 HERAtrays, 1/2 width for half width shelves, copper	–	50065810
CultiMaxx Shelving System		
Set of 8 shelves to support up to 116 1 L cell culture bags	–	50166275
Set of 5 shelves to support up to ten 4- or 5-layer culture vessels, such as Thermo Scientific™ Nunc™ Cell Factory™ Systems	–	50166268
Set of 3 shelves to support up to six 10- or 13-layer culture vessels, such as Nunc Cell Factory Systems	–	50166285
Set of 3 shelves to support up to ten G-Rex 500M-CS bioreactors	–	50164781
Monitoring accessories		
Door lock retrofit kit, key entry, to prevent unauthorized access	50145438	
OPC-UA gateway	50168119	
Shakers for CO_2 incubators		
CO_2 Resistant shaker, 19 mm, with universal platform and flask clamp starter kit, 100 - 120 V	88881103	
CO_2 Resistant Shaker, 3 mm, with universal platform and flask clamp starter kit, 100 - 120 V	8881103B	
CO_2 Resistant shaker, 19 mm, with universal platform and flask clamp starter kit, 220 - 240 V	88881104	
CO_2 Resistant Shaker, 3 mm, with universal platform and flask clamp starter kit, 220 - 240 V	88881104B	





See accessories

DOMINIQUE DUTSCHER SAS

Start-up and compliance services

Invest in a Vios iDx CO_2 Incubator and you can benefit not just from top-tier cell expansion performance, but from the confidence that comes with knowing you're ready to tackle whatever challenges tomorrow may bring. And sometimes that's about more than just technology. With Unity™ Lab Services, you'll have access to exceptional support service experts for help, whenever you need.

From start-up support to comprehensive service plans and compliance solutions, your support package can help you meet your individual research needs.

See service plans



DOMINIQUE DUTSCHER SAS

ThermoFisher SCIENTIFIC



Evolve. Expand. Excel.

Thermo Scientific Vios iDx CO_2 Incubators

Learn more at **thermofisher.com/viosidx**

DOMINIQUE DUTSCHER SAS

For Laboratory Use. It is the customer's responsibility to ensure that the performance of the product is suitable for customers' specific use or application. ©2025 Thermo Fisher Scientific Inc. All rights reserved. G-Rex is a trademark of Wilson Wolf Corporation, VHP is a trademark of STERIS Corporation and OPC-UA is a trademark of OPC Foundation. All other trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. **BROC-165&255MODELS**