Hoja de Datos

Mezclar / Agitadores Magnéticos



RO 5

5-position digital magnetic stirrer without heating, designed for synchronous stirring. The magnetic coil technology provides noiseless and consistent stirring on all positions. Speed remains constant, even when load changes. The closed and compact design allows easy cleaning and protects the equipment against the penetration of liquids. Additionally, a removable transparent anti-slip mat is included.

- Adjustable reverse operation
- Wear free magnetic coils
- Error code display
- Easy operation with touch keypad
- Suitable for continuous operation
- Adjustable speed in increments of 10 rpm

Accesorios: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars,

Información Técnica	
Número de puestos de agitación	5
Distancia entre puestos de agitación [mm]	90
Deviación de velocidad individual por cada puesto [%]	0
Max. cantidad a agitar (H2O) [l]	0.4
Control de velocidad	10 pasos de RPM
Rango de velocidad [rpm]	0 - 1200
Longitud mínima de la barra de agitación [mm]	25
Longitud max. varilla magnética [mm]	30
Material de la superficie de la placa	acero inoxidable 1.4301
Dimensiones de la superficie de la placa [mm]	120 x 470
Dimensiones (An x Al x Pr) [mm]	120 x 60 x 570
Peso [kg]	3
Temperatura ambiental permitida [°C]	5 - 40
Humedad relativa permitida [%]	80
Clase de protección de acuerdo al DIN EN 60529	IP 40
Voltaje [V]	100 - 240
Frecuencia [Hz]	50/60
Consumo de energía [W]	13
Voltaje DC [V=]	24
Consumo de energía [mA]	500
No. ref.	**0003690500**

© IKA® Werke Staufen/Germany 2017 www.ika.com
Sujeto a modificaciones ténicas

DUNIQUE DUTSCHER SAS

IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, H 11 Cable de alimentación enchufe Euro, H 11 Cable de alimentación enchufe CH, RSE Extractor de varillas agitadoras, BC 1000 Tapa para Beaker, H 11 Cable de alimentación enchufe EURO, H 11 Cable de alimentación USA

DOMINIQUE DUTSCHER SAS

© IKA® Werke Staufen/Germany 2017 www.ika.com
Sujeto a modificaciones ténicas