SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name **HiTrap™ TALON® crude, 1 ml, 5 x 1 ml**

Catalogue Number 28953766

Product description Not available.

Product type Liquid.

Other means of identification Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Analytical chemistry.
Liquid chromatography.
Scientific research and development

☑ Consumer use -

1.3 Details of the supplier of the safety data sheet

Supplier

Cytiva
Amersham Place
Little Chalfont
Buckinghamshire
HP7 9NA United Kingdom
+44 1494 508000

Hours of operation
08.30 - 17.00

Person who prepared the SDS : sds_author@cytiva.com

1.4 Emergency telephone number

United Kingdom (UK)

Cytiva UK
Amersham Place
Little Chalfont
Buckinghamshire
HP7 9NA
t: 0870 606 1921

Call INFOTRAC 24 Hour number:
001-352-323-3500 (Calll Collect).

National advisory body/Poison Centre

United Kingdom (UK)

Health professionals should contact the National Poisons Information Service (NPIS) by telephone, or use TOXBASE www.toxbase.org .

NPIS http://www.npis.org/ advise that others seeking specific information on poisons should contact:
In England and Wales: NHS Direct - 0845 4647 or 111
In Scotland: NHS 24 - 08454 24 24 24
In N Ireland: Contact your local GP or pharmacist during normal hours; click here (www.gpoutofhours.hscni.net/) for GP services Out-of-Hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

Ingredients of unknown toxicity 16.5 percent of the mixture consists of component(s) of unknown acute dermal toxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word Warning

Hazard statements Flammable liquid and vapour.

Precautionary statements

General Not applicable.

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response Not applicable.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures Mixture

Product/ingredient name	Identifiers	%	Classification	Type
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	14 - 19	Flam. Liq. 2, H225	[1] [2]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Eye Irrit. 2, H319 STOT SE 1, H370	[1] [2]
cobalt	REACH #: 01-2119517392-44 EC: 231-158-0	<0.1	Acute Tox. 4, H302 Resp. Sens. 1, H334	[1] [2]

	CAS: 7440-48-4 Index: 027-001-00-9	Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 Repr. 1B, H360F

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard
[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	No specific data.
Ingestion	No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Use dry chemical, CO_2, water spray (fog) or foam.
Unsuitable extinguishing media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special precautions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 2 to 8°C (35.6 to 46.4°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

Recommendations	Analytical chemistry. Liquid chromatography. Scientific research and development.
Industrial sector specific solutions	Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanol	**EH40/2005 WELs (United Kingdom (UK), 1/2020)** TWA 8 hours: 1000 ppm. TWA 8 hours: 1920 mg/m³.
methanol	**EH40/2005 WELs (United Kingdom (UK), 1/2020)** Absorbed through skin. STEL 15 minutes: 333 mg/m³. STEL 15 minutes: 250 ppm. TWA 8 hours: 266 mg/m³. TWA 8 hours: 200 ppm.
cobalt	**EH40/2005 WELs (United Kingdom (UK), 1/2020) [cobalt and cobalt compounds]** Carc. Inhalation sensitiser. TWA 8 hours: 0.1 mg/m³ (as Co).

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
ethanol	**DNEL - Workers - Long term - Inhalation** 380 mg/m³ Effects: Systemic **DNEL - General population - Long term - Oral** 87 mg/kg bw/day Effects: Systemic **DNEL - General population - Long term - Inhalation** 114 mg/m³ Effects: Systemic **DNEL - General population - Long term - Dermal** 206 mg/kg bw/day Effects: Systemic **DNEL - Workers - Long term - Dermal** 343 mg/kg bw/day Effects: Systemic **DNEL - General population - Short term - Inhalation** 950 mg/m³ Effects: Local **DNEL - Workers - Short term - Inhalation** 1900 mg/m³ Effects: Local
methanol	**DNEL - General population - Short term - Oral** 4 mg/kg bw/day Effects: Systemic **DNEL - General population - Long term - Oral** 4 mg/kg bw/day Effects: Systemic **DNEL - General population - Short term - Dermal** 4 mg/kg bw/day Effects: Systemic **DNEL - General population - Long term - Dermal** 4 mg/kg bw/day Effects: Systemic **DNEL - Workers - Short term - Dermal** 20 mg/kg bw/day Effects: Systemic **DNEL - Workers - Long term - Dermal**

	20 mg/kg bw/day Effects: Systemic **DNEL - General population - Short term - Inhalation** 26 mg/m³ Effects: Local **DNEL - General population - Long term - Inhalation** 26 mg/m³ Effects: Local **DNEL - General population - Short term - Inhalation** 26 mg/m³ Effects: Systemic **DNEL - General population - Long term - Inhalation** 26 mg/m³ Effects: Systemic **DNEL - Workers - Short term - Inhalation** 130 mg/m³ Effects: Local **DNEL - Workers - Long term - Inhalation** 130 mg/m³ Effects: Local **DNEL - Workers - Short term - Inhalation** 130 mg/m³ Effects: Systemic **DNEL - Workers - Long term - Inhalation** 130 mg/m³ Effects: Systemic
cobalt	**DNEL - General population - Long term - Inhalation** 6.3 µg/m³ Effects: Local **DNEL - General population - Long term - Inhalation** 8.1 µg/m³ Effects: Systemic **DNEL - General population - Long term - Oral** 8.9 µg/kg bw/day Effects: Systemic **DNEL - Workers - Long term - Inhalation** 40 µg/m³ Effects: Local **DNEL - Workers - Long term - Inhalation** 54.1 µg/m³ Effects: Systemic **DNEL - General population - Long term - Dermal** 3265.2 µg/kg bw/day Effects: Systemic **DNEL - Workers - Long term - Dermal** 7228.9 µg/kg bw/day Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields

Skin protection

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): butyl rubber , neoprene
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to British Standard BS EN 1149 for further information on material and design requirements and test methods. Recommended: lab coat
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: A respirator is not needed under normal and intended conditions of product use.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid. [and Suspension]
Colour	solution : Colourless. / Suspension : Light Red
Odour	Sweetish. Alcohol-like. [Slight]
Odour threshold	Not available.
pH	5.5 to 8.5 [Conc. (% w/w): 100%]
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Flash point	Closed cup: 38 to 43°C
Auto-ignition temperature	Not available.

Ingredient name	°C	Method
ethanol	455	DIN 51794
methanol	455	DIN 51794

Decomposition temperature	Not available.
Viscosity	Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): Not available.

Solubility(ies)

Media	Result
cold water	Easily soluble
hot water	Easily soluble

Solubility in water	Not available.
Miscible with water	Yes.
Partition coefficient: n-octanol/ water	Not applicable.
Vapour pressure	Not available.

	Vapour Pressure at 20˚C			Vapour pressure at 50˚C		
Ingredient name	**mm Hg**	**kPa**	**Method**	**mm Hg**	**kPa**	**Method**

methanol	126.96329	16.9
ethanol	42.94865	5.7
water	17.5	2.3

Evaporation rate Not available.

Relative density Not available.

Vapour density Not available.

Explosive properties Not considered to be a product presenting a risk of explosion.

Oxidising properties Not available.

Particle characteristics

Median particle size Not applicable.

9.2 Other information

Not available.

Burning time Not applicable.

Burning rate Not applicable.

Solubility in water Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability The product is stable.

10.3 Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
ethanol	**Rat - Oral - LD50** 7060 mg/kg Toxic effects: Lung, Thorax, or Respiration - Other changes **Rat - Inhalation - LC50 Vapour** 124700 mg/m³ [4 hours]
methanol	**Rabbit - Dermal - LD50** 15800 mg/kg **Rat - Oral - LD50** 5600 mg/kg **Rat - Inhalation - LC50 Gas.** 145000 ppm [1 hours] **Rat - Inhalation - LC50 Gas.** 64000 ppm [4 hours]
cobalt	**Rat - Oral - LD50** 1500 mg/kg

Conclusion/Summary [Product] Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Media in 20% EtOH + 1% Methanol (TALON with <0.1% Cobolt) - GROUP	15109	40377.0	N/A	453.3	N/A
ethanol	7000	N/A	N/A	124.7	N/A
methanol	100	300	64000	3	N/A
cobalt	1500	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Not available.

Conclusion/Summary [Product] Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product/ingredient name	Result
methanol	**Rabbit - Eyes - Severe irritant** Amount/concentration applied: 0.1 Ml

Conclusion/Summary [Product] Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] Not available.

Respiratory

Conclusion/Summary [Product] Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
methanol	STOT SE 1, H370

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation No known significant effects or critical hazards.

Ingestion No known significant effects or critical hazards.

Skin contact	No known significant effects or critical hazards.
Eye contact	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation	No specific data.
Ingestion	No specific data.
Skin contact	No specific data.
Eye contact	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]	Not available.
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Reproductive toxicity	No known significant effects or critical hazards.
Other information	Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
ethanol	**Acute - LC50 - Marine water** Fish - Bleak - *Alburnus alburnus* Size: 8 to 10 cm 11 g/l [96 hours] Effect: Mortality **Chronic - NOEC - Marine water** Algae - Green algae - *Ulva pertusa* 4.995 mg/l [96 hours] Effect: Reproduction **Acute - EC50 - Fresh water** Crustaceans - Ostracod - *Cypris subglobosa* 1074 mg/l [48 hours] Effect: Intoxication **Chronic - NOEC - Fresh water** Daphnia - Water flea - *Daphnia magna* - Neonate Age: <24 hours 100 µl/l [21 days] Effect: Mortality **Acute - EC50 - Marine water** Algae - Green algae - *Ulva pertusa* Size: 9.4 mm 3306 mg/l [96 hours] Effect: Reproduction
methanol	**Acute - LC50 - Marine water** Crustaceans - Common shrimp, sand shrimp - *Crangon crangon* - Adult 2500 mg/l [48 hours] Effect: Mortality **Acute - LC50 - Fresh water** Fish - Zebra danio - *Danio rerio* - Egg Age: 12 290 mg/l [96 hours] Effect: Mortality

	Acute - EC50 - Marine water Algae - Green algae - *Ulva pertusa* 16.912 mg/l [96 hours] Effect: Reproduction **Chronic - NOEC - Marine water** Algae - Green algae - *Ulva pertusa* 9.96 mg/l [96 hours] Effect: Reproduction
cobalt	**Acute - LC50 - Fresh water** Fish - Fathead minnow - *Pimephales promelas* 3.4 mg/l [96 hours] Effect: Mortality **Acute - LC50 - Fresh water** Daphnia - Water flea - *Daphnia magna* 4400 µg/l [48 hours] Effect: Mortality

Conclusion/Summary [Product] Not available.

12.2 Persistence and degradability

Product/ingredient name	Result
ethanol	**Aerobic** 100% [20 days] - Readily

Conclusion/Summary [Product] Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethanol	-	-	Readily
methanol	1 to 10 days [Fresh water] [4 to 30 °C]	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
≥10 - ≤25	-0.35	0.66	Low
<3	-0.77	<10	Low
<0.1	-	15600	High

12.4 Mobility in soil

Soil/water partition coefficient Not available.

Mobility Not available.

12.5 Results of PBT and vPvB assessment

ethanol	No	N/A	No	No	No	N/A	No
methanol	No	No	No	No	No	No	No
cobalt	No	No	No	No	No	No	No

12.6 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

Waste catalogue

Waste code	Waste designation
07 07 99	wastes not otherwise specified

Packaging

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	**Remarks** IATA Special Provision A 58 - Aqueous solutions containing 24% or less alcohol by volume is not subject to these regulations.

14.6 Special precautions for user **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
Media in 20% EtOH + 1% Methanol (TALON with <0.1% Cobolt) - GROUP	≥90	3
methanol	<3	69

Labelling Not applicable.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

Product/ingredient name	List name	Name on list	Classification	Notes
cobalt	EH40/2005 WELs	cobalt and cobalt compounds	Carc	-

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air	Not listed
Industrial emissions (integrated pollution prevention and control) - Water	Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

United States	All components are active or exempted.
Canada inventory	All components are listed or exempted.
China	All components are listed or exempted.
Japan	**Japan inventory (CSCL)**: Not determined. **Japan inventory (ISHL)**: Not determined.
15.2 Chemical safety assessment	This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226	On basis of test data

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360F	May damage fertility.
H370	Causes damage to organs.

Full text of classifications	Acute Tox. 3	ACUTE TOXICITY - Category 3
	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Carc. 1B	CARCINOGENICITY - Category 1B
	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
	Muta. 2	GERM CELL MUTAGENICITY - Category 2
	Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
	Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
	Skin Sens. 1	SKIN SENSITISATION - Category 1
	STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
Date of printing	08 August 2025	
Date of issue/ Date of revision	07 August 2025	
Date of previous issue	29 October 2024	
Version	9	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.