


# Thermo Scientific HERAEUS® BB 15

Designed for  
contamination  
prevention

High quality at an  
affordable price



User-friendly control panel with large clear display – easy to read from across the laboratory.

**Our Heraeus BB 15 Function Line CO<sub>2</sub> incubator provides everything you need for the good growth of cell and tissue cultures.**

### Major Features

- Precise temperature and CO<sub>2</sub> control for optimal growth conditions
- Powerful humidification system for short recovery times
- Solid copper interior for permanent contamination control (optional)

### Temperature Control

A precise Pt 1000 temperature sensor controls the air jacket heating for constant temperature. In case of failure, the system is equipped with a second circuit, taking over control to keep the temperature at the preset value.

### CO<sub>2</sub> Control

The CO<sub>2</sub> concentration is measured with a highly reliable TCD sensor. The sensor is auto calibrated on every auto-start routine.

### Humidification

For reducing the surface area, the water pan has been eliminated and the bottom of

the chamber is used as a water reservoir. Therefore, a quicker evaporation rate has been achieved, through a greater water surface area and supported by the direct heat transfer from the bottom of the chamber.

### Minimal Surface

The BB 15 chamber is consequently designed for a less contamination-prone surface area. It doesn't have any air ducts and no duplicate side walls. The shelf system has been reduced to the absolute minimum. Even the water pan has been eliminated. Therefore, the BB 15 has up to 50% less surface than other incubators.

## Easy to Clean

The chamber has a high quality electropolished finish resulting in a very smooth surface. All corners and edges are covered; there are no bolts or screws inside. All door gaskets can be easily removed and reinstalled, making cleaning easy.

## Easy to Use

The shelf system is easy to mount and take off. The shelves contain a travel stop to avoid tipping when dragged out too far. The back of the chamber is equipped with a 42mm (1.7 inch) access port to facilitate installation of appliances within the chamber. Large displays allow easy parameter control.



### Solid Copper Interior (optional)

The BB 15 is available with a solid copper interior. The chamber, the shelving system, the fan and even the fan housing is made of solid copper. Solid copper has been proven to show good antimicrobial activity. In the humid atmosphere the copper surface will slightly oxidize and microbes settling down on this surface get inactivated by the released copper ions. And because copper oxide is not volatile, it will not affect any cells in vessels or flasks that are not in contact with the copper surface. This results in a very effective, permanent contamination control of the whole interior surface area.



Left: BB 15 Function Line CO<sub>2</sub> incubator – ideal for cell and tissue culture.



Right: The BB 15 chamber is consequently designed for less contamination-prone surface area.

## Technical Data

Type	Unit	BB 15
<b>Dimensions</b>		
External	w x h x d	637 x 867 x 766 / 25.1 x 34.1 x 30.2
Internal	w x h x d	470 x 607 x 530 / 18.5 x 23.9 x 20.9
Total volume	litres cu.ft.	approx. 151 5.3
<b>Temperature</b>		
air jacket temperature control		
Temperature control range	°C	T <sub>A</sub> +3 ... 55
Temperature deviation, time <sup>1)</sup> / spatial <sup>1)</sup>	K	±0.1 / ± 0.5
Ambient temperature range	°C	+ 18 ... 33
Recovery time at 37 °C <sup>2)</sup>	min	≤10
<b>Humidity</b>		
Constant humidity	%RH	≥95
Recovery time at 95 % rH <sup>3)</sup>	min	≤30
<b>CO<sub>2</sub> Control</b>		
Measure and control range	Vol – %	0 ... 20
Control accuracy	Vol – %	± 0.1
Recovery time, 5% CO <sub>2</sub> <sup>2)</sup>	min	≤5
<b>Weight (excl. accessories)</b>	kg / Lbs	70 / 154

<sup>1)</sup> DIN 12 880, part 2 \*30 sec. door open, to 98 % of initial value \*30 sec. door open, to 96 % of initial value T<sub>A</sub> = ambient temperature

## Order Numbers

Standard equipment: Heraeus® BB 15: air-jacket heating, right hinged door, 150 l (5.3 cu.ft.) internal volume

Type	Description	Cat. No.
Heraeus BB 15 (230 V, 50/60 Hz)	stainless steel inner chamber	51023121
Heraeus BB 15 (230 V, 50/60 Hz)	<del>solid copper inner chamber</del>	<del>51023122</del>
Heraeus BB 15 (120 V, 50/60 Hz)	stainless steel inner chamber	51023125
Heraeus BB 15 (120 V, 50/60 Hz)	solid copper inner chamber	51023126
<b>Accessories</b>		
Support frame 200 mm / 7.9 in	(without castors)	50051376
Support frame 200 mm / 7.9 in	(with castors, height incl. castors)	50057161
Support frame 780 mm / 30.7 in	(without castors)	50051436
Castor set 100 mm / 3.9 in	4 castors for support frames	50052528, 50051376 and 50051436
HERAtray	stainless steel shelf tray 1/3 width; 3 pcs.	50051913
HERAtray	solid copper shelf tray 1/3 width; 3 pcs.	50051914
Additional	shelf full-width stainless steel, incl. 2 support bars	50051909
Additional	shelf full-width copper, incl. 2 support bars	50051910

**North America:** USA/Canada +1 866 984 3766

**Europe:** Austria +43 1 801 40 0, Belgium +32 2 482 30 30, Finland +358 9 329 100, France +33 2 2803 2000, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 95059 1, Netherlands +31 76 571 4440, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

**Asia:** China +86 21 6865 4588 or +86 10 5850 3588, India +91 22 5542 9494, Japan +81 45 453 9220, Other Asian countries +852 2885 4613

**Countries not listed:** +49 6184 90 6940 or +33 2 2803 2000

[www.thermo.com/incubators](http://www.thermo.com/incubators)

© 2007 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.