

Data SheetMixing / Magnetic Stirrers



topolino mobil

Mobile magnetic mini-stirrer for mixing quantities up to 250 ml for battery and mains operation.

- Durable, brushless motor
- Continuously adjustable speed range
- High magnetic adhesion
- Portable operation with long operating time (8-12 h)
- Short charging time (2-3 h)
- Standard replaceable AA rechargeable batteries
- Optional power mode:
- a) Mains-free with standard batteries
- b) With supplied mains adapter (without batteries)
- c) Combined mains/battery operation (with batteries fitted)

Accessories: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON®

Battery operation Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	
Number of stirring positions Stirring quantity max. per stirring position (H2O) [I] Speed range [rpm] Set-up plate material s Battery operation Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	
Stirring quantity max. per stirring position (H2O) [I] Speed range [rpm] Set-up plate material s Battery operation Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	
Speed range [rpm] Set-up plate material s Battery operation Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	1
Set-up plate material s Battery operation Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	0.25
Battery operation Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	300 - 1800
Protection class according to DIN EN 60529 Voltage [V] Frequency [Hz] DC Voltage [V=]	synthetic (PP)
Voltage [V] Frequency [Hz] DC Voltage [V=]	yes
Frequency [Hz] DC Voltage [V=]	I P 20
DC Voltage [V=]	100 - 240
	50/60
	9
Current consumption [mA]	1000
Ident. No. 0	0003381300

20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE Stirring bar remover, BC 1000 Beaker