GE Healthcare

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

HiTrap™ TALON® crude, 1 ml; part of 'Tagged

package, His'

Catalogue Number 29-0588-03

 Product description
 Not available.

 Product type
 Liquid.

 Other means of identification
 Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in laboratories

1.3 Details of the supplier of the safety data sheet

SupplierGE Healthcare UK LtdHours of operationAmersham Place08.30 - 17.00

Little Chalfont

Buckinghamshire HP7 9NA

England +44 0870 606 1921

Perso

Person who prepared the MSDS: msdslifesciences@ge.com

1.4 Emergency telephone number

United Kingdom (UK) GE Healthcare UK Ltd 0870 606 1921

Amersham Place Little Chalfont Buckinghamshire HP7 9NA

National advisory body/Poison Centre

United Kingdom (UK) Health professionals should contact the National Poisons Information Service (NPIS) by telephone, or use

TOXBASE www.toxbase.org .

NPIS http://www.npis.org/ advise that others seeking specific information on poisons should contact:

In England and Wales: NHS Direct - 0845 4647 or 111

In Scotland: NHS 24 - 08454 24 24 24

In N Ireland: Contact your local GP or pharmacist during normal hours; click here (www.gpoutofhours.

hscni.net/) for GP services Out-of-Hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity Not applicable.



Article Number

29141578-2 Validation date 4 March 2016



Version 2

Page: 1/11

Ingredients of unknown ecotoxicity Not applicable.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word Warning

Hazard statements Flammable liquid and vapour.

Precautionary statements

Prevention Wear protective gloves: 1 - 4 hours (breakthrough time): butyl rubber, neoprene. Wear eye or face

protection: Recommended: safety glasses with side-shields. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-

handling equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Response

Storage Keep cool.

Disposal Dispose of contents and container in accordance with all local, regional, national and international

regulations.

Hazardous ingredients

Supplemental label elements Contains cobalt. May produce an allergic reaction.

Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures

and articles

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Other hazards which do not result None known.

in classification

SECTION 3: Composition/information on ingredients

Substance/mixture

			<u>Classification</u>	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	14 - 19	Flam. Liq. 2, H225	[2]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	[1] [2]
cobalt	REACH #: 01-2119517392-44 EC: 231-158-0 CAS: 7440-48-4 Index: 027-001-00-9	0.1 - 0.2	Acute Tox. 4, H302 Resp. Sens. 1, H334 Skin Sens. 1, H317	[1] [2]
			See Section 16 for the full text of the H statements declared above.	




Article Number

29141578-2



Page: 2/11



Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for

and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if

irritation occurs.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if

breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

a collar, tie, belt or waistband.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical

attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a

position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training. It may be dangerous to

the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contactNo known significant effects or critical hazards.InhalationNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contactNo specific data.InhalationNo specific data.Skin contactNo specific data.IngestionNo specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been

ingested or inhaled.

Specific treatments No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or

mixture

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

GE OG

Article Number 29141578-2

Validation date 4 March 2016

validation date 4 March 201

Page: 3/11

29-0588-03

Hazardous combustion products Decomposition products may include the following materials

carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special precautions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire

area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for

fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding For non-emergency personnel

areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on For emergency responders

suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform 6.2 Environmental precautions

the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof

equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof Large spill

equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hvaiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 2 to 8°C (35.6 to 46.4°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds (in tonnes)

Named substances

Name Notification and MAPP Safety report threshold threshold

500 methanol 5000

Danger criteria



Article Number

29141578-2 Validation date 4 March 2016



Version 2

Page: 4/11

29-0588-03

Category

Notification and MAPP
threshold

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b
5000
5000
50000

7.3 Specific end use(s)

Recommendations Liquid chromatography. Research and Development Analytical chemistry.

Industrial sector specific solutions Not available.

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 1920 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.
methanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 333 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 266 mg/m³ 8 hours. TWA: 200 ppm 8 hours.
cobalt	EH40/2005 WELs (United Kingdom (UK), 12/2011). Skin sensitiser. Notes: TWA: 0.1 mg/m³, () 8 hours. Form:

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DELs available.

PNECs

No PECs available.

8.2 Exposure controls

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): butyl rubber , neoprene

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: lab coat

(ge)

Article Number Page: 5/11

29141578-2

Validation date 4 March 2016



Other skin protection

being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk

assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: A respirator is not needed under normal and intended conditions of product use.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the

requirements of environmental protection legislation. In some cases, fume scrubbers, filters or

engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state Liquid. [and Suspension]

Colour solution: Colourless. / Suspension: Light Red

Odour Sweetish. Alcohol-like. [Slight]

Not available. Odour threshold рΗ Not available Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Closed cup: 38 to 43°C Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. **Burning time** Not applicable. **Burning rate** Not applicable.

Upper/lower flammability or

explosive limits

Not available.

Vapour pressure Not available. Vapour density Not available. Relative density Not available.

Solubility(ies) Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-octanol/

water

Not available

Not available. Auto-ignition temperature Decomposition temperature Not available. Viscosity Not available.

Explosive properties Not considered to be a product presenting a risk of explosion.

Oxidising properties Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

The product is stable. 10.2 Chemical stability

10.3 Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill,

grind or expose containers to heat or sources of ignition.

Reactive or incompatible with the following materials: 10.5 Incompatible materials

oxidizing materials

10.6 Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Article Number 29141578-2

Validation date 4 March 2016

Page: 6/11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methanol	LC50 Inhalation Gas. LC50 Inhalation Gas.	Rat Rat	145000 ppm	1 hours 4 hours
	LD50 Dermal	Rabbit	64000 ppm 15800 mg/kg	4 Hours
	LD50 Oral	Rat	5600 mg/kg	-
cobalt	LD50 Oral	Rat	1500 mg/kg	-

Conclusion/Summary Not available.

Acute toxicity estimates

Route	ATE value
Oral	10000 mg/kg
Dermal	30000 mg/kg
Inhalation (vapours)	300 mg/l

Irritation/Corrosion

Conclusion/Summary

Skin Repeated exposure may cause skin dryness or cracking.

Sensitisation

Conclusion/Summary Not available.

<u>Mutagenicity</u>

Conclusion/Summary Not available.

Carcinogenicity

Conclusion/Summary Not available.

Reproductive toxicity

Conclusion/Summary Not available.

Teratogenicity

Conclusion/Summary Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methanol	Category 1	Not determined	Not determined

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of Routes of entry anticipated: Oral, Dermal, Inhalation. **exposure**

Potential acute health effects

InhalationNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.Eye contactNo known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

InhalationNo specific data.IngestionNo specific data.Skin contactNo specific data.Eye contactNo specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects Not available.



Article Number

29141578-2



_

Validation date 4 March 2016

Version 2

Page: 7/11

Long term exposure

Potential delayed effects

Potential immediate effects Not available.

Potential delayed effects Not available.

Potential chronic health effects

Not available.

Conclusion/Summary Not available.

General No known significant effects or critical hazards. No known significant effects or critical hazards. Carcinogenicity Mutagenicity No known significant effects or critical hazards. No known significant effects or critical hazards. **Teratogenicity Developmental effects** No known significant effects or critical hazards. Fertility effects No known significant effects or critical hazards.

Not available

Other information Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
methanol	Acute LC50 100 mg/l Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Crangon crangon - Adult Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 48 hours 48 hours 96 hours
cobalt	Chronic NOEC 9.96 mg/l Marine water Acute LC50 4400 µg/l Acute LC50 3.4 mg/l Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Fish - Pimephales promelas	96 hours 48 hours 96 hours

Conclusion/Summary

12.2 Persistence and degradability

Conclusion/Summary Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
methanol	Fresh water 1 to 10 days	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
methanol cobalt	-0.77	<10 15600	low high

12.4 Mobility in soil

Soil/water partition coefficient (Koc) Not available.

Mobility Not available.

12.5 Results of PBT and vPvB assessment

PBT Not applicable. vPvB

12.6 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product



Article Number

29141578-2



Page: 8/11

Validation date 4 March 2016

MiTrap™ TALON® crude, 1 ml; part of 'Tagged package, His'

7

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental.

solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with

jurisdiction.

Hazardous waste Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as

defined by EU Directive 91/689/EEC.

European waste catalogue (EWC)

Waste code	Waste designation	
07 07 99	wastes not otherwise specified	

Packaging

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Waste packaging should be

recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautionsThis material and its container must be disposed of in a safe way. Care should be taken when handling

emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-		-
14.3 Transport hazard class(es)	-			-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information			-	Remarks IATA Special Provision A 58 - Aqueous solutions containing 24% or less alcohol by volume is not subject to these regulations.

14.6 Special precautions for

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.



Article Number

29141578-2



Page: 9/11

Validation date 4 March 2016

Not applicable

HiTrap™ TALON® crude, 1 ml; part of 'Tagged package, His'

manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Annex XVII - Restrictions on the

Other EU regulations

Europe inventory All components are listed or exempted.

Black List Chemicals Not listed **Priority List Chemicals** Not listed Integrated pollution prevention Not listed and control list (IPPC) - Air

Integrated pollution prevention

Not listed

and control list (IPPC) - Water

Seveso II Directive

This product is controlled under the Seveso II Directive.

Named substances

Name

methanol

Danger criteria

Category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

Chemical Weapons Convention List Schedule I Chemicals

Not listed

Not listed

Chemical Weapons Convention

List Schedule II Chemicals

Chemical Weapons Convention List Schedule III Chemicals

Not listed

15.2 Chemical Safety

This product contains substances for which Chemical Safety Assessments are still required.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data

Full text of abbreviated H	H225	Highly flammable liquid and vapour.
statements	H226	Flammable liquid and vapour.
	H301	Toxic if swallowed.
	H302	Harmful if swallowed.
	H311	Toxic in contact with skin.
	H317	May cause an allergic skin reaction.
	H331	Toxic if inhaled.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H370	Causes damage to organs.



Article Number

29141578-2

Validation date 4 March 2016

Version 2

Page: 10/11

29-0588-03

HiTrap™ TALON® crude, 1 ml; part of 'Tagged package, His'

Hull text of classifications (CLP/Acute Tox. 3, H301Acute Tox. 3, H311Acute Tox. 3, H331Acute Tox. 4, H302Acute Tox. 4,

Acute Tox. 3, H331 Acute Tox. 4, H302 Flam. Liq. 2, H225 Flam. Liq. 3, H226 Resp. Sens. 1, H334 Skin Sens. 1, H317 ACUTE TOXICITY: SKIN - Category 3
ACUTE TOXICITY: INHALATION - Category 3
ACUTE TOXICITY: INHALATION - Category 4
FLAMMABLE LIQUIDS - Category 2
FLAMMABLE LIQUIDS - Category 3
RESPIRATORY SENSITIZATION - Category 1
SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

STOT SE 1, H370

Date of printing 04 March 2016

Date of issue/ Date of revision 04 March 2016

Date of previous issue 11 December 2015

Version 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



Article Number 29141578-2

Page: 11/11

Validation date 4 March 2016