1-800-518-0364 / 1-450-973-9420
1-450-973-6373
www.ga-international.com
www.labtag.com | www.industritag.com

Product Data Sheet

Cryo-JetTAG™ - AJA Material
Cryogenic Labels for Inkjet Printers

Facestock Material:	Thermoplastic Film
Adhesive Type:	Permanent
Media Thickness:	8.3 mil ± 10%
Support Liner Thickness:	2.5 mil ± 10%
Finish:	Matte
Suggested Printing Method:	InkJet
Lower Temperature Resistance:	-196°C (-321°F)
Upper Temperature Resistance:	+90°C (+194°F)
Minimum Application Temperature:	-12°C (+10°F)
Storage Instructions:	Between +15°C and +25°C (+59°F to +77°F) at 50% RH, in original packaging
Compliance:	Please contact quality_assurance@ga-international.com for compliance and regulatory information.
Product Warranty:	Refer to our *Terms and Conditions* found on https://www.labtag.com/resources/terms-and-conditions/.

DOMINIQUE DUTSCHER SAS

The specifications provided herein are based on the information supplied by the primary material manufacturer (s) and tests conducted by GA International Inc. The end-user shall independently determine the suitability of the labels for the purpose for which they were purchased.

Last Update: November 3, 2026