HYDRANAL™Solver (Crude) oil

34697-1L

Version 1.12 Revision Date 09.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	:	HYDRANAL™Solver (Crude) oil
SDS-number	:	000000020642
Type of product	:	Mixture
Remarks	:	SDS according to Art. 31 of Regulation (EC) 1907/2006.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Laboratory chemicals
Uses advised against	:	none

1.3. Details of the supplier of the safety data sheet

Company	:	Honeywell Specialty Chemicals Seelze GmbH Wunstorfer Straße 40 30926 Seelze Germany	Solstice Advanced Materials US, Inc. 115 Tabor Road Morris Plains, NJ 07950-2546 USA
Telephone	:	(49) 5137-999 0	
For further information, please contact:	:	SafetyDataSheet@solstice.com	

1.4. Emergency telephone number

Emergency telephone number	:	+1-703-527-3887 (ChemTrec-Transport) +1 303-739-1378 (Medical)
	:	United Kingdom: (+44) 844 892 0111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Flammable liquids Category 2

H225 Highly flammable liquid and vapour.
Acute toxicity Category 4 - Oral
H302 Harmful if swallowed.
Acute toxicity Category 3 - Inhalation
H331 Toxic if inhaled.
Acute toxicity Category 4 - Dermal
H312 Harmful in contact with skin.
Skin irritation Category 2
H315 Causes skin irritation.
Eye irritation Category 2
H319 Causes serious eye irritation.
Carcinogenicity Category 2
H351 Suspected of causing cancer.
Reproductive toxicity Category 1B
H360D May damage the unborn child.
Specific target organ toxicity - single exposure Category 1
H370 Causes damage to organs.
Specific target organ toxicity - single exposure Category 3 - Respiratory system
H335 May cause respiratory irritation.
Specific target organ toxicity - single exposure Category 3
H336 May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure Category 1
H372 Causes damage to organs through prolonged or repeated exposure if swallowed and inhaled.
Aspiration hazard Category 1
H304 May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard Category 3
H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

REGULATION (EC) No 1272/2008

Hazard pictograms :



Signal word : Danger

Hazard statements :

H225	Highly flammable liquid and vapour.
H302 + H312 + H332	Harmful if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

		H335	May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.
		H351	Suspected of causing cancer.
		H360D	May damage the unborn child.
		H370	Causes damage to organs.
		H372	Causes damage to organs through prolonged or repeated exposure if swallowed and inhaled.
		H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
		P280	Wear protective gloves/protective clothing/eye protection/face protection.
		P284	In case of inadequate ventilation wear respiratory protection.
		P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
		P302 + P352	IF ON SKIN: Wash with plenty of water.
		P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
		P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
		P308 + P313	IF exposed or concerned: Get medical advice/ attention.

Hazardous components which must be listed on the label	:	Xylene (mixture of isomers) trichloromethane methanol imidazole sulfur dioxide
Special labelling of certain products:	:	Restricted to professional users.

2.3. Other hazards

Avoid exposure - obtain special instructions before use. Do not breathe vapours or spray mist.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical name	CAS-No. Index-No. EC-No.	Classification 1272/2008	Concentration	Remarks
o-xylene	95-47-6 601-022-00-9 202-422-2	Flam. Liq. 3; H226 Acute Tox. 4; H332; Inhalation Acute Tox. 4; H312; Dermal Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 30 % - <= 60 %	
trichloromethane	67-66-3 602-006-00-4 200-663-8	Acute Tox. 4; H302; Oral Acute Tox. 3; H331; Inhalation Skin Irrit. 2; H315 Eye Irrit. 2; H319 Carc. 2; H351 Repr. 2; H361d STOT RE 1; H372 STOT SE 3; H336	>= 20 % - <= 50 %	
methanol	67-56-1 603-001-00-X 200-659-6	Flam. Liq. 2; H225 Acute Tox. 3; H331; Inhalation Acute Tox. 3; H311; Dermal Acute Tox. 3; H301; Oral STOT SE 1; H370	>= 15 % - <= 20 %	STOT SE 1; H370:>= 10 % STOT SE 2; H371:3 - < 10 % STOT SE 2; H371:3 - < 10 % STOT SE 1; H370:>= 10 %
imidazole	288-32-4 613-319-00-0 206-019-2	Acute Tox. 4; H302; Oral Skin Corr. 1C; H314 Eye Dam. 1; H318 Repr. 1B; H360D	>= 1 % - <= 10 %	
sulfur dioxide	7446-09-5	Press. Gas Liquefied gas;	>= 1 % - <= 5 %	

	016-011-00-9 231-195-2	H280 Acute Tox. 3; H331; Inhalation Skin Corr. 1B; H314 STOT SE 1; H370; Inhalation; Respiratory system		ATE(inhalative gas): 1000 ppm

Remaining components of this product are non-hazardous and/or are present at concentrations below reportable limits.

Occupational Exposure Limit(s), if available, are listed in Section 8.
For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice:
First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

Inhalation:
Remove to fresh air. Keep patient warm and at rest. Call a physician immediately.

Skin contact:
Wash off immediately with plenty of water. If skin irritation persists, call a physician.

Eye contact:
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Protect unharmed eye.

Ingestion:
When swallowed, allow water to be drunk. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

See Section 11 for more detailed information on health effects and symptoms. :

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical

Extinguishing media which shall not be used for safety reasons:
Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO2)
Phosgene
Nitrogen oxides (NOx)
Sulphur oxides
Hydrogen chloride gas

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Wear personal protective equipment. Unprotected persons must be kept away. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material.
Pick for disposal in tightly closed containers

6.4. Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling:
Wear personal protective equipment. Use only in well-ventilated areas.

Advice on protection against fire and explosion:
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. The heavy vapours can overcome a considerable distance up to the source of ignition. Vapours may form explosive mixtures with air.

Hygiene measures:
Take off all contaminated clothing immediately. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions:
Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from atmospheric moisture and water.

7.3. Specific end use(s)

no additional data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

Components	Basis / Value type	Value / Form of exposure	Exceeding Factor	Remarks
o-xylene	EU ELV SKIN_DES			Can be absorbed through the skin.
o-xylene	EH40 WEL			Listed
o-xylene	EU ELV TWA	221 mg/m3 50 ppm		Indicative
o-xylene	EU ELV STEL	442 mg/m3 100 ppm		Indicative
o-xylene	EU SCOELS TWA	221 mg/m3 50 ppm	8 hours	
o-xylene	EU SCOELS SKIN_DES			Can be absorbed through the skin.
o-xylene	EU SCOELS STEL	442 mg/m3 100 ppm	15 minutes	
o-xylene	EH40 WEL TWA	220 mg/m3 50 ppm		
o-xylene	EH40 WEL STEL	441 mg/m3 100 ppm	15 minutes	
o-xylene	EH40 WEL SKIN_DES			Can be absorbed through the skin.
o-xylene	EU ELV SKIN_DES			Can be absorbed through the skin.

trichloromethane	EH40 WEL			Listed
trichloromethane	EH40 WEL SKIN_DES			Can be absorbed through the skin.
trichloromethane	EH40 WEL TWA	9,9 mg/m3 2 ppm		
trichloromethane	EU ELV TWA	10 mg/m3 2 ppm		Indicative
trichloromethane	EU SCOELS SKIN_DES			Can be absorbed through the skin.
trichloromethane	EU SCOELS TWA	10 mg/m3 2 ppm	8 hours	
trichloromethane	EU ELV SKIN_DES			Can be absorbed through the skin.
methanol	EH40 WEL SKIN_DES			Can be absorbed through the skin.
methanol	EH40 WEL TWA	266 mg/m3 200 ppm		
methanol	EU ELV TWA	260 mg/m3 200 ppm		Indicative
methanol	EH40 WEL STEL	333 mg/m3 250 ppm	15 minutes	
methanol	EU ELV SKIN_DES			Can be absorbed through the skin.

EU ELV - EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended
SKIN_DES - Skin designation:
EH40 WEL - UK. EH40 Workplace Exposure Limits (WELs), as amended
-
EU ELV - EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended
TWA - Time weighted average
EU ELV - EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended
STEL - Short term exposure limit

DNEL/ PNEC-Values

Component	End-use/impact	Exposure duration	Value	Exposure routes	Remarks
o-xylene	Workers / Long-term systemic		221 mg/m3	Inhalation	

	effects				
o-xylene	Workers / Acute systemic effects		442 mg/m3	Inhalation	
o-xylene	Workers / Long-term local effects		221 mg/m3	Inhalation	
o-xylene	Workers / Acute local effects		442 mg/m3	Inhalation	
o-xylene	Workers / Long-term systemic effects		3182mg/kg bw/d	Skin contact	
o-xylene	Consumers / Long-term systemic effects		65,3 mg/m3	Inhalation	
o-xylene	Consumers / Acute systemic effects		260 mg/m3	Inhalation	
o-xylene	Consumers / Long-term local effects		65,3 mg/m3	Inhalation	
o-xylene	Consumers / Acute local effects		260 mg/m3	Inhalation	
o-xylene	Consumers / Long-term systemic effects		1872mg/kg bw/d	Skin contact	
o-xylene	Consumers / Long-term systemic effects		12,5mg/kg bw/d	Ingestion	
trichloromethane	Workers / Long-term systemic effects		2,5 mg/m3	Inhalation	

trichloromethane	Workers / Acute systemic effects		333 mg/m3	Inhalation	
trichloromethane	Workers / Long-term local effects		2,5 mg/m3	Inhalation	
trichloromethane	Workers / Long-term systemic effects		0,94mg/kg bw/d	Skin contact	
trichloromethane	Consumers / Long-term systemic effects		0,18 mg/m3	Inhalation	
methanol	Consumers / Acute systemic effects		4mg/kg bw/d	Skin contact	
methanol	Workers / Acute systemic effects		20mg/kg bw/d	Skin contact	
methanol	Consumers / Long-term systemic effects		4mg/kg bw/d	Skin contact	
methanol	Workers / Long-term systemic effects		20mg/kg bw/d	Skin contact	
methanol	Consumers / Acute local effects		26 mg/m3	Inhalation	
methanol	Workers / Acute local effects		130 mg/m3	Inhalation	
methanol	Consumers / Acute systemic effects		26 mg/m3	Inhalation	
methanol	Workers /		130 mg/m3	Inhalation	

	Acute systemic effects				
methanol	Consumers / Long-term local effects		26 mg/m3	Inhalation	
methanol	Workers / Long-term local effects		130 mg/m3	Inhalation	
methanol	Consumers / Long-term systemic effects		26 mg/m3	Inhalation	
methanol	Workers / Long-term systemic effects		130 mg/m3	Inhalation	
methanol	Consumers / Acute systemic effects		4mg/kg bw/d	Ingestion	
methanol	Consumers / Long-term systemic effects		4mg/kg bw/d	Ingestion	
imidazole	Workers / Long-term systemic effects		10,6 mg/m3	Inhalation	
imidazole	Workers / Long-term systemic effects		1,5mg/kg bw/d	Skin contact	
sulfur dioxide	Workers / Long-term local effects		1,3 mg/m3	Inhalation	
sulfur dioxide	Workers / Acute local effects		2,7 mg/m3	Inhalation	
sulfur dioxide	Consumers / Long-term local effects		0,53 mg/m3	Inhalation	

Component	Environmental compartment / Value	Remarks
o-xylene	Fresh water: 0,25 mg/l	
o-xylene	Marine water: 0,25 mg/l	
o-xylene	Sewage treatment plant: 5 mg/l	
o-xylene	Fresh water sediment: 14,33 mg/kg dw	
o-xylene	Marine sediment: 14,33 mg/kg dw	
o-xylene	Soil: 2,41 mg/kg dw	
trichloromethane	Fresh water: 0,146 mg/l	Assessment factor: 10
trichloromethane	Marine water: 0,015 mg/l	Assessment factor: 100
trichloromethane	Sewage treatment plant: 0,048 mg/l	Assessment factor: 10
trichloromethane	Fresh water sediment: 0,45 mg/kg dw	Assessment factor: 10
trichloromethane	Marine sediment: 0,09 mg/kg dw	Assessment factor: 50
trichloromethane	Soil: 0,56 mg/kg dw	
methanol	Sewage treatment plant: 100 mg/l	
methanol	Fresh water: 20,8 mg/l	Assessment factor: 10
methanol	Marine water: 2,08 mg/l	Assessment factor: 100
methanol	Fresh water sediment: 77 mg/kg	
methanol	Marine sediment: 7,7 mg/kg	
methanol	Soil: 100 mg/kg	Assessment factor: 100
imidazole	Fresh water: 0,13 mg/l	Assessment factor: 1000

imidazole	Marine sediment: 0,034 mg/l	Assessment factor: 10000
imidazole	Sewage treatment plant: 10 mg/l	Assessment factor: 100
imidazole	Fresh water sediment: 0,336 mg/kg dw	
imidazole	Marine sediment: 0,034 mg/kg dw	
imidazole	Soil: 0,0425 mg/kg dw	
sulfur dioxide	:	No data available

8.2. Exposure controls

Occupational exposure controls

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345.
Avoid exposure - obtain special instructions before use.

Engineering measures
Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.

Personal protective equipment
Respiratory protection:
In case of insufficient ventilation wear suitable respiratory equipment.

Hand protection:
Glove material: Viton®
Gloves must be inspected prior to use.
Replace when worn.
Remarks:Due to varying conditions (e.g.temperature or other strains) it must be considered that the usage of a chemical protective glove in practice may be much shorter than the permeation time determined in accordance with EN 374.
Since actual conditions of practical use often deviate from standardised conditions according EN 374 the glove manufacturer reccomends to use the chemical protective glove in practice not longer than 50% of the recomended permeation time.
Manufacturer´s directions for use should be observed because of great diversity of types .

Eye protection:
Safety goggles

Skin and body protection:
Protective suit

Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(a) Physical state	:	liquid
(b) Colour	:	colourless
(c) Odour	:	aromatic
(d) Melting point/freezing point	:	No data available
(e) Boiling point/boiling range	:	57 °C at 1.013 hPa
(h) Flash point	:	6,00 °C closed cup
(i) Auto-ignition temperature	:	No data available
(j) Decomposition temperature	:	No decomposition if used as directed.
(k) pH	:	6,0 - 7,0 at 20 °C
(l) Viscosity, kinematic	:	No data available
(m) Solubility(ies)	:	Water solubility: partly soluble
(n) Partition coefficient: n-	:	No data available

octanol/water

(o) Vapour pressure	:	No data available
(p) Density and / or relative density	:	1,013 g/cm3 at 20 °C
(q) Relative vapour density	:	No data available
(r) Particle characteristics	:	No data available

9.2 Other Information

Polymer characteristics	:	No data available
Evaporation rate	:	No data available
Viscosity, dynamic	:	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage conditions.

10.2. Chemical stability

No decomposition if used as directed.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.
Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Protect from atmospheric moisture and water.
Heat, flames and sparks.

10.5. Incompatible materials

Strong bases
Acids
Oxidizing agents
Alkali metals
Acid chlorides
Acid anhydrides
Reducing agents

10.6. Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO2)
Phosgene
Nitrogen oxides (NOx)
Sulphur oxides
Hydrogen chloride gas

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) Acute toxicity

Acute oral toxicity:
No data available

Acute dermal toxicity:
No data available

Acute inhalation toxicity:
No data available

Acute toxicity (other routes of administration):
No data available

(b) Skin corrosion/irritation:
No data available

(c) Serious eye damage/eye irritation:
No data available

(d) Respiratory or skin sensitisation:
No data available

(h) STOT-single exposure:
No data available

(i) STOT - repeated exposure:
No data available

(j) Aspiration hazard:
No data available

11.2. Information on other hazards

Endocrine disrupting properties
No data available

Other information:
No data available

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish:
No data available

Toxicity to aquatic plants:
No data available

Toxicity to aquatic invertebrates:
No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product:
Dispose according to legal requirements.

Packaging:
Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

Further information:
Provisions relating to waste:
EC Directive 2006/12/EC; 2008/98/EEC
Regulation No. 1013/2006
For personal protection see section 8.

SECTION 14: Transport information

14.1 UN number or ID number
ADR/RID:1992 IMDG:1992 IATA:1992

14.2 UN proper shipping name
ADR/RID:FLAMMABLE LIQUID, TOXIC, N.O.S.(METHANOL, CHLOROFORM, XYLENE)
IMDG:FLAMMABLE LIQUID, TOXIC, N.O.S.(METHANOL,CHLOROFORM,XYLENE)
IATA:Flammable liquid, toxic, n.o.s.(Methanol, Chloroform, Xylene)

14.3 Transport hazard class(es)
ADR/RID:3 (6.1) IMDG: 3 (6.1) IATA: 3 (6.1)

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards
ADR/RID: no Marine pollutant: no

14.6 Special precautions for user
IMDG Code segregation group (SGG10) – Liquid halogenated hydrocarbons,

14.7 Maritime transport in bulk according to IMO instruments
No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Basis	Value	Remarks
Regulation (EC) No. 1907/2006, Annex XVII		This product contains an ingredient according to Annex XVII of the REACH Regulation1907/2006/EC.
Substances of very high concern (SVHC)		This product does not contain substances of very high concern according to Regulation (EC) No Article 57 above the respective regulatory 1907/2006 (REACH), concentration limit of ≥ 0.1 % (w/w).

Other inventory information

USA. List of Active Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended
On TSCA Inventory

Australia. Inventory of Industrial Chemicals (AIIC), as amended
On the inventory, or in compliance with the inventory

Canada. Domestic Substances List (DSL), as amended
All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List

On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)
On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS)
On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC)
On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand
On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI)
On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Text of H-statements referred to under heading 3

o-xylene	:	H226	Flammable liquid and vapour.
		H332	Harmful if inhaled.
		H312	Harmful in contact with skin.
		H315	Causes skin irritation.
		H319	Causes serious eye irritation.
		H335	May cause respiratory irritation.
		H304	May be fatal if swallowed and enters airways.
		H412	Harmful to aquatic life with long lasting effects.
trichloromethane	:	H302	Harmful if swallowed.
		H331	Toxic if inhaled.

		H315	Causes skin irritation.
		H319	Causes serious eye irritation.
		H351	Suspected of causing cancer.
		H361d	Suspected of damaging the unborn child.
		H372	Causes damage to organs through prolonged or repeated exposure if swallowed and inhaled.
		H336	May cause drowsiness or dizziness.
methanol	:	H225	Highly flammable liquid and vapour.
		H331	Toxic if inhaled.
		H311	Toxic in contact with skin.
		H301	Toxic if swallowed.
		H370	Causes damage to organs.
imidazole	:	H302	Harmful if swallowed.
		H314	Causes severe skin burns and eye damage.
		H318	Causes serious eye damage.
		H360D	May damage the unborn child.
sulfur dioxide	:	H280	Contains gas under pressure; may explode if heated.
		H331	Toxic if inhaled.
		H314	Causes severe skin burns and eye damage.
		H370	Causes damage to organs.

Further information

All directives and regulations refer to amended versions.
Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

Abbreviations:
EC European Community
CAS Chemical Abstracts Service
DNEL Derived no effect level
PNEC Predicted no effect level

vPvB Very persistent and very biaccumulative substance
PBT Persistent, bioaccmulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.
This information should not constitute a guarantee for any specific product properties.
This document is not a UK REACH-compliant SDS, and the Great Britain importer bears full responsibility for UK REACH compliance. This document is provided to assist the Great Britain importers in ensuring their own compliance.