

TECHNICAL SPECIFICATIONS

Trade name	Spare vaccum retention valve
Use	Vacuum retention valve for desiccators codes 550-230-554
Material	PC with PE needle

DIMENSIONAL SPECIFICATIONS

Ext. Ø tubing connection	8.10mm ±0.2
---------------------------------	-------------

**GENERAL FEATURES**

CE mark	NO
Autoclavability	YES
Sterile	NO
Food contact suitability of the raw material	YES

CHEMICAL RESISTANCE of PC

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
Inorganic acid	Sulphuric acid	98	C	-	-
Organic acid	Benzoic acid	100	A	B	B
Alcohol	Ethanol	100	A	B	B
Aldehydes	Acetaldehyde	100	B	C	
Inorganic alkali	Sodium hydroxide	50	B	B	C
Organic alkali	Aniline	100	C	-	-
Ketone	Acetone	100	C	-	-
Esther	Ethyl acetate	100	C	-	-
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	-	-	-
Hydrocarbons, linear	Hexane	100	-	-	-
Supersolvent	Tetrahydrofuran	100	-	-	-

Legenda (not applicable if neglected):

- **A: fair resistance;** exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistance;** exposure causes damage of poor importance, which sometimes is only temporary.
- **C: poor resistance;** exposure to chemical is not allowed or causes immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing.

PACKAGING

Case	1000 pcs
Pack	5 pcs

Quality Assurance

This paper is an electronic print-out: signature is not requested