Kartell SpA DIVISIONE LABWARE	TECHNICAL DATA SHEET ITEM 2602	Mod. AQ 001 Rev. 0 del 25/09/2003

TECHNICAL SPECIFICATIONS

Trade name	Sample cup
Use	Sample cup for Enzymun-Test System Boehringer ES 300® and ES 600®
Material	Polystyrene PS

DIMENSIONAL SPECIFICATIONS

Height	mm. 40,00 +/- 0,10
Base, diameter	mm. 11,00 +/- 0,05
Mouth, diameter	mm. 12,10 +/- 0,05
Drawing	Upon motivated request
Graduated, capacity	ml. 0,5 - 1,00 - 1,50 - 2,00

GENERAL FEATURES

CE mark	Yes
Autoclavability	No
Sterilization	To be effected by radiations
Food contact suitable	Yes

CHEMICAL RESISTANCE

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
Inorganic acid	Sulphuric acid	98	C	-	-
Organic acid	Benzoic acid	100	B	B	B
Alcohol	Ethanol	100	B	C	-
Aldehydes	Acetaldehyde	100	C	-	-
Inorganic alkali	Sodium hydroxide	50	A	A	A
Organic alkali	Aniline	100	C	-	-
Ketone	Acetone	100	-	-	-
Esther	Ethyl acetate	100	C	-	-
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	C	-	-
Hydrocarbons, linear	Hexane	100	C	-	-
Supersolvent	Tetrahydrofuran	100	C	-	-

Legenda (not applicable if neglected):

- **A: fair resistence;** exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistence;** exposure causes damage of poor importance, which sometimes is only temponary.
- **C: poor resistence;** exposure to chemical is not allowed, or cases immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing..

PACKAGING

Bag	Pz. 500
Case	Pz. 6000

DOMINIQUE DUTSCHER SAS

Quality Assurance — Massimiliano Capitanio

Technical Direction — Guido Borona

This paper is an electronic print-out: signature is not requested